

22-0-22

High K Fall

Blend # 16156

A 15.4% SLOW RELEASE NITROGEN FERTILIZER THAT CONTAINS 4.4% SLOW RELEASE NITROGEN FROM XCU and 11% SLOW RELEASE NITROGEN FROM XRT.

22-0-22 High K Fall:

- An effective ratio of Nitrogen, Potash, and Iron.
- **4.4%** of the Total Nitrogen is Slow Release Nitrogen from Polymer Coated Sulfur Coated Urea (XCU) and **11%** of the Total Nitrogen is Slow Release Nitrogen from Polymer Coated Urea (XRT 90 Day).
- 5% Iron for a deep green look.
- **15.4%** of the total Nitrogen is controlled released, to provide over 12 weeks of Nitrogen release.
- An excellent choice for schools, golf courses, homes (Professional lawn care), etc.,

APPLICATION RATES:

| | Pounds of Actual Nitrogen desired per 1,000 sq.ft. | Pounds of 22-0-22 to apply per 1,000 sq.ft. | Pounds of 22-0-22 to apply per Acre |
|--------------------------|--|---|---|
| Turfgrass: | 0.75..... | 3.4 | 148 |
| <i>*Recommended Rate</i> | 1.00..... | 4.5 | 196 |
| | 1.50*..... | 6.8* | 296* |

XRTTM
Extended Release Fertilizer Technology

PREPLANT: Broadcast 7½ lbs. per 1,000 sq. ft. (327 lbs. per acre)

GROUND COVER: Broadcast at 5 lbs. per 1,000 sq. ft. (½ lb. per 100 sq. ft.)

SHRUBS & EVERGREENS: Sprinkle ¼ cup evenly around dripline of plant and work into top 1 inch of soil.

TREES: Apply ½ lb. per 1 inch of trunk diameter. Distribute evenly under branches out to dripline.

NOTE: Liquid measuring cups are very close in estimating the weight of dry granular fertilizer.

Example: An 8 oz. (1 cup) measuring cup holds approximately 8 oz. of dry granular fertilizer.

PRODUCT COVERAGE: ONE-50 LB. BAG COVERS 7,300 SQ. FT.
SIX-50 LB. BAGS COVER 1 ACRE.

XCUTM
Slow-Release Fertilizer

SPREADER SETTINGS: Scotts R-8A..... O1/2

Listed Settings Will

Earthway..... 17

Approximately Apply the

Lesco..... 18

Recommended Rate.

NOTE: Spreader settings are guidelines only. Spreaders should be checked for accuracy.

APPLICATION PRECAUTIONS:

- Plant nutrients can cause staining of sidewalks. Sweep walkways prior to irrigation. Walkways should be dry at time of application.
- Keep away from pools, ponds, etc. Do not contaminate potable water.
- Do not apply with a drop-type spreader. The grinding action of these spreaders can damage the coating of the polymer coated sulfur-coated urea and will increase the burn potential.

GUARANTEED ANALYSIS:

TOTAL NITROGEN (N).....22.00%

21.65% Urea Nitrogen*

0.35% Water Insoluble Nitrogen

SOLUBLE POTASH (K₂O).....22.00%

Iron (Fe).....5.00%

Derived from Polymer Coated Sulfur Coated Urea, Polymer Coated Urea, Urea, Biosolids, Iron Oxide and Muriate of Potash.

*4.40% Slow Release Urea Nitrogen from Polymer Coated Sulfur Coated Urea (XCU)

*11.00% Slow Release Urea Nitrogen from Polymer Coated Urea (XRT)

Information regarding the contents and levels of metals in this product is available on the Internet at <http://www.aapfco.org/metals.htm>

PACKAGE SIZE: 50-LB. (22.68-Kg.) BAGS

HANDLING PRECAUTIONS:

CAUTION: KEEP OUT OF REACH OF CHILDREN

MAS * PO BOX 732 * NEWBERG, OR 97132