

22-0-8

High Iron

Blend # 16536

22-0-8 High Iron:

- An effective ratio of Nitrogen, Potash, and Iron.
- 11% of the Total Nitrogen is Slow Release Nitrogen from Polymer Coated Sulfur Coated Urea (XCU).
- 6.5% Iron for a deep green look.
- An excellent choice for schools, golf courses, homes (Professional lawn care), etc.,

APPLICATION RATES:

	Pounds of Actual Nitrogen desired per 1,000 sq.ft.	Pounds of 22-0-8 to apply per 1,000 sq.ft.	Pounds of 22-0-8 to apply per Acre
Turfgrass:	0.75.....	3.4.....	148
<i>*Recommended Rate</i>	1.00.....	4.5.....	196
	1.50*.....	6.8*.....	296*



PREPLANT: Broadcast 7½ lbs. per 1,000 sq. ft. (327 lbs. per acre)

GROUND COVER: Broadcast at 5 lbs. per 1,000 sq. ft. (½ lb. per 100 sq. ft.)

SHRUBS & EVERGREENS: Sprinkle ¼ cup evenly around dripline of plant and work into top 1 inch of soil.

TREES: Apply ½ lb. per 1 inch of trunk diameter. Distribute evenly under branches out to dripline.

NOTE: Liquid measuring cups are very close in estimating the weight of dry granular fertilizer.

Example: An 8 oz. (1 cup) measuring cup holds approximately 8 oz. of dry granular fertilizer.

**PRODUCT COVERAGE: ONE-50 LB. BAG COVERS 7,300 SQ. FT.
SIX-50 LB. BAGS COVER 1 ACRE.**

SPREADER SETTINGS: Scotts R-8A..... O1/2

Listed Settings Will Earthway..... 17

Approximately Apply the Lesco..... 18

Recommended Rate.

NOTE: Spreader settings are guidelines only. Spreaders should be checked for accuracy

APPLICATION PRECAUTIONS:

- Plant nutrients can cause staining of sidewalks. Sweep walkways prior to irrigation. Walkways should be dry at time of application.
- Keep away from pools, ponds, etc. Do not contaminate potable water.
- Do not apply with a drop-type spreader. The grinding action of these spreaders can damage the coating of the polymer coated sulfur-coated urea and will increase the burn potential.

GUARANTEED ANALYSIS:

TOTAL NITROGEN (N).....	22.00%
22.00% Urea Nitrogen*	
SOLUBLE POTASH (K ₂ O).....	8.00%
Calcium (Ca).....	8.85%
Sulfur (S).....	1.02%
Iron (Fe).....	6.50%

Derived from Polymer Coated Sulfur Coated Urea, Urea, Pelletized Limestone, Iron Oxide and Muriate of Potash.

*11.00% Slow Release Urea Nitrogen from Polymer Coated Sulfur Coated Urea (XCU)

Information regarding the contents and levels of metals in this product is available on the Internet at <http://www.aapfco.org/metals.htm>

PACKAGE SIZE: 50-LB. (22.68-Kg.)BAGS

HANDLING PRECAUTIONS: CAUTION: KEEP OUT OF REACH OF CHILDREN

MAS * PO BOX 732 * NEWBERG, OR 97132