

22-5-5

ECO PRIDE

A 11% SLOW RELEASE NITROGEN FERTILIZER THAT CONTAINS 5.5% SLOW RELEASE NITROGEN FROM XCU and 5.5% SLOW RELEASE NITROGEN FROM XRT.

22-5-5 ECO PRIDE:

- An effective ratio of Nitrogen, Phosphate, Potash, and Sulfur.
- 5.5% Slow Release Nitrogen from Polymer Coated Sulfur Coated Urea (XCU) and 5.5% Slow Release Nitrogen from Polymer Coated Urea (XRT 90 Day).
- 2% Iron for a deep green look.
- Half of the Total Nitrogen is controlled released, to provide over 12 weeks of Nitrogen release.
- An excellent choice for schools, golf courses, homes (Professional lawn care), etc.,

APPLICATION RATES:

	Pounds of Actual Nitrogen desired per 1,000 sq.ft.	Pounds of 22-5-5 to apply per 1,000 sq.ft.	Pounds of 22-5-5 to apply per Acre
Turfgrass:	0.75.....	3.4.....	148
<i>*Recommended Rate</i>	1.00.....	4.5.....	.196
	1.50*.....	6.8*.....	.296*



PREPLANT: Broadcast 7½ lbs. per 1,000 sq. ft. (325 lbs. per acre)
GROUND COVER: Broadcast at 5 lbs. per 1,000 sq. ft. (½ lb. per 100 sq. ft.)
SHRUBS & EVERGREENS: Sprinkle ¼ cup evenly around dripline of plant and work into top 1 inch of soil.
TREES: Apply ½ lb. per 1 inch of trunk diameter. Distribute evenly under branches out to dripline.
NOTE: Liquid measuring cups are very close in estimating the weight of dry granular fertilizer.
 Example: An 8 oz. (1 cup) measuring cup holds approximately 8 oz. of dry granular fertilizer.



PRODUCT COVERAGE: *ONE-50 LB. BAG COVERS 7,300 SQ. FT.
 SIX-50 LB. BAGS COVER 1 ACRE.

SPREADER SETTINGS: Scotts R-8A..... O1/2
 Listed Settings Will Earthway..... 17
 Approximately Apply the Lesco..... 18
 Recommended Rate.
NOTE: Spreader settings are guidelines only. Spreaders should be checked for accuracy.

APPLICATION PRECAUTIONS:

- Plant nutrients can cause staining of sidewalks. Sweep walkways prior to irrigation. Walkways should be dry at time of application.
- Keep away from pools, ponds, etc. Do not contaminate potable water.
- Do not apply with a drop-type spreader. The grinding action of these spreaders can damage the coating of the polymer coated sulfur-coated urea and will increase the burn potential.

GUARANTEED ANALYSIS:

TOTAL NITROGEN (N).....	22.00%
0.58% Ammoniacal Nitrogen	
19.49% Urea Nitrogen*	
1.93% Water Insoluble Nitrogen**	
AVAILABLE PHOSPHATE (P ₂ O ₅).....	5.00%
SOLUBLE POTASH (K ₂ O).....	5.00%
Sulfur (S).....	7.00%
Iron (Fe).....	2.00%
Derived from Polymer Coated Sulfur Coated Urea, Polymer Coated Urea, Urea, Monoammonium Phosphate, Biosolids, Elemental Sulfur, Iron Oxide and Muriate of Potash.	
*5.50% Slow Release Urea Nitrogen from Polymer Coated Sulfur Coated Urea (XCU)	
*5.50% Slow Release Urea Nitrogen from Polymer Coated Urea (XRT)	
**1.93% Slowly Available Water Insoluble Nitrogen from Biosolids	

Information regarding the contents and levels of metals in this product is available on the Internet at <http://www.aapfco.org/metals.htm>

PACKAGE SIZE: 50-LB. (22.68-Kg.)BAGS

HANDLING PRECAUTIONS: CAUTION: KEEP OUT OF REACH OF CHILDREN