

24-2-4

A 16.8% SLOW RELEASE NITROGEN FERTILIZER THAT CONTAINS 8.4% SLOW RELEASE NITROGEN FROM XCU and 8.4% SLOW RELEASE NITROGEN FROM XRT.

24-2-4 Provides:

- An effective ratio of Nitrogen, Phosphate, Potash, and Sulfur.
- 8.4% Slow Release Nitrogen from Polymer Coated Sulfur Coated Urea (XCU) and 8.4% Slow Release Nitrogen from Polymer Coated Urea (XRT 90 Day).
- 16.8% of the total Nitrogen is controlled released, to provide over 12 weeks of Nitrogen release.
- An excellent choice for schools, golf courses, homes (Professional lawn care), etc.,

APPLICATION RATES:

	Pounds of Actual Nitrogen desired per 1,000 sq.ft.	Pounds of 24-2-4 to apply per 1,000 sq.ft.	Pounds of 24-2-4 to apply per Acre
Turfgrass:	0.75.....	3.1	135
<i>*Recommended Rate</i>	1.00.....	4.2	183
	1.50*.....	6.3*	274*

XRT[™]
Extended Release Fertilizer Technology

PREPLANT: Broadcast 7½ lbs. per 1,000 sq. ft. (325 lbs. per acre)

GROUND COVER: Broadcast at 5 lbs. per 1,000 sq. ft. (½ lb. per 100 sq. ft.)

SHRUBS & EVERGREENS: Sprinkle ¼ cup evenly around dripline of plant and work into top 1 inch of soil.

TREES: Apply ½ lb. per 1 inch of trunk diameter. Distribute evenly under branches out to dripline.

NOTE: Liquid measuring cups are very close in estimating the weight of dry granular fertilizer.

Example: An 8 oz. (1 cup) measuring cup holds approximately 8 oz. of dry granular fertilizer.

PRODUCT COVERAGE: *ONE-50 LB. BAG COVERS 7,300 SQ. FT.
SIX-50 LB. BAGS COVER 1 ACRE.

XCU[™]
Slow-Release Fertilizer

SPREADER SETTINGS: Scotts R-8A..... O1/2

Listed Settings Will Earthway..... 17

Approximately Apply the Lesco..... 18

Recommended Rate.

NOTE: Spreader settings are guidelines only. Spreaders should be checked for accuracy.

APPLICATION PRECAUTIONS:

- Plant nutrients can cause staining of sidewalks. Sweep walkways prior to irrigation. Walkways should be dry at time of application.
- Keep away from pools, ponds, etc. Do not contaminate potable water.
- Do not apply with a drop-type spreader. The grinding action of these spreaders can damage the coating of the polymer coated sulfur-coated urea and will increase the burn potential.

GUARANTEED ANALYSIS:

TOTAL NITROGEN (N).....	24.00%
4.97% Ammoniacal Nitrogen	
17.25% Urea Nitrogen*	
1.78% Water Insoluble Nitrogen**	
AVAILABLE PHOSPHATE (P ₂ O ₅).....	2.00%
SOLUBLE POTASH (K ₂ O).....	4.00%
Sulfur (S)	6.60%

Derived from Polymer Coated Sulfur Coated Urea, Polymer Coated Urea, Urea, Ammonium Sulfate, Biosolids, and Muriate of Potash.

*8.40% Slow Release Urea Nitrogen from Polymer Coated Sulfur Coated Urea (XCU)

*8.40% Slow Release Urea Nitrogen from Polymer Coated Urea (XRT)

**1.78% Slowly Available Water Insoluble Nitrogen from Biosolids (SoundGro).

Information regarding the contents and levels of metals in this product is available on the Internet at <http://www.aapfco.org/metals.htm>

PACKAGE SIZE: 50-LB. (22.68-Kg.)BAGS

HANDLING PRECAUTIONS: CAUTION: KEEP OUT OF REACH OF CHILDREN