SAFETY DATA SHEET

AWAKEN®



Section 1. Identification

Product identifier : AWAKEN®

SDS# : 465

Other means of : AWAKEN® 16-0-2 identification

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Fertilizer.

Uses advised against

Not available.

Supplier's details : LOVELAND PRODUCTS, INC.

P.O. Box 1286

Greeley, CO 80632-1286

: 1-888-574-2878 (Customer Service) Telephone no.

Email : retail-SDS2@nutrien.com

Emergency telephone

number (with hours of

operation)

: CHEMTREC: 1-800-424-9300 (24 hrs)

Medical Emergencies: 1-866-944-8565 (24 hrs)

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Classification of the substance or mixture : SERIOUS EYE DAMAGE - Category 1

GHS label elements

Hazard pictograms



Signal word : Danger

Hazard statements : Causes serious eye damage.

Precautionary statements

: Read label before use. Keep out of reach of children. If medical advice is needed, have General

product container or label at hand.

Prevention : Wear eye or face protection.

Response : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Immediately call a POISON CENTER or

doctor.

: Not applicable. **Storage Disposal** : Not applicable.

Hazards not otherwise

classified

: None known.

Date of issue/Date of revision : 5/17/2023 : 5/17/2023 Version : 1.1 1/13 Date of previous issue

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	%	CAS number
	10 - 20 5 - 10	6484-52-2 557-34-6

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact : CORROS

: CORROSIVE. Begin eye irrigation immediately. All eye exposures require medical evaluation following decontamination. Immediately rinse eyes with large quantities of water or saline for a minimum 30 minutes, longer irrigation time is preferred if possible. If possible, remove contact lenses being careful not to cause additional eye damage. If the initial water supply is insufficient, keep the affected area wet with a moist cloth and transfer the person to the nearest place where rinsing can be continued for the recommended length of time. Call an ambulance for transport to hospital. Continue eye irrigation during transport. For additional advice call the medical emergency number on this safety data sheet or your poison center or doctor.

Inhalation

: Remove person to fresh air. No known significant effects. Seek medical attention for any signs of wheezing and/or breathing difficulties. For additional advice call the medical emergency number on this SDS or your poison center or medical provider.

Skin contact

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Never give anything by mouth to an unconscious person. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.

Skin contact: May cause slight transient irritation.

Ingestion
 Nitrate based product. May be irritating to mouth, throat and stomach. May be harmful if swallowed. Over-exposure by ingestion is unlikely under normal working conditions.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

pain watering redness

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

redness

Date of issue/Date of revision : 5/17/2023 Date of previous issue : 5/17/2023 Version : 1.1 2/13

Section 4. First aid measures

Ingestion

: Adverse symptoms may include the following: nausea or vomiting diarrhea

Indication of immediate medical attention and special treatment needed, if necessary

stomach pains

Notes to physician

: In case of inhalation of decomposition products (carbon monoxide, carbon dioxide, nitrogen oxides) in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for up to 72 hours. In cases of suspected methemoglobinemia, monitor methemoglobin blood levels. Treatment is supportive; methylene blue may be indicated based on patient severity.

Specific treatments

: Call the medical emergency number on this SDS or your poison center or doctor immediately if large quantities have been ingested. In cases of suspected methemoglobinemia, methylene blue may be indicated based on patient severity.

Protection of first-aiders

No action shall be taken involving any personal risk or without suitable training. Decontamination measures may be necessary. Personnel and equipment must be checked and decontaminated prior to leaving the area.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media

: None known.

metal oxide/oxides

Specific hazards arising from the chemical

: Not an oxidizer at the manufactured concentration. It may become an oxidizing liquid if concentrated by evaporation. If evaporated to dryness, the product acts as an oxidizing agent, and supports combustion by liberating oxygen even if smothered. Cool containing vessels with flooding quantities of water until well after fire is out. A self contained breathing apparatus should be used to avoid inhalation of toxic fumes. When heated to decomposition it emits toxic fumes (NH3, NO, NO2...). Contaminated water can cause environmental damage. Contain and collect water used to fight fire.

Hazardous thermal decomposition products : Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides

Special protective actions for fire-fighters

: No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. Contain and collect the water used to fight the fire for later treatment and disposal. Dangerous if allowed to dry out. Residue may exhibit oxidizing properties.

Special protective equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

3/13 Date of issue/Date of revision : 5/17/2023 Date of previous issue : 5/17/2023 Version: 1.1

Section 6. Accidental release measures

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused adverse impacts (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Shut off all ignition sources. No flares, smoking or flames in hazard area. Stop leak if without risk. Do not absorb in sawdust or other combustible material. It may lead to a fire risk when it dries out. Put on appropriate personal protective equipment (see Section 8). Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Use appropriate equipment to put the spilled substance in a container for reuse or disposal. Recycle to process, if possible.

Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Read label before use. Apply this product only as specified on the label. Do not handle until all safety precautions have been read and understood. Avoid breathing vapor or mist. Avoid contact with eyes, skin and clothing. Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not ingest. Do not breathe vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. While AN solution as produced is not classified as an oxidizer, it is important to prevent conditions during handling and storage which may result in concentration of the product which may encourage it to behave as an oxidizer. Ensure that AN solution pumps are thermally protected against exceeding a temperature of 66 deg. C (150 deg. F). Also ensure that piping sytems, if insulated, are not externally heated (heat traced). May form corrosive sludge on prolonged storage. Contact your sales representative or a metallurgical specialist to ensure compatibility with your equipment.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

None.

Biological exposure indices

No exposure indices known.

Date of issue/Date of revision : 5/17/2023 Date of previous issue : 5/17/2023 Version : 1.1 4/13

Section 8. Exposure controls/personal protection

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Ensure compliance with OSHA 29CFR1910.109 requirements.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Contact your personal protective equipment supplier to verify the compatibility of the equipment for the intended purpose.

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/ or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

For U.S. work sites where respiratory protection is required, ensure that a respiratory protection program meeting 29 CFR 1910.134 requirements is in place.

Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state : Liquid.

Color : Green. [Dark]
Odor : Sweet. [Slight]
Odor threshold : Not available.

pH : 6 to 6.6 [Conc. (% w/w): 100%]

Melting point/freezing point: Not available.

Date of issue/Date of revision : 5/17/2023 Date of previous issue : 5/17/2023 Version : 1.1 5/13

Section 9. Physical and chemical properties and safety characteristics

Boiling point, initial boiling point, and boiling range

: Not available.

Flash point

: [Product does not sustain combustion.]

Flammability

: Non-flammable.

Lower and upper explosion limit/flammability limit

: Not applicable.

Vapor pressure

	Vapor Pressure at 20°C (68°F)		Vapor pressure at 50°C (122°F		50°C (122°F)	
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
Water	23.8	3.2				

Relative vapor density

: Not available.

Relative density

: 1.23 to 1.24

Solubility in water

: 10.26 to 10.36 lb/gal: Miscible in water.

Partition coefficient: n-

: Not applicable.

octanol/water

Bulk density

Auto-ignition temperature

: Not available.

Decomposition temperature

: Not available.

Viscosity

: Not available.

Particle characteristics

Median particle size : N

: Not applicable.

Section 10. Stability and reactivity

Reactivity

: Not an oxidizer at the manufactured concentration. It may become an oxidizing liquid if concentrated by evaporation. Keep away from incompatible materials. May form corrosive sludge on prolonged storage.

Chemical stability

: The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur. If mixed with chlorine or hypochlorites, it may form nitrogen trichloride which may explode spontaneously in air.

Conditions to avoid

: Do not allow to dry out. Avoid high temperatures in combination with high pressures. Keep away from heat and direct sunlight. Keep from freezing. Keep away from incompatible materials.

Incompatible materials

: Strong acids, strong alkalis, reducing materials, combustible materials, organic materials, chlorine, hypochlorites, chlorates, copper, zinc and their alloys, including brass, bronze and galvanized materials. Contact your sales representative or a metallurgical specialist to ensure compatibility with your equipment.

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced. Burns or explodes when heated to decomposition.

Date of issue/Date of revision : 5/17/2023 Date of previous issue : 5/17/2023 Version : 1.1 6/13

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
ammonium nitrate zinc di(acetate)	LD50 Oral LD50 Oral		2217 mg/kg 2510 mg/kg	-

Conclusion/Summary

: Nitrate based product. May be irritating to the digestive tract. May cause nausea, vomiting, diarrhea, and abdominal pain. May cause methemoglobinemia (a condition that interferes with the oxygen-carrying capacity of the blood) if ingested in large quantities or over a prolonged period of time. Persons with methemoglobinemia may have blue tinge color to lips, nails, and skin. Also they may have shortness of breath or trouble breathing. Persons more susceptible to methemoglobinemia include: very young (less than 3 months), the elderly, those with chronic obstructive pulmonary disease (COPD), anemia, coronary artery disease, recent surgery or infection, and those with a genetic deficiency of G-6-PD.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
ammonium nitrate	Eyes - Edema of the conjunctivae	Rabbit	3	-	3 days
	Skin - Edema	Rabbit	0	-	72 hours

Conclusion/Summary

Skin : May cause slight transient irritation.

Eyes : Corrosive to eyes. Causes serious eye damage.

Respiratory : No known significant effects or critical hazards.

Sensitization

3	Route of exposure	Species	Result
ammonium nitrate	skin	Mouse	Not sensitizing

Conclusion/Summary

Skin : No known significant effects or critical hazards.Respiratory : No known significant effects or critical hazards.

Mutagenicity

Product/ingredient name	Test	Experiment	Result
	OECD 471 Bacterial Reverse Mutation Test OECD 476 In vitro Mammalian Cell Gene Mutation Test	Experiment: In vitro Subject: Bacteria Experiment: In vitro Subject: Mammalian-Animal	Negative Negative

Conclusion/Summary

: No known significant effects or critical hazards.

Carcinogenicity

Not available.

Conclusion/Summary

: Potential for nitrosamine formation if ingested. Do not ingest.

Classification

Product/ingredient name	OSHA	IARC	NTP
ammonium nitrate	-	2A	-

Reproductive toxicity

Date of issue/Date of revision : 5/17/2023 Date of previous issue : 5/17/2023 Version : 1.1 7/13

Section 11. Toxicological information

Product/ingredient name	Maternal toxicity	Fertility	Development toxin	Species	Dose	Exposure
ammonium nitrate	Negative	Negative	Negative	Rat - Male, Female	Oral: 1500 mg/ kg	-

Conclusion/Summary

: No known significant effects or critical hazards.

Teratogenicity

Product/ingredient name	Result	Species	Dose	Exposure
ammonium nitrate	Negative - Oral	Rat - Female	1500 mg/kg	-

Conclusion/Summary : No known significant effects or critical hazards.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely

routes of exposure

: Dermal contact. Eye contact.

Potential acute health effects

Eye contact : Corrosive to eyes. Causes serious eye damage. Inhalation : No known significant effects or critical hazards.

Skin contact : May cause slight transient irritation.

Ingestion : Nitrate based product. May be irritating to mouth, throat and stomach. May be harmful if

swallowed. Over-exposure by ingestion is unlikely under normal working conditions.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:

> pain watering redness

Inhalation : No specific data.

Skin contact : Adverse symptoms may include the following:

redness

Ingestion : Adverse symptoms may include the following:

nausea or vomiting

diarrhea stomach pains

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate : See above.

effects

Potential delayed effects : See below.

Long term exposure

Potential immediate : Nitrate based product. Methemoglobinemia (see Acute Health Effects).

effects

Potential delayed effects : See below.

Potential chronic health effects

Date of issue/Date of revision 8/13 : 5/17/2023 : 5/17/2023 Version: 1.1 Date of previous issue

Section 11. Toxicological information

Product/ingredient name	Result	Species	Dose	Exposure
ammonium nitrate	Chronic NOAEL Oral	Rat - Male, Female	256 mg/kg	12 months Continuous

Conclusion/Summary: Adverse chronic health effects are associated with high level exposures.

General : See above.

Carcinogenicity: Potential for nitrosamine formation if ingested. Do not ingest.

Mutagenicity : No known significant effects or critical hazards.Reproductive toxicity : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	(gases)	(vapors)	Inhalation (dusts and mists) (mg/ I)
AWAKEN® ammonium nitrate zinc di(acetate)	7142.9	N/A	N/A	N/A	N/A
	2217	N/A	N/A	N/A	N/A
	500	N/A	N/A	N/A	N/A

Other information : Not available.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
ammonium nitrate zinc di(acetate)	Acute EC50 800 μg/l Fresh water	Algae Daphnia Crustaceans - Cladocera Algae - Algae	10 days 48 hours 21 days 72 hours
	Acute LC50 0.55 mg/l Fresh water	Fish - Oncorhynchus mykiss - Young of the year	96 hours

Conclusion/Summary

Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
ammonium nitrate	-	-	Readily

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

Date of issue/Date of revision : 5/17/2023 Date of previous issue : 5/17/2023 Version : 1.1 9/13

[:] Harmful to aquatic life with long lasting effects. Excessive nutrient runoff to a body of water may result in eutrophication. Apply this product only as specified on the label.

Section 13. Disposal considerations

Disposal methods

: Follow disposal instructions on label. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Triple rinse containers with water and add the rinse water to the spray tank. Do not reuse containers for any purpose. Disposal should be in accordance with applicable regional, national and local laws and regulations. Recycling decontaminated containers is the best option of container disposal. The Agricultural Container Recycling Council (ACRC) operates the national recycling program. To contact your state and local ACRC recycler visit the ACRC web page at http://www.acrecycle.org/. Do not contaminate water, food or feed by storage or disposal.

Section 14. Transport information

	DOT Classification	TDG Classification	IMDG	IATA
UN number	UN3082	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (copper sulfate, zinc di(acetate))	-	-	-
Transport hazard class(es)	9	-	-	-
Packing group	III	-	-	-
Environmental hazards	No.	No.	No.	No.

Additional information

DOT Classification

: Reportable quantity 2590.7 lbs / 1176.2 kg [251.59 gal / 952.36 L]. The classification of the product is due solely to the presence of one or more US DOT-listed 'Hazardous substances' that are subject to reportable quantity requirements and only applies to shipments of a package that contains greater than, or equal to, the product reportable quantity threshold. Package sizes containing less than the product reportable quantity are not regulated as hazardous materials.

Remarks This product does not contain any DOT listed marine pollutants (49 CFR Appendix B to 172.101).

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to IMO instruments

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Section 15. Regulatory information

Not listed.

10/13 Date of issue/Date of revision : 5/17/2023 : 5/17/2023 Version: 1.1 Date of previous issue

Section 15. Regulatory information

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia : All components are listed or exempted.

Canada : All components are listed or exempted.

China : All components are listed or exempted.

Eurasian Economic Union

: Russian Federation inventory: All components are listed or exempted.

Japan

New Zealand

Philippines

Japan inventory (ISHL): Not determined.
All components are listed or exempted.
All components are listed or exempted.
All components are listed or exempted.

: Japan inventory (CSCL): Not determined.

Republic of Korea Taiwan

: All components are listed or exempted.

Thailand : Not determined.

Turkey : Not determined.

United States : All components are active or exempted.Viet Nam : All components are listed or exempted.

U.S. Federal regulations

: TSCA 8(a) CDR Exempt/Partial exemption: Not determined

Clean Water Act (CWA) 307: zinc di(acetate); copper sulfate; zinc sulfate

Clean Water Act (CWA) 311: zinc di(acetate); ammonia; ferrous sulfate; copper sulfate;

zinc sulfate

Clean Air Act Section 112

(b) Hazardous Air Pollutants (HAPs)

: Listed

Clean Air Act Section 602

Class | Substances

: Not listed

Clean Air Act Section 602

Class II Substances

: Not listed

DEA List I Chemicals

(Precursor Chemicals)

: Not listed

DEA List II Chemicals

: Not listed

(Essential Chemicals)

SARA 302/304

Composition/information on ingredients

			SARA 302 TPQ SARA		SARA 304 F	RA 304 RQ	
Name	%	EHS	(lbs)	(gallons)	(lbs)	(gallons)	
ammonia	0.1 - 1	Yes.	500	-	100	-	

SARA 304 RQ : 23501 lbs / 10669.5 kg [2282.2 gal / 8639.3 L]

SARA 311/312

Classification : SERIOUS EYE DAMAGE - Category 1

SARA 313

Date of issue/Date of revision : 5/17/2023 Date of previous issue : 5/17/2023 Version : 1.1 11/13

Section 15. Regulatory information

	Product name	CAS number	%
Form R - Reporting requirements	ammonium nitrate	6484-52-2	10 - 20
	zinc di(acetate)	557-34-6	5 - 10
	Proprietary	-	Proprietary
Supplier notification	ammonium nitrate	6484-52-2	10 - 20
	zinc di(acetate)	557-34-6	5 - 10
	Proprietary	-	Proprietary

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts : The following components are listed: ammonium nitrate; Proprietary; zinc di(acetate)

New York : The following components are listed: Proprietary; zinc di(acetate)

New Jersey : The following components are listed: ammonium nitrate; Proprietary; zinc di(acetate) **Pennsylvania** : The following components are listed: ammonium nitrate; Proprietary; zinc di(acetate)

California Prop. 65



MARNING: This product can expose you to chemicals including Nickel, which is known to the State of California to cause cancer, and Lead, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Section 16. Other information

History

Date of issue/Date of : 5/17/2023

revision

Date of previous issue : 5/17/2023

Version

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available

SGG = Segregation Group **UN = United Nations**

Procedure used to derive the classification

Classification	Justification	
SERIOUS EYE DAMAGE - Category 1	Calculation method	

[▼] Indicates information that has changed from previously issued version.

Notice to reader

Supply chain partners must ensure they pass this SDS, and all other relevant safety information to their customers.

DISCLAIMER AND LIMITATION OF LIABILITY

The information and recommendations contained in this Safety Data Sheet ("SDS") relate only to the specific material referred to herein (the "Material") and do not relate to the use of such Material in combination with any other material or process. The information and recommendations contained herein are believed to be current and correct as of the date of this SDS. HOWEVER, THE INFORMATION AND RECOMMENDATIONS ARE PRESENTED WITHOUT WARRANTY, REPRESENTATION OR LICENSE OF ANY KIND, EXPRESS OR IMPLIED, WITH RESPECT TO THEIR ACCURACY, CORRECTNESS OR COMPLETENESS, AND THE SELLER, SUPPLIER AND MANUFACTURER OF THE MATERIAL AND THEIR RESPECTIVE AFFILIATES (COLLECTIVELY, THE "SUPPLIER")

Date of issue/Date of revision : 5/17/2023 : 5/17/2023 Version: 1.1 12/13 Date of previous issue

Section 16. Other information

DISCLAIM ALL LIABILITY FOR RELIANCE ON SUCH INFORMATION AND RECOMMENDATIONS. This SDS is not a guarantee of safety. A buyer or user of the Material (a "Recipient") is responsible for ensuring that it has all current information necessary to safely use the Material for its specific purpose.

FURTHERMORE, THE RECIPIENT ASSUMES ALL RISK IN CONNECTION WITH THE USE OF THE MATERIAL. THE RECIPIENT ASSUMES ALL RESPONSIBILITY FOR ENSURING THE MATERIAL IS USED IN A SAFE MANNER IN COMPLIANCE WITH APPLICABLE ENVIRONMENTAL, HEALTH, SAFETY AND SECURITY LAWS, POLICIES AND GUIDELINES. THE SUPPLIER DOES NOT WARRANT THE MERCHANTABILITY OF THE MATERIAL OR THE FITNESS OF THE MATERIAL FOR ANY PARTICULAR USE AND ASSUMES NO RESPONSIBILITY FOR INJURY OR DAMAGE CAUSED DIRECTLY OR INDIRECTLY BY OR RELATED TO THE USE OF THE MATERIAL.

AWAKEN® is a registered trademark of Loveland Products, Inc.

Date of issue/Date of revision : 5/17/2023 Date of previous issue : 5/17/2023 Version : 1.1 13/13