

SAFETY DATA SHEET

1. Identification

Product identifier	Brimstone
Other means of identification	None.
Recommended use	Ag Product - Adjuvant
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	
Manufacturer	
Company name	Wilbur-Ellis Company LLC
Address	16300 Christensen Rd. Ste 135 Tukwila, WA 98188 United States
Telephone	Branded Products Information (800) 500-1698
E-mail	SDS@wilburellis.com
Emergency phone number	Chemtrec - Domestic (800) 424-9300 Chemtrec - International +1 703-741-5970

2. Hazard(s) identification

Physical hazards	Corrosive to metals	Category 1
Health hazards	Acute toxicity, oral	Category 4
	Skin corrosion/irritation	Category 1B
	Serious eye damage/eye irritation	Category 1
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		



Signal word	Danger
Hazard statement	May be corrosive to metals. Harmful if swallowed. Causes severe skin burns and eye damage. Causes serious eye damage. May cause respiratory irritation.
Precautionary statement	
Prevention	Keep only in original container. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear eye/face protection. Wear protective gloves, protective clothing, eye protection, and face protection.
Response	IF SWALLOWED: Call a poison center or doctor or doctor if you feel unwell. If swallowed: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor. Call a POISON CENTER or doctor if you feel unwell. Specific treatment (see this label). Wash contaminated clothing before reuse. Absorb spillage to prevent material damage.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Store in corrosive resistant container with a resistant inner liner.
Disposal	Dispose of contents and container in accordance with government regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Proprietary Blend		Proprietary	100

Percentage ranges of composition to protect confidentiality or due to batch variation. Specific chemical identity withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. Call a physician if symptoms develop or persist.
Skin contact	Take off immediately all contaminated clothing. Wash off with soap and water. Call a physician or poison control center immediately. Chemical burns must be treated by a physician. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical attention if you feel unwell.
Most important symptoms/effects, acute and delayed	Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb spillage to prevent material damage. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. Small Spills: Wipe up with inert absorbent material. Clean surface thoroughly to remove residual contamination.
Environmental precautions	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not breathe mist or vapor. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in a cool, dry place out of direct sunlight. Store in corrosive resistant container with a resistant inner liner. Keep only in the original container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Butanol (CAS 71-36-3)	PEL	300 mg/m ³ 100 ppm	
Ethanolamine (CAS 141-43-5)	PEL	6 mg/m ³ 3 ppm	
Glycerol (CAS 56-81-5)	PEL	5 mg/m ³ 15 mg/m ³	Respirable fraction. Total dust.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Butanol (CAS 71-36-3)	TWA	20 ppm	
Diethanolamine (CAS 111-42-2)	TWA	1 mg/m ³	Inhalable fraction and vapor.
Ethanolamine (CAS 141-43-5)	STEL	6 ppm	
	TWA	3 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Butanol (CAS 71-36-3)	Ceiling	150 mg/m ³ 50 ppm
Diethanolamine (CAS 111-42-2)	TWA	15 mg/m ³ 3 ppm
Ethanolamine (CAS 141-43-5)	STEL	15 mg/m ³
	TWA	6 ppm 8 mg/m ³ 3 ppm

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

US - California OELs: Skin designation

Butanol (CAS 71-36-3)

Can be absorbed through the skin.

Diethanolamine (CAS 111-42-2)

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Butanol (CAS 71-36-3)

Skin designation applies.

US - Tennessee OELs: Skin designation

Butanol (CAS 71-36-3)

Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Diethanolamine (CAS 111-42-2)

Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Butanol (CAS 71-36-3)

Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection	Wear safety glasses with side shields (or goggles) and a face shield.
Skin protection	
Hand protection	Wear appropriate chemical resistant gloves.
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment. Chemical respirator with organic vapor cartridge.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	Clear yellow liquid
Physical state	Liquid.
Form	Liquid.
Color	Clear to yellow
Odor	Fatty
Odor threshold	Not available.
pH	2 - 2.5
pH concentration	0.25 %
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	> 200.0 °F (> 93.3 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	> 1
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Soluble
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	9.93 - 10.01 lb/gal
Flammability class	Combustible IIIB estimated
Specific gravity	1.19 - 1.2

10. Stability and reactivity

Reactivity	May be corrosive to metals.
Chemical stability	Material is stable under normal conditions.

Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Metals.
Hazardous decomposition products	Irritating and/or toxic fumes and gases may be emitted upon the products decomposition.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause irritation to the respiratory system. Prolonged inhalation may be harmful.
Skin contact	Causes severe skin burns. Prolonged or repeated exposure may cause liver and kidney damage. These effects have not been observed in humans.
Eye contact	Causes serious eye damage.
Ingestion	Causes digestive tract burns. Harmful if swallowed.
Symptoms related to the physical, chemical and toxicological characteristics	Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation.

Information on toxicological effects

Acute toxicity	In high concentrations, vapors are anesthetic and may cause headache, fatigue, dizziness and central nervous system effects. Harmful if swallowed. May cause respiratory irritation.
-----------------------	--

Components	Species	Test Results
Butanol (CAS 71-36-3)		
Acute		
Dermal		
LD50	Rabbit	3430 mg/kg, 24 Hours 4.24 ml/kg, 24 Hours
Oral		
LD50	Rat	4360 mg/kg 2.83 ml/kg
Diethanolamine (CAS 111-42-2)		
Acute		
Oral		
LD50	Rat	1820 mg/kg
Ethanolamine (CAS 141-43-5)		
Acute		
Dermal		
LD50	Rabbit	2881 mg/kg, 24 Hours 2.46 - 2.83 ml/kg, 24 Hours
Inhalation		
<i>Vapor</i>		
LC50	Rat	> 1.3 mg/l, 6 Hours
Oral		
LD50	Rat	1515 mg/kg 1089 mg/kg 1.19 ml/kg
Glycerol (CAS 56-81-5)		
Acute		
Dermal		
LD50	Guinea pig	45 ml/kg, Days

Components	Species	Test Results
Inhalation		
<i>Vapor</i>		
LC50	Rat	4655 mg.min/l, 7 Hours
Oral		
LD50	Guinea pig	>= 10000 mg/kg
	Mouse	23000 mg/kg
		20.81 ml/kg
	Rat	27200 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Causes severe skin burns and eye damage.
Serious eye damage/eye irritation	Causes serious eye damage.
Corneal opacity value	1.0000
Iris lesion value	1.1110
Conjunctival reddening value	2.8889
Conjunctival oedema value	2.1111
Recover days	21
Respiratory or skin sensitization	
Respiratory sensitization	Not available.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Risk of cancer cannot be excluded with prolonged exposure.
IARC Monographs. Overall Evaluation of Carcinogenicity	
	Diethanolamine (CAS 111-42-2) 2B Possibly carcinogenic to humans.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	
	Not regulated.
US. National Toxicology Program (NTP) Report on Carcinogens	
	Not listed.
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	May cause respiratory irritation.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not available.
Chronic effects	May be harmful if absorbed through skin. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.
	Prolonged or repeated exposure may cause liver and kidney damage. These effects have not been observed in humans.

12. Ecological information

Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	No data available.
Mobility in soil	No data available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents and container in accordance with government regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	D002: Waste Corrosive material [pH <=2 or =>12.5, or corrosive to steel] The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings, if applicable, even after container is emptied.

14. Transport information

DOT

UN number	UN1760
UN proper shipping name	Corrosive liquids, n.o.s. (monocarbamide dihydrogen sulfate)
Transport hazard class(es)	
Class	8
Subsidiary risk	-
Label(s)	8
Packing group	II
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	IB3, T7, TP1, TP28
Packaging exceptions	154
Packaging non bulk	203
Packaging bulk	241

IATA

UN number	UN1760
UN proper shipping name	Corrosive liquid, n.o.s. (monocarbamide dihydrogensulfate)
Transport hazard class(es)	
Class	8
Subsidiary risk	-
Packing group	II
Environmental hazards	No.
ERG Code	8L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.

IMDG

UN number	UN1760
UN proper shipping name	CORROSIVE LIQUID, N.O.S. (monocarbamide dihydrogensulfate)
Transport hazard class(es)	
Class	8
Subsidiary risk	-
Packing group	II
Environmental hazards	
Marine pollutant	Yes - Amines, tallow alkyl ethoxylated
EmS	F-A, S-B
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not established.

DOT



IATA; IMDG



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are listed on or exempted from the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Butanol (CAS 71-36-3) Listed.
Diethanolamine (CAS 111-42-2) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories
Immediate Hazard - Yes
Delayed Hazard - No
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
N-BUTYL ALCOHOL	71-36-3	1 - < 3

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Diethanolamine (CAS 111-42-2)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Butanol (CAS 71-36-3) Low priority
Glycerol (CAS 56-81-5) Other Flavoring Substances with OSHA PEL's

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Diethanolamine (CAS 111-42-2)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

1,4-dioxane (CAS 123-91-1)	Listed: January 1, 1988
Diethanolamine (CAS 111-42-2)	Listed: June 22, 2012

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Ethylene Glycol (CAS 107-21-1)	Listed: June 19, 2015
--------------------------------	-----------------------

16. Other information, including date of preparation or last revision

Issue date	12-17-2014
Revision date	09-26-2017
Version #	06
NFPA ratings	Health: 3 Flammability: 0 Instability: 0

NFPA ratings



Disclaimer

This information was developed from information on the constituent materials. No warranty is expressed or implied regarding the completeness or continuing accuracy of the information contained herein, and Wilbur-Ellis disclaims all liability for reliance thereon. The user should satisfy himself that he has all current data relevant to his particular use.