

Revision date: 2023/06/12 Page: 1/12

Version: 6.0 (30587274/SDS\_GEN\_US/EN)

#### 1. Identification

Product identifier used on the label

# **Custom Seed Gloss 661**

#### Recommended use of the chemical and restriction on use

Recommended use\*: Seed coating

### Details of the supplier of the safety data sheet

Company: BASF SE 67056 Ludwigshafen GERMANY Contact address:
BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932
USA

Telephone: +1 973 245-6000

## **Emergency telephone number**

24 Hour Emergency Response Information

CHEMTREC: 1-800-424-9300

BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

#### 2. Hazards Identification

#### According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

#### Classification of the product

No need for classification according to GHS criteria for this product.

#### **Label elements**

The product does not require a hazard warning label in accordance with GHS criteria.

<sup>\*</sup> The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Revision date: 2023/06/12 Page: 2/12

Version: 6.0 (30587274/SDS\_GEN\_US/EN)

#### Hazards not otherwise classified

Labeling of special preparations (GHS):

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Safety data sheet available on request.

Product contains the following components and may cause an allergic skin reaction: The substance may cause sensitization of the skin in particularly sensitive individuals. Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses. mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 1,2-benzisothiazol-3(2H)-one

# 3. Composition / Information on Ingredients

#### According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Quartz (SiO2)

CAS Number: 14808-60-7 Content (W/W): 0.0 - 1.0% Synonym: Silicon dioxide

Mica-group minerals

CAS Number: 12001-26-2 Content (W/W): 15.0 - 30.0%

Synonym: Mica

Titanium dioxide

CAS Number: 13463-67-7 Content (W/W): 5.0 - 15.0% Synonym: C.I. Pigment White 6

1,2-benzisothiazol-3(2H)-one

CAS Number: 2634-33-5 Content (W/W): < 0.05% Synonym: No data available.

mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

CAS Number: 55965-84-9 Content (W/W): < 0.05%

Synonym: 5-Chloro-2-methyl-3(2H)-isothiazolone mixt. with 2-methyl-3(2H)-

isothiazolone

# 4. First-Aid Measures

#### **Description of first aid measures**

#### General advice:

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing.

#### If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

Revision date: 2023/06/12 Page: 3/12

Version: 6.0 (30587274/SDS\_GEN\_US/EN)

#### If on skin:

Immediately wash thoroughly with soap and water, seek medical attention.

#### If in eves:

Wash affected eyes for at least 15 minutes under running water with eyelids held open.

#### If swallowed:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

# Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11., (Further) symptoms and / or effects are not known so far

#### Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

# 5. Fire-Fighting Measures

### **Extinguishing media**

Suitable extinguishing media: water spray, dry powder, foam, carbon dioxide

### Special hazards arising from the substance or mixture

Hazards during fire-fighting:

carbon monoxide, Hydrogen chloride, hydrogen bromide, carbon dioxide, nitrogen oxides, silica compounds, sulfur oxides, halogenated compounds, metal oxides

The substances/groups of substances mentioned can be released in case of fire.

#### Advice for fire-fighters

Protective equipment for fire-fighting:

Wear self-contained breathing apparatus and chemical-protective clothing.

#### Further information:

Keep containers cool by spraying with water if exposed to fire. In case of fire and/or explosion do not breathe fumes. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

## 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

Do not breathe vapour/spray. Use personal protective clothing. Avoid contact with the skin, eyes and clothing.

Revision date: 2023/06/12 Page: 4/12 Version: 6.0 (30587274/SDS GEN US/EN)

#### **Environmental precautions**

Do not discharge into the subsoil/soil. Do not discharge into drains/surface waters/groundwater.

# Methods and material for containment and cleaning up

For small amounts: Pick up with suitable absorbent material (e.g. sand, sawdust, general-purpose binder, kieselguhr).

For large amounts: Dike spillage. Pump off product.

Dispose of absorbed material in accordance with regulations. Collect waste in suitable containers, which can be labeled and sealed. Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations. Wear suitable protective equipment.

# 7. Handling and Storage

#### Precautions for safe handling

No special measures necessary if stored and handled correctly. Ensure thorough ventilation of stores and work areas. When using do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift.

Protection against fire and explosion:

No special precautions necessary. The substance/product is non-combustible. Product is not explosive.

# Conditions for safe storage, including any incompatibilities

Segregate from foods and animal feeds.

Further information on storage conditions: Keep away from heat. Protect from direct sunlight.

## 8. Exposure Controls/Personal Protection

#### Components with occupational exposure limits

Mica-group minerals OSHA Z3: TWA value 20 millions of particles per cubic foot

of air;

ACGIH, US: TWA value 0.1 mg/m3 Respirable fraction;

OSHA Z1: PEL 15 mg/m3 Total dust;

OSHA Z1: PEL 5 mg/m3 Respirable fraction;

Titanium dioxide ACGIH, US: TWA value 2.5 mg/m3 Respirable finescale

particles:

ACGIH, US: TWA value 0.2 mg/m3 Respirable nanoscale

particles;

OSHA Z1: PEL 15 mg/m3 Total dust;

## Advice on system design:

Whenever possible, engineering controls should be used to minimize the need for personal protective equipment.

#### Personal protective equipment

# **Respiratory protection:**

Wear respiratory protection if ventilation is inadequate. Wear a NIOSH-certified (or equivalent) TC23C Chemical/Mechanical type filter system to remove a combination of particles, gas and

Revision date: 2023/06/12 Page: 5/12 Version: 6.0 (30587274/SDS GEN US/EN)

vapours. For situations where the airborne concentrations may exceed the level for which an air purifying respirator is effective, or where the levels are unknown or Immediately Dangerous to Life or Health (IDLH), use NIOSH-certified full facepiece pressure demand self-contained breathing apparatus (SCBA) or a full facepiece pressure demand supplied-air respirator (SAR) with escape provisions.

#### Hand protection:

Chemical resistant protective gloves, Protective glove selection must be based on the user's assessment of the workplace hazards.

#### Eye protection:

Safety glasses with side-shields. Wear face shield or tightly fitting safety goggles (chemical goggles) if splashing hazard exists.

#### **Body protection:**

Body protection must be chosen depending on activity and possible exposure, e.g. head protection, apron, protective boots, chemical-protection suit.

## General safety and hygiene measures:

Handle in accordance with good industrial hygiene and safety practice. Wearing of closed work clothing is recommended. Store work clothing separately. Keep away from food, drink and animal feeding stuffs.

# 9. Physical and Chemical Properties

Form: liquid Odour: faint odour

Odour threshold: Not determined due to potential health hazard by inhalation.

Colour: off-white with pearly reflection

pH value: approx. 8 - 9.5

(20 °C)

Melting temperature: approx. 0 °C

Information applies to the solvent.

boiling temperature: approx. 100 °C

Information applies to the solvent.

Flash point: > 100 °C Flammability: not applicable

Lower explosion limit: As a result of our experience with this

product and our knowledge of its composition we do not expect any hazard as long as the product is used appropriately and in accordance with

the intended use.

Upper explosion limit: As a result of our experience with this

product and our knowledge of its composition we do not expect any hazard as long as the product is used appropriately and in accordance with

the intended use.

Autoignition: Based on the water content the

product does not ignite.

Vapour pressure: approx. 23.4 hPa

(20°C)

Information applies to the solvent.

Revision date: 2023/06/12 Page: 6/12 Version: 6.0 (30587274/SDS GEN US/EN)

Density: approx. 1.2 g/cm3

(20°C)

Vapour density: not applicable Partitioning coefficient n- not applicable

octanol/water (log Pow):

Thermal decomposition: No decomposition if stored and handled as

prescribed/indicated.

Viscosity, dynamic: approx. 1 mPa.s

Information applies to the solvent.

Solubility in water: dispersible Evaporation rate: not applicable

Other Information: If necessary, information on other physical and chemical

parameters is indicated in this section.

# 10. Stability and Reactivity

#### Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Oxidizing properties:

Based on its structural properties the product is not classified as oxidizing.

#### **Chemical stability**

The product is stable if stored and handled as prescribed/indicated.

#### Possibility of hazardous reactions

No hazardous reactions if stored and handled as prescribed/indicated.

#### Conditions to avoid

See SDS section 7 - Handling and storage.

#### Incompatible materials

strong acids, strong bases, strong oxidizing agents

#### Hazardous decomposition products

Decomposition products:

Hazardous decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

## 11. Toxicological information

#### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

# **Acute Toxicity/Effects**

**Acute toxicity** 

Revision date: 2023/06/12 Page: 7/12 Version: 6.0 (30587274/SDS GEN US/EN)

Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Virtually nontoxic by inhalation. Virtually nontoxic after a single skin contact. The product has not been tested. The statement has been derived from the properties of the individual components.

Oral

Type of value: ATE Value: > 5,000 mg/kg

Information on: 1,2-benzisothiazol-3(2H)-one

Type of value: LD50 Species: rat (male/female)

Value: 490 mg/kg (similar to OECD guideline 401)

\_\_\_\_\_

Inhalation

Type of value: ATE Value: > 20.0000 mg/l Determined for vapor

Type of value: ATE Value: > 5.0000 mg/l Determined for mist

Dermal

Type of value: ATE Value: > 5,000 mg/kg

Information on: 1,2-benzisothiazol-3(2H)-one

Type of value: LD50 Species: rat (male/female)

Value: > 2,000 mg/kg (OECD Guideline 402)

No mortality was observed.

#### Assessment other acute effects

Assessment of STOT single:

Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

The product has not been tested. The statement has been derived from the properties of the individual components.

#### Irritation / corrosion

Assessment of irritating effects: Not irritating to the skin. Not irritating to the eyes. The product has not been tested. The statement has been derived from the properties of the individual components.

#### Skin

Information on: 1,2-benzisothiazol-3(2H)-one

Species: rabbit Result: Irritant. Method: other Literature data.

\_\_\_\_\_

#### <u>Eye</u>

Revision date: 2023/06/12 Page: 8/12 Version: 6.0 (30587274/SDS GEN US/EN)

Information on: 1,2-benzisothiazol-3(2H)-one

Species: rabbit

Result: Severely irritating.

Method: other Literature data.

-----

#### Sensitization

Assessment of sensitization: There is no evidence of a skin-sensitizing potential. The product has not been tested. The statement has been derived from the properties of the individual components.

Information on: 1,2-benzisothiazol-3(2H)-one

Guinea pig maximization test

Species: guinea pig Result: sensitizing

Method: OECD Guideline 406

-----

#### **Aspiration Hazard**

No aspiration hazard expected. The product has not been tested. The statement has been derived from the properties of the individual components.

# **Chronic Toxicity/Effects**

#### Repeated dose toxicity

Assessment of repeated dose toxicity: The product has not been tested. The statement has been derived from the properties of the individual components.

#### Information on: crystalline silica

Assessment of repeated dose toxicity: Prolonged or repeated inhalation of respirable crystalline silica may result in silicosis. Repeated inhalation exposure may cause inflammatory effects in the lung. The substance may cause increase in lung mass and lung tissue changes after repeated inhalation. This product may contain greater than 0.1% crystalline silica. Repeated exposure to high concentrations results in silicosis, a lung disease characterized by coughing, difficult breathing, wheezing, scarring of the lungs, and repeated, non-specific chest illnesses.

OSHA (Occupational Safety and Health Administration) has classified this substance as harmful to the lung, kidney and immune system following repeated inhalation exposure.

-----

#### Information on: Titanium dioxide

Assessment of repeated dose toxicity: Repeated oral uptake of the substance did not cause substance-related effects. The substance may cause increase in lung mass and lung tissue changes after repeated inhalation.

-----

#### Genetic toxicity

Assessment of mutagenicity: Mutagenicity tests revealed no genotoxic potential. The product has not been tested. The statement has been derived from the properties of the individual components.

### Carcinogenicity

Assessment of carcinogenicity: The product has not been tested. The statement has been derived from the properties of the individual components.

Revision date: 2023/06/12 Page: 9/12 Version: 6.0 (30587274/SDS GEN US/EN)

Information on: Titanium dioxide

Assessment of carcinogenicity: IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans). In long-term studies in rats in which the substance was given by inhalation, a carcinogenic effect was observed. Tumors were only observed in rats after chronic inhalative exposure to high concentrations which caused sustained lung inflammation. In long-term studies in rats and mice in which the substance was given by feed, a carcinogenic effect was not observed. Dermal exposure is not expected to be carcinogenic.

\_\_\_\_\_

#### Information on: crystalline silica

Assessment of carcinogenicity: May cause cancer by inhalation. The substance was found to cause cancer in animal experiments. Epidemiological studies stated a carcinogenic activity also in humans. The substance and its compounds in the form of respirable dusts/aerosolsis classified by the German MAK commision as a category 1 carcinogen (substances that cause cancer to humans). The International Agency for Research on Cancer (IARC) has classified this substance as a Group 1 (known) human carcinogen.

NTP listed carcinogen

OSHA (Occupational Safety and Health Administration) has classified this substance as carcinogenic.

.....

#### Reproductive toxicity

Assessment of reproduction toxicity: The product has not been tested. The statement has been derived from the properties of the individual components. The results of animal studies gave no indication of a fertility impairing effect.

#### Teratogenicity

Assessment of teratogenicity: The product has not been tested. The statement has been derived from the properties of the individual components. Animal studies gave no indication of a developmental toxic effect at doses that were not toxic to the parental animals.

#### Other Information

Misuse can be harmful to health.

#### 12. Ecological Information

#### **Toxicity**

Aquatic toxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms.

# Toxicity to fish

Information on: 1,2-benzisothiazol-3(2H)-one

LC50 (96 h) 2.15 mg/l, Oncorhynchus mykiss (OECD Guideline 203, static)

-----

#### Aquatic invertebrates

Information on: 1,2-benzisothiazol-3(2H)-one

EC50 (48 h) 2.9 mg/l, Daphnia magna (OECD Guideline 202, part 1, static)

Revision date: 2023/06/12 Page: 10/12 Version: 6.0 (30587274/SDS GEN US/EN)

-----

#### Aquatic plants

Information on: 1.2-benzisothiazol-3(2H)-one

EC50 (96 h) 0.110 mg/l, Pseudokirchneriella subcapitata (OECD Guideline 201, static) No observed effect concentration (96 h) 0.040 mg/l, Pseudokirchneriella subcapitata (OECD

Guideline 201, static)

### Persistence and degradability

#### Assessment biodegradation and elimination (H2O)

The product has not been tested. The statement has been derived from the properties of the individual components.

#### Assessment biodegradation and elimination (H2O)

Information on: 1,2-benzisothiazol-3(2H)-one

Not readily biodegradable (by OECD criteria).

-----

#### Bioaccumulative potential

#### Assessment bioaccumulation potential

The product has not been tested. The statement has been derived from the properties of the individual components.

#### Bioaccumulation potential

Information on: 1,2-benzisothiazol-3(2H)-one

Bioconcentration factor: 6.62 (56 d), Lepomis macrochirus (measured)

-----

#### Mobility in soil

#### Assessment transport between environmental compartments

The product has not been tested. The statement has been derived from the properties of the individual components.

Information on: 1,2-benzisothiazol-3(2H)-one

The substance will not evaporate into the atmosphere from the water surface.

Adsorption to solid soil phase is not expected.

# **Additional information**

# Other ecotoxicological advice:

Do not discharge product into the environment without control.

Revision date: 2023/06/12 Page: 11/12 Version: 6.0 (30587274/SDS\_GEN\_US/EN)

# 13. Disposal considerations

#### Waste disposal of substance:

Must be disposed of or incinerated in accordance with local regulations.

#### Container disposal:

Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

# 14. Transport Information

## Land transport

USDOT

Not classified as a dangerous good under transport regulations

# Sea transport

**IMDG** 

Not classified as a dangerous good under transport regulations

# Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

## 15. Regulatory Information

#### **Federal Regulations**

#### Registration status:

Chemical TSCA, US released / listed

**EPCRA 311/312 (Hazard categories):** Refer to SDS section 2 for GHS hazard classes applicable for this product.

#### **State regulations**

State RTK	CAS Number	Chemical name
PA	12001-26-2	Mica-group minerals
	13463-67-7	Titanium dioxide
NJ	12001-26-2	Mica-group minerals
	13463-67-7	Titanium dioxide
	14808-60-7	Quartz (SiO2)

# Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:

**WARNING:** This product can expose you to chemicals including TITANIUM DIOXIDE (AIRBORNE, UNBOUND PARTICLES OF RESPIRABLE SIZE), which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.

Revision date: 2023/06/12 Page: 12/12 Version: 6.0 (30587274/SDS\_GEN\_US/EN)

#### 16. Other Information

#### SDS Prepared by:

BASF NA Product Regulations SDS Prepared on: 2023/06/12

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

**END OF DATA SHEET**