




Diesel Exhaust Fluid (DEF)



FOR DIESEL SCR ENGINES

ONE U.S. GALLON (3.78 L)

Supporting a cleaner environment.



Diesel Exhaust Fluid (DEF)

DE-ZAUST™ Diesel Exhaust Fluid is for use in diesel engines equipped with Selective Catalytic Reduction (SCR) systems and is formulated to meet 2010 EPA regulations to reduce NOx emissions from diesel exhaust.

- Non-toxic
- Non-flammable
- Non-polluting
- Meets ISO 22241 Specifications

MADE IN U.S.A.

Always read and follow the label instructions on the products container(s) before using. DE-ZAUST and the DREXEL logo are either trademarks or registered trademarks of Drexel Chemical Company. Combine image courtesy of Case IH. Sky background image courtesy of Stock.XCHNG. Photo by ClassicDes. 6995DZSL1-0912

DIRECTIONS FOR USE

DO NOT MIX WITH DIESEL FUEL.

STORE BETWEEN 12°F (-11°C) AND 86°F (30°C).

- DE-ZAUST should only be added to the dedicated DEF tank. Do not add to the diesel fuel tank.
- DE-ZAUST is ready-to-use. Do Not Add Water.

CAUTION:

If **SWALLOWED**, rinse mouth with water. Do **NOT** induce vomiting. Seek medical attention.

EYES: rinse with plenty of water, and seek medical attention If irritation occurs.

SKIN: wash area with soap and water.

INGREDIENTS

Water	67.5%
Urea	32.5%



Manufactured By:
Drexel Chemical Company
P.O. BOX 13327, MEMPHIS, TN 38113-0327

SINCE 1972



Supporting a cleaner environment.