

MATERIAL SAFETY DATA SHEET
PRECISION LABORATORIES, INC.



Updated: December 10, 2010
Page 1 of 3

Product Name: FS Barrier™ - Drift Retardant / Deposition Aid

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: **FS Barrier™**
Manufactured by: PRECISION LABORATORIES, INC.
1429 S. SHIELDS DRIVE
WAUKEGAN, IL 60085

Emergency telephone number: (Chemtrec Information 24 hours) 1-800-424-9300
For MSDS, Product Safety, or (Technical Support on Product) 1-800-323-6280
Regulatory inquiries, call:


2. COMPOSITION / INFORMATION ON INGREDIENTS

<u>Component</u>	<u>CAS#</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>% By Wt.</u>
Light Hydrotreated Petroleum Distillate	64742-47-8	N/A	400 ppm-ceiling	N/A

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

NFPA Hazard Rating:



Primary Routes of Exposure:

Eyes: **Yes** Skin: **Yes** Oral: **No** Inhalation: **Yes**

Signs and Symptoms of Exposure:

Eye contact: May cause irritation and reddening.
Skin contact: May cause irritation and reddening.
Inhalation: May cause respiratory and mucosal irritation.
Ingestion: May cause nausea, vomiting and diarrhea.

4. FIRST AID MEASURES

FIRST AID MEASURES FOR ACCIDENTAL EXPOSURE

Eye Exposure: Check for and remove contact lenses. Immediately flush eyes with water for at least 15 minutes. Cold water may be used. Seek medical attention if irritation occurs.

Skin Exposure: Wash affected area with plenty of soap and water. Cold water may be used. Seek medical attention if irritation develops.

Inhalation: Move person to fresh air. If person is having difficulty breathing, give oxygen. If not breathing, give artificial respiration. Seek immediate medical attention.

Ingestion: Do not induce vomiting unless directed to do so by medical personnel. Give never give fluids or force vomiting if the person is unconscious, is having convulsions or has no gag reflex. If large quantities are swallowed, seek immediate medical attention.

Medical Conditions Aggravated by Overexposure: None known.

5. FIRE-FIGHTING MEASURES

FIRE HAZARD DATA:

Flammability: N/E **LEL:** 0.9% Estimate **UEL:** N/E
Auto-ignition temperature: N/E
Flash Point: >200°F

Extinguishing Media: Use carbon dioxide, dry chemical for small fires and fog or foam for large fires.
Special Fire Fighting Procedures: Firefighters should wear NIOSH/OSHA approved self-contained breathing apparatus and full protective clothing.

Additional Fire and Explosive Data: When exposed to extreme heat, closed containers may rupture due to buildup of pressure. Water can cause extremely slippery floor surfaces.

Product Name: FS Barrier™ - Drift Retardant / Deposition Aid

6. ACCIDENTAL RELEASE MEASURES

Spill or Leak Procedures: Evacuate the spill area, except for cleanup personnel. Wear NIOSH/OSHA-approved respirator and protective equipment as referenced in Section 8 below. Control spill with adsorbent pads or booms. Recover free liquid. If necessary, apply granular or loose absorbent (sand, earth, sawdust, etc.) to spill. Sweep or otherwise collect and dispose of properly. Large spills may be flushed to sewer if local authorities approve such. Product is slippery under foot; flush smooth surfaces thoroughly. See Section 13 below for disposal considerations.

7. HANDLING AND STORAGE

Precautions to be Taken in Handling: Keep away from heat, sparks and flame. Keep container closed. Safety goggles with full-face shield and eyewash recommended. USDA-accepted nitrile (CFR-20) or neoprene rubber (CFR-21) recommended. Wear appropriate clothing to prevent repeated or prolonged skin contact. Use only with adequate mechanical exhaust ventilation. To avoid fire minimize ignition sources.

Precautions to be Taken in Storage: Product should be stored in a dry place with temperatures above 30°F. Partially used containers should be resealed between uses for maximum storage stability.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Note: When selecting personal protective equipment and clothing, follow all of the manufacturer specifications and recommendations that apply to your specific operation and processing conditions. Take into consideration all working conditions and all chemicals to be handled or processed.

Eye Protection: Wear splash-proof chemical safety goggles. Contact lenses should not be worn when working with chemicals.

Skin Protection: Wear coveralls and boots to minimize skin contact. As precautions, wash hands and face with mild soap and water before eating, drinking, smoking or using restroom. After each shift, clean all protective equipment, wash work clothes, and shower.

Inhalation Protection: Not required under normal use conditions with good ventilation. Protect against spray mists.

Other Protection: Eye wash fountains and drench showers should be located within 100 feet or a 10 second walk or the work area per ANSI Z358.1-1990.

Personal Protection in Case of Large Spill: Splash goggles. Full suit. Boots, gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Appearance & Odor: White liquid emulsion with slight organic odor.

Boiling Point: >200°F

pH: N/A

Solubility in Water: Partial (10% form as gel).

10. STABILITY AND REACTIVITY

Chemical Stability: Stable.

Incompatibility: Strong oxidizers.

Hazardous Decomposition Products: Combustion products may include ammonia and oxides of carbon and nitrogen

Hazardous Polymerization: Will not occur.

Conditions to Avoid: None known.

11. TOXICOLOGICAL INFORMATION

No toxicological data is available for this product.

12. ECOLOGICAL INFORMATION

No ecological data is available for this product.

13. DISPOSAL CONSIDERATIONS

Disposal Methods: Recycle or rework material if at all possible. Incinerate material at an approved facility. Treat at an acceptable waste treatment facility, or municipal waste treatment plant after proper testing and approval waste samples in compliance with applicable federal, state and local environmental regulations.

Container Reuse: An empty container can contain product residue, and should be not reused. If not professionally cleaned and reconditioned, crushing or other means is recommended to prevent unauthorized reuse.

14. TRANSPORT INFORMATION

DOT Status (Highway and rail): N/E

IATA Status (Air): N/E

Product Name: FS Barrier™ - Drift Retardant / Deposition Aid

15. REGULATORY INFORMATION

SARA HAZARD:	Title III, Section 313: Contains no Section 313 listed substances subject to reporting.
AICS (Australia):	Components listed
DSL (Canada):	Components listed
EINECS (Europe):	Components listed
TSCA:	Components listed

WHILE INFORMATION AND RECOMMENDATIONS SET FORTH HEREIN ARE BELIEVED TO BE ACCURATE AS OF THE DATE HEREON, PRECISION LABORATORIES, INC., MAKES NO WARRANTY WITH RESPECT THERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON.

N/R—Not Rated
N/D—Not Determined
N/A—Not Applicable
N/E—Not Established