

# Green Lawngr® Lineman® Pro

## Professional- choice turf paint

- Recommended for professional athletic fields
- Non-phytotoxic to turf
- Superior formulation for reduced rub off on uniforms
- Contains no hazardous chemicals or heavy metals

Exclusive **ColorLock™** Technology

## FOR PROFESSIONAL USE ONLY

Keep Out of Reach of Children

### GHS Signal Word: Danger

**Hazard Statement:** Causes serious eye damage.  
Causes skin irritation.

**Precautionary Statements (Prevention):** Wear protective gloves and eye/face protection. Avoid breathing dust/fume/gas/mist/vapours/spray. Contaminated work clothing should not be allowed out of the workplace. Wash with plenty of water and soap thoroughly after handling.

**Precautionary Statements (Response):** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician. IF ON SKIN (or hair): Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.



### Net Contents:

Before applying **Green Lawnger® Lineman® Pro Green**, cut turf to desired height. One gallon (3.78 L) of **Lineman Pro Green** will cover 2,000 - 4,000 sq ft (186-372 m<sup>2</sup>) of turf. Typically a 1:4 - 1:5 colorant-to-water ratio is recommended depending on desired color.

## Directions For Use

Shake well. Dilute one gallon (3.78 L) of **Lineman Pro Green** with 4 to 5 gallons (15-19 L) of water.

For a darker turf color, apply a second coat 24 hours after first application. Best results are obtained by making two lighter applications, (versus one heavier application).

Allow the first application to dry before the second application. Second application should be made perpendicular to the first application pattern. Utilize flat fan spray tips and small spray droplets to achieve uniform coverage.

**Equipment Notice:** BASF recommends the use of **Teflon®** seals to aid in the prevention of leaks when using **Lineman Pro Green** in centrifugal pumps. Standard ceramic seals may leak during operation.

## Application Tips:

A spray shield is recommended for applications if overspray or drift is a potential problem. If this product is mixed with pesticides, the entire mixture, including rinsate, must be handled and disposed of according to all applicable local, State, and Federal guidelines.

## Storage and Disposal

**Storage:** Segregate from foods and animal feeds. Keep from freezing. Keep away from heat. Protect from direct sunlight. Store in original container only and keep sealed.

**Waste Disposal of Substance:** Must be disposed of or incinerated in accordance with local regulations.

**Container Disposal:** Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

**Accidental Release Measures:** Do not discharge into the subsoil/soil. Do not discharge into drains/surface waters/groundwater. For small amounts: Pick up with suitable absorbent material (e.g. sand, sawdust, general-purpose binder, kieselguhr). For large amounts: Dike spillage, Pump off product. Dispose of absorbed material in accordance with regulations. Collect waste in suitable containers, which can be labeled and sealed. Clean contaminated floors and objects thoroughly with

water and detergents, observing environmental regulations.

## State Right To Know Description and CAS # / TSRN

Kaolin / 1332-58-7; Ester Alcohol / 25265-77-4; Propylene glycol / 57-55-6; Proprietary compound / TSRN 161090809-5100

## EMERGENCY CONTACT:

**CHEMTREC 1-800-424-9300**

**BASF Corporation 1-800-832-HELP (4357)**

## Conditions of Sale and Warranty

The **Directions For Use** of this product reflect the opinion of experts based on field use and tests. The directions are believed to be reliable and must be followed carefully. However, it is impossible to eliminate all risks inherently associated with the use of this product. Crop injury, ineffectiveness or other unintended consequences may result because of such factors as weather conditions, presence of other materials, or use of the product in a manner inconsistent with its labeling, all of which are beyond the control of BASF CORPORATION ("BASF") or the Seller. To the extent consistent with applicable law, all such risks shall be assumed by the Buyer. BASF warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes referred to in the **Directions For Use**, subject to the inherent risks, referred to above. **TO THE EXTENT CONSISTENT WITH APPLICABLE LAW, BASF MAKES NO OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS OR MERCHANTABILITY OR ANY OTHER EXPRESS OR IMPLIED WARRANTY. TO THE EXTENT CONSISTENT WITH APPLICABLE LAW, BUYER'S EXCLUSIVE REMEDY AND BASF'S EXCLUSIVE LIABILITY, WHETHER IN CONTRACT, TORT, NEGLIGENCE, STRICT LIABILITY, OR OTHERWISE, SHALL BE LIMITED TO REPAYMENT OF THE PURCHASE PRICE OF THE PRODUCT. TO THE EXTENT CONSISTENT WITH APPLICABLE LAW, BASF AND THE SELLER DISCLAIM ANY LIABILITY FOR CONSEQUENTIAL, EXEMPLARY, SPECIAL OR INDIRECT DAMAGES RESULTING FROM THE USE OR HANDLING OF THIS PRODUCT.** BASF and the Seller offer this product, and the Buyer and User accept it, subject to the foregoing **Conditions of Sale and Warranty** which may be varied only by agreement in writing signed by a duly authorized representative of BASF.

*ColorLock* is a trademark of BASF.

*Green Lawngrer* and *Lineman* are registered trademarks of BASF.

*Teflon* is a registered trademark of E.I. du Pont de Nemours and company or its affiliates.

© 2016 BASF Corporation  
All rights reserved.

GREEN LAWNGRER LINEMAN PRO SPEC 8/2016

BASF Corporation  
26 Davis Drive  
Research Triangle Park, NC 27709

  
We create chemistry