



SAFETY DATA SHEET HUMA GRO® Calcium

HMIS			
HEALTH	3		
FLAMMABILITY	0		
PHYSICAL HAZARD	0		
PPE	D		

SECTION 1:	CHEMICAL	PRODUCT & C	COMPANY IDEN	TIFICATION

PRODUCT IDENTIFIER: HUMA GRO® Calcium Product# 030

GENERAL USE: Used as a part of a plant nutrition program and in the production of plant nutrient products.

PRODUCT DESCRIPTION: A clear to slightly hazy, light amber liquid having a wintergreen type odor.

SUPPLIER INFORMATION: Bio Huma Netics, Inc.

1331 W Houston Avenue Gilbert, AZ 85233

For Additional SDS call: PHONE: (480) 961-1220

EMERGENCY PHONE NUMBERS

CHEMTREC: (In the USA) 800-424-9300

(International) 703-527-3887

SECTION 2: HAZARDS IDENTIFICATION

HAZARDS OVERVIEW: A clear to slightly hazy, light amber, strongly acidic liquid having a wintergreen type odor. The vapors, mists and liquid may be irritating or corrosive to all tissues contacted. Inhalation of mists may cause severe irritation or burns to the entire respiratory tract. Ingesting this product can be harmful or possibly fatal even if swallowed in a relatively small amount. **The NIOSH I.D.L.H. for Nitric Acid is: 25 ppm.**



CLASSIFICATION: SKIN CORROSION – CATEGORY 1A

SIGNAL WORD: DANGER

HAZARD STATEMENT: H314; causes severe skin burns and eye damage

PRECAUTIONARY STATEMENT: P260; Do not breathe dusts/mist/vapors. P280; Wear protective

gloves/protective clothing/eye protection/face protection P264; Wash hands thoroughly after handling

SECTION 3: COMPOSITION & INFORMATION ON INGREDIENTS ACGIH OSHA PEL_(TWA) **COMPONENT OSHA HAZARD** WT % STEL STEL CAS# TLV_(TWA) **Calcium Nitrate** 10124-37-5 Oxidizer; Eye, Skin & Respiratory Irritant; 36 ± 5 None None None None Toxic by Ingestion Nitric Acid 7697-37-2 Corrosive; Eye, Skin & Respiratory Hazard; 2 ± 0.5 None 2 ppm 4 ppm 2 ppm Lung toxin; Toxic by Ingestion

NDA = No Data Available N/A = Not Applicable

SECTION 4: FIRST AID MEASURES

INHALATION:

If inhaled, immediately move to fresh air. If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; use the Holger Nielsen method (back pressure-arm lift) or proper

respiratory device. If breathing is difficult, give oxygen. Call a physician.

In case of contact, immediately flush eyes with plenty of clean running water for at least 15 minutes, lifting the upper **EYE CONTACT:**

and lower lids occasionally. Remove contact lenses, if worn. Get medical attention immediately.

In case of contact, immediately flush skin with plenty of clean running water for at least 15 minutes, while removing SKIN CONTACT:

contaminated clothing and shoes. If burn or irritation occurs, call a physician.

If swallowed, DO NOT induce vomiting, unless directed to do so by medical personnel. Get medical attention **INGESTION:**

immediately. If victim is fully conscious, give plenty of water to drink. Never give anything by mouth to an

unconscious person.

NOTE TO PHYSICIANS: This product may be corrosive to all tissues contacted. If inhaled, delayed pulmonary edema may occur. If ingested, consideration should be given to careful endoscopy as stomach or esophageal burns, perforations or strictures may occur. Careful gastric lavage with an endotracheal tube in place should be considered. (Avoid using carbonate / bicarbonate lavage solutions as they may liberate a large volume of Carbon Dioxide gas and that could possibly damage or rupture internal organs from the pressure.) Treat exposure symptomatically.

SECTION 5: FIRE FIGHTING MEASURES

Flashpoint and Method: This product does not flash.

Flammable Limits (in air, % by volume) Lower: Not applicable Upper: Not applicable

Autoignition Temperature: Not applicable

GENERAL HAZARD: This product is an aqueous solution of an inorganic oxidizer and a strong inorganic acid. The Uniform Fire Code

physical hazard classification for this product is: Oxidizer, Class 1; the health hazard is: Corrosive (Acidic). This product may ignite or react with many substances. This product can generate flammable / explosive Hydrogen gas on contact with some metals (especially Aluminum, Magnesium and Zinc). Dilute solutions of this product may also be corrosive. This product may produce hazardous vapors and hazardous decomposition

products.

EXTINGUISHING MEDIA: Flood with water. FIRE FIGHTING INSTRUCTIONS:

Use water spray or fog to cool the containers exposed to the heat of a fire.

FIRE FIGHTING EQUIPMENT: Fire fighters should wear full protective equipment, including self-contained breathing

apparatus.

HAZARDOUS COMBUSTION PRODUCTS: When heated to dryness and decomposition, it emits toxic Nitric Acid vapors, nitrogen

oxides and calcium oxide, with trace or ultra-trace toxic oxide amounts, of phosphorus,

potassium, sulfur, iron, zinc, manganese, magnesium, sodium and carbon.

SECTION 6: ACCIDENTAL RELEASE MEASURES

RELEASE TO LAND:

Wearing recommended protective equipment and clothing, dike the spill and pick up the bulk of liquid using pumps or a vacuum truck, or absorb the liquid in sand or a commercial absorbent. Place in approved containers for recovery, disposal, or satellite accumulation. Neutralize the acidity, of the remaining liquid, using soda ash, lime, or other agent appropriate for neutralizing acidic liquids. Flush the spill area with water; collect the rinsates for disposal or sewer, as

appropriate.

RELEASE TO WATER:

Wear recommended protective equipment and clothing if contact with hazardous material can occur. Stop or divert water flow. Dike contaminated water and remove for disposal and/or treatment. As appropriate, notify all downstream

users of possible contamination.

SECTION 7: HANDLING AND STORAGE

STORAGE PRESSURE: Ambient STORAGE TEMPERATURE: Ambient

GENERAL: Store in a cool, dry, well-ventilated area away from incompatible materials and products. Avoid storing this product in direct sunlight. Do not allow this product to contact eyes, skin or clothing. Wear recommended personnel protective equipment when handling this product. Do not breathe vapors, mists or aerosols. Use only with adequate ventilation. Do

not ingest (drink) this product. Keep the container tightly closed when not in use. Wash thoroughly after handling this

product.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

CONTROL Use a local or general, mechanical exhaust ventilation system capable of maintaining emissions, in the work area,

MEASURES: below the OSHA-PEL, ACGIH-TLV or levels that may cause irritation.

RECOMMENDED PERSONAL PROTECTIVE EQUIPMENT

RESPIRATOR: For exposures above the OSHA-PEL or ACGIH-TLV, for Nitric Acid, up to 25 ppm: wear a full facepiece

supplied air respirator operated in the continuous flow mode. For exposures greater than 25 ppm, emergency situations or entry into unknown concentrations: wear a full facepiece self-contained breathing apparatus (SCBA) operated in the positive pressure mode; or wear a full facepiece supplied air respirator operated in the positive pressure mode, equipped with an auxiliary positive pressure SCBA. Note: Always consult the respirator

manufacturer's data when determining the suitability of respiratory protective devices prior to use.

EYES: Wear chemical goggles (recommended by ANSI Z87.1-1979), unless a full facepiece respirator is worn. Note:

Always consult the protective eyewear manufacturer's data when determining the suitability of protective eyewear

prior to use.

GLOVES: Wear 4H, Saranex, Barricade, Neoprene or Butyl Rubber gloves. Note: Always consult the glove manufacturer's

permeation data when determining the suitability of gloves prior to use.

CLOTHING &Wear a Neoprene or Butyl Rubber apron or full protective suit. An eye wash station and safety shower should be available in the work area. **Note:** Always consult the clothing/equipment manufacturer's permeation data when

determining the suitability of clothing/equipment prior to use.

FOOTWEAR: Wear Neoprene or Butyl Rubber boots, or Natural Rubber boots with 4H inserts. Note: Always consult the footwear

manufacturer's permeation data when determining the suitability of footwear prior to use.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES						
Appearance:	Clear to slightly hazy, light amber	Bulk Density (pounds/ft³):	Not applicable			
Physical State:	Liquid	Vapor Pressure:	No data available			
Odor:	Slight, acidic type	Vapor Density (air=1):	No data available			
Odor Threshold:	No data available	Evaporation Rate (n-Butyl Acetate=1):	No data available			
Molecular Formula:	Mixture	VOC Content / Organic Matter:	No data available / 0.03%			
Molecular Weight:	Not applicable	% Volatile:	No data available			
Boiling Point:	Greater than 100° C. (212° F.)	Solubility in H₂O:	Complete			
Freezing/Melting Point:	Less than 0° C. (32° F.)	Octanol/Water Partition Coefficient:	No data available			
Specific Gravity:	1.39 – 1.45 @ 20° C.	pH (as is):	≤1.00			
Density (pounds/gallon):	Approximately 11.6	pH (1% solution):	Less than 2.5			

SECTION 10: STABILITY AND REACTIVITY

GENERAL: This product is stable and hazardous polymerization will not occur.

CONDITIONS TO AVOID: Do not store this product below 50° F (10° C) or above 90° F (30° C)

INCOMPATIBLE MATERIAL: Caustics and alkali, all reducing agents, oxidizable inorganic compounds, turpentine, organic chemicals,

carbides, sulfides, sulfites, cyanides, chlorine releasers, most metals (especially Aluminum, Magnesium,

Zinc, etc.) and combustible materials.

HAZARDOUS DECOMPOSITION PRODUCTS: When heated to dryness and decomposition, it emits toxic Nitric Acid vapors, oxides

of nitrogen and calcium with trace or ultra-trace toxic oxide amounts of phosphorus,

potassium, sulfur, iron, zinc, manganese, magnesium, sodium and carbon.

SENSITIVITY TO MECHANICAL IMPACT: This product is not sensitive to mechanical impact.

SENSITIVITY TO STATIC DISCHARGE: This product is <u>not</u> sensitive to static discharge.

SECTION 11: TOXICOLOGICAL INFORMATION

Components: <u>Calcium Nitrate</u> <u>Nitric Acid</u>

Eye Contact: No data available No data available

Skin Contact: No data available No data available

Oral Rat LD50:302 mg/kgNo data availableDermal Rabbit LD50:No data availableNo data available

No data available

Human Data: No data available Oral Human LD_{Lo}: 430 mg/kg

Other Toxicological Data: No data available Unreported Route Man LD_{Lo}: 110 mg/kg

Carcinogenicity: No data available No data available

Teratogenicity: No data available Oral Rat TD_{Lo}: 21,150 mg/kg; Duration: (female 1-21 Days

Pregnant) Effects on Embryo or Fetus - Fetotoxicity

Mutagenicity: No data available No data available

Synergistic Products: None reported None reported

Target Organs: Eyes, Skin, Lungs, & Gastrointestinal tract Eyes, Skin, Mucous membranes, Lungs, Gastrointestinal tract

& Teeth

No data available

Medical Conditions

Inhalation Rat LC₅₀:

Aggravated By Exposure: Skin, Respiratory or Gastrointestinal disorders Skin, Respiratory or Gastrointestinal disorders

SECTION 12: ECOLOGICAL INFORMATION

ENVIRONMENTAL FATE:

This product is completely soluble in water and may significantly affect the pH of water. No specific environmental fate data is available. Inorganic products do not meet the definition of biodegradability.

ENVIRONMENTAL CONSIDERATIONS:

The aquatic toxicity of this product is related to the pH of the water. For Rainbow trout, the reported LC_{50} is about a pH of 4.0, for a 7-day bioassay. Some species may vary from this pH level but all are susceptible to acidic conditions.

SECTION 13: DISPOSAL CONSIDERATIONS

RCRA 40 CFR 261 CLASSIFICATON: Corrosive
U.S. EPA WASTE NUMBER/DESCRIPTION: D002

If this product is disposed of as shipped, it meets the criteria of a hazardous waste as defined under 40 CFR 261 due to its corrosivity. If this product becomes a waste, it will be a hazardous waste which is subject to the Land Disposal Restrictions under 40 CFR 268 and must be managed accordingly. As a hazardous liquid waste, it must be disposed of in accordance with local, state, and federal regulations in a permitted hazardous waste treatment, storage, and disposal facility.

SECTION 14: TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME: Corrosive Liquid, n.o.s. (Contains Nitric Acid)

Hazard Class: 8 UN Number: UN1760 Packing Group: ||

Primary Label: Corrosive Subsidiary Label(s): None

Primary/Subsidiary Placards: Corrosive

DOT Reportable Quantity (RQ): 1,000 pounds (Nitric Acid) RQ for Product: 25,000 pounds (2,161 gallons)

Marine Pollutant: No

2012 North American Emergency Response Guidebook No.: 154

TDG PROPER SHIPPING NAME: Corrosive Liquids, n.o.s. (Contains Nitric Acid)

Hazard Class: 8 UN Number: UN1760 Packing Group:

Primary Label: Corrosive Subsidiary Label(s): None

Primary/Subsidiary Placards: Corrosive

TDG Reportable Quantity (RQ): * At least 5kg or 5 liters

TDG Schedule XII: Not listed

Regulated Limit (RL): ** 50kg (Nitric Acid) RL for Product: 1,250kg (901.9 liters)

Other Shipping Information: None

SECTION 15: REGULATORY INFORMATION

COMPONENTS: <u>Calcium Nitrate</u> <u>Nitric Acid</u>

OSHA Target Organs: Eyes, Skin, Lungs, & Eyes, Skin, Mucous membranes,

Gastrointestinal tract Lungs, Gastrointestinal tract &

Teeth

Carcinogenic Potential:

 Regulated by OSHA:
 No
 No

 Listed on NTP Report:
 No
 No

 Listed by IARC:
 No
 No

IARC Group:

ACGIH Appendix A:

A1 Confirmed Human:

A2 Suspected Human:

Not applicable

Not applicable

Not applicable

Not applicable

Not applicable

Not applicable

U.S. EPA Requirements

Release Reporting

CERCLA (40 CFR 302)

Listed Substance: Not listed Yes

Reportable Quantity: Not applicable 1,000 pounds

Category: Not applicable C

RCRA Waste No.:

Unlisted Substance:

Reportable Quantity:

Characteristic:

RCRA Waste No.:

Not applicable

SARA TITLE III

Section 302 & 303 (40 CFR 355):

Listed Substance: Not listed Yes

Reportable Quantity: Not applicable 1,000 pounds Planning Threshold: Not applicable 1,000 pounds

^{*} Canadian Transportation of Dangerous Goods Regulations (TDGR), Part IX, Table I, Quantities or levels for Immediate Reporting: releases of reportable quantities, RQ, that meet the definition of a "dangerous occurrence" (a threat to life, health, property, or the environment) must be reported to the appropriate authorities as outlined in TDGR 9.13(1) and 9.14(1). ** Reporting to Environment Canada is required for any releases exceeding the regulated limits, RL, of 9.2 materials (primary or secondary). The regulated limits are found in Schedule XIII of the TDGR.

SECTION 15: REGULATORY INFORMATION (continued from page 4)

Section 311 & 312 (40 CFR 370):

Hazard Categories (product): Fire: N Sudden Release of Pressure: N Reactive: N Acute Health: Y Chronic Health: N

Planning threshold: 10,000 pounds 10,000 pounds

Section 313 (40 CFR 372):

Listed Toxic Chemical: Yes (Nitrate Compounds) Yes

Reporting Threshold: 10,000 pounds 10,000 pounds

U.S. TSCA Status

Listed (40 CFR 710): Yes Yes

State Regulations

State of California: Safe Drinking Water and Toxins Enforcement Act, 1986 (Proposition 65):

Carcinogen: No No Reproductive Toxin: No No No

Other Regulations

State Right To Know Laws: MA, NJ, PA, CA

Canadian Regulations

Product Information:

Controlled Product: Yes

WHMIS Hazard Symbols: Oxidizing Material; Corrosive Material

WHMIS Class & Division: C; E

Ingredient Information:

IDL Substance:NoYesDSL or NDSL Lists:DSLDSL

SECTION 16: OTHER INFORMATION

EPA Registration number: Not applicable

Approved Product Uses: Used as a part of a plant nutrition program.

Special Notes:

This product is not manufactured, or formulated to contain substances, which the State of California has found to cause cancer and/or birth defects or other reproductive harm.

Special instructions:

Store Calcium in a cool, dry, well-ventilated area, out of direct sunlight and away from incompatible materials or products. Do not add this product to hypochlorite bleaches, chlorine sanitizers or chlorinated cleaners as this liberates toxic, corrosive Chlorine gas.

SDS Revision Information: Revised Date: 9/03/2020

SDS Distributed by: Bio Huma Netics, Inc.

Prepared By: Frank S. Pidgeon, Sr. EHSS Director | Date Prepared: October 20, 2014

This Safety Data Sheet is provided as an information resource only. It should not be taken as a warranty or representation for which Bio Huma Netics, Inc. assumes legal liability. While Bio Huma Netics, Inc. believes the information contained herein is accurate and compiled from sources believed to be reliable, it is the responsibility of the user to investigate and verify its validity. The buyer assumes all responsibility of using and handling the product in accordance with applicable federal, state, and local regulations.