SAFETY DATA SHEET

MICROBURST 2-0-0



Section 1. Identification

Product identifier : MICROBURST 2-0-0

Product code : 1000883826, 100883829,1000883828, 1000883827

SDS # : 567

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Fertilizer.

Uses advised against

Not available.

Supplier's details : LOVELAND PRODUCTS, INC.

P.O. Box 1286

Greeley, CO 80632-1286

Telephone no. : 1-888-574-2878 (Customer Service)

Email: retail-SDS2@nutrien.com

Emergency telephone

number (with hours of operation)

: CHEMTREC: 1-800-424-9300 (24 hrs)

Medical Emergencies: 1-866-944-8565 (24 hrs)

Section 2. Hazards identification

OSHA/HCS status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture

: SERIOUS EYE DAMAGE - Category 1 TOXIC TO REPRODUCTION - Category 1B

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2

GHS label elements

Hazard pictograms





Signal word : Danger

Hazard statements : Causes serious eye damage.

May damage fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

General

: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

Prevention : Obtain special instructions before use. Do not handle until all safety precautions have

been read and understood. Wear protective gloves, protective clothing and eye or face

protection. Do not breathe vapor.

Response : IF exposed or concerned: Get medical advice or attention. IF IN EYES: Rinse

cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. Immediately call a POISON CENTER or doctor.

Storage : Store locked up.

Date of issue/Date of revision : 4/13/2023 Date of previous issue : No previous validation Version : 1 1/13

Section 2. Hazards identification

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazards not otherwise classified

: None known.

Section 3. Composition/information on ingredients

: Mixture Substance/mixture

Ingredient name	%	CAS number
manganese sulfate	5 - 10	7785-87-7
urea	1 - 5	57-13-6
zinc sulfate	1 - 5	7733-02-0
ferrous sulfate	1 - 5	7720-78-7
disodium octaborate	1 - 3	12008-41-2
copper sulfate	1 - 5	7758-98-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact

: CORROSIVE. Begin eye irrigation immediately. All eye exposures require medical evaluation following decontamination. Immediately rinse eyes with large quantities of water or saline for a minimum 30 minutes, longer irrigation time is preferred if possible. If possible, remove contact lenses being careful not to cause additional eye damage. If the initial water supply is insufficient, keep the affected area wet with a moist cloth and transfer the person to the nearest place where rinsing can be continued for the recommended length of time. Call an ambulance for transport to hospital. Continue eye irrigation during transport. For additional advice call the medical emergency number on this safety data sheet or your poison center or doctor.

Inhalation

: Remove person to fresh air. No known significant effects. Seek medical attention for any signs of wheezing and/or breathing difficulties. For additional advice call the medical emergency number on this SDS or your poison center or medical provider.

Skin contact

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Never give anything by mouth to an unconscious person. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Corrosive to eyes. Causes serious eye damage.

Inhalation : No known significant effects or critical hazards.

Skin contact Causes mild skin irritation.

: May be harmful if swallowed. Over-exposure by ingestion is unlikely under normal Ingestion working conditions.

Over-exposure signs/symptoms

2/13 Date of issue/Date of revision : 4/13/2023 Version:1 Date of previous issue : No previous validation

Section 4. First aid measures

Eye contact: Adverse symptoms may include the following:

pain watering redness

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

irritation redness

Ingestion: No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments

: Improved outcome requires prolonged rinsing or soaking with water in order to extract corrosive ions that have penetrated through the stratum corneum. Expert opinion indicates an extended duration of rinsing is required to remove corrosive chemicals - 60 minutes for strong alkalis, and 30 minutes for other corrosive substances. Water should be maintained at a comfortable temperature. It may be necessary to delay transport to emergency care facilities in order to to ensure 30 or 60 minutes of rinsing time. However, transporting the patient may be necessary depending on the condition of the patient or the availability of a water supply. If transport is necessary, rinsing the affected area should continue, if possible, during transport.

Protection of first-aiders

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Decontamination measures may be necessary. Personnel and equipment must be checked and decontaminated prior to leaving the area.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

Unsuitable extinguishing media

: None known.

surrounding fire.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

: Non-flammable. Material will not burn. Use an extinguishing agent suitable for the

Hazardous thermal decomposition products

: Decomposition products may include the following materials: carbon dioxide

carbon dioxide carbon monoxide nitrogen oxides sulfur oxides ammonia

Special protective actions for fire-fighters

: No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. Contain and collect the water used to fight the fire for later treatment and disposal.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Date of issue/Date of revision : 4/13/2023 Date of previous issue : No previous validation Version : 1 3/13

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused adverse impacts (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Approach release from upwind. Put on appropriate personal protective equipment (see Section 8). Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Use appropriate equipment to put the spilled substance in a container for reuse or disposal. Recycle to process, if possible.

or

Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Read label before use. Apply this product only as specified on the label. Do not handle until all safety precautions have been read and understood. Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Do not breathe vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Date of issue/Date of revision : 4/13/2023 Date of previous issue : No previous validation Version : 1 4/13

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

None.

Biological exposure indices

No exposure indices known.

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Contact your personal protective equipment supplier to verify the compatibility of the equipment for the intended purpose.

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/ or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

For U.S. work sites where respiratory protection is required, ensure that a respiratory protection program meeting 29 CFR 1910.134 requirements is in place.

Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state : Liquid.

Color : Green to brown. [Light]

Date of issue/Date of revision : 4/13/2023 Date of previous issue : No previous validation Version : 1 5/13

Section 9. Physical and chemical properties and safety characteristics

Odor : Slight.

Odor threshold : Not available.

pH : 3.5 [Conc. (% w/w): 100%]

Melting point/freezing point

Boiling point, initial boiling point, and boiling range

: Not available. : Not available.

Flash point [Product does not sustain combustion.]

: Non-flammable. **Flammability** Lower and upper explosion

limit/flammability limit

: Not applicable.

Vapor pressure

	Vapor Pressure at 20°C			Vapor pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
Water	23.8	3.2				

: Not available. **Relative vapor density**

Relative density 1.2

: 10.05 lb/gal **Bulk density**

Solubility(ies)

Media	Result
cold water hot water	Easily soluble Easily soluble

Solubility in water : Not available.

Miscible with water Yes.

Partition coefficient: n-

octanol/water

: Not applicable.

: Not applicable. **Auto-ignition temperature Decomposition temperature** : Not available. **Viscosity** : Not available.

Particle characteristics

Median particle size : Not applicable.

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : Extremes of temperature and direct sunlight. Keep away from incompatible materials.

: Strong oxidizers, strong reducing agents, strong acids, strong alkalis and halogenated Incompatible materials

compounds.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

6/13 Date of issue/Date of revision : 4/13/2023 Date of previous issue : No previous validation Version: 1

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
manganese sulfate	LD50 Oral	Rat	2150 mg/kg	-
urea	LD50 Oral	Rat	8471 mg/kg	-
ferrous sulfate	LD50 Oral	Rat	319 mg/kg	-
disodium octaborate	LD50 Oral	Rat	2 g/kg	-
copper sulfate	LD50 Oral	Rat	300 mg/kg	-

Conclusion/Summary

: May be harmful if swallowed.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
zinc sulfate	Eyes - Moderate irritant	Rabbit	-	420 ug	-

Conclusion/Summary

Skin : Causes mild skin irritation.Eyes : Causes serious eye damage.

Respiratory: No known significant effects or critical hazards.

Sensitization

Not available.

Conclusion/Summary

Skin: No known significant effects or critical hazards.Respiratory: No known significant effects or critical hazards.

Mutagenicity

Not available.

Conclusion/Summary

: No known significant effects or critical hazards.

Carcinogenicity

Not available.

Conclusion/Summary

Reproductive toxicity

Not available.

: No known significant effects or critical hazards.

Conclusion/Summary

: Contains material which may damage fertility or the unborn child if swallowed. (Boron compounds <3.0%)

Teratogenicity

Not available.

Conclusion/Summary

: Contains material which may cause developmental abnormalities, based on animal data. (Boron compounds <3.0%)

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Product/ingredient name		Route of exposure	Target organs
manganese sulfate	Category 2	-	-

Aspiration hazard

Not available.

Information on the likely routes of exposure

: Dermal contact. Eye contact. Ingestion.

Date of issue/Date of revision : 4/13/2023 Date of previous issue : No previous validation Version : 1 7/13

Section 11. Toxicological information

Potential acute health effects

Eye contact : Corrosive to eyes. Causes serious eye damage.

Inhalation : No known significant effects or critical hazards.

: Causes mild skin irritation. Skin contact

Ingestion : May be harmful if swallowed. Over-exposure by ingestion is unlikely under normal

working conditions.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:

> pain watering redness

Inhalation : No specific data.

Skin contact : Adverse symptoms may include the following:

> irritation redness

Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

effects

: Acute or intermediate exposure to excess manganese affects the respiratory system and the central nervous system. Inflammation of the lungs may occur after acute toxic inhalation. "Manganese pneumonia" has been reported in mine workers with clinical signs of alveolar inflammation, marked dyspnea, shallow respiration, facial cyanosis and an increased susceptibility to infection. Acute renal failure, abdominal pain, and mild methemoglobinemia have been reported following the ingestion of manganesecontaining products.

Potential delayed effects

See above.

Long term exposure

Potential immediate

effects

: See above.

Potential delayed effects

Inhalation of large quantities of manganese containing dust over many years may result in damage to the central nervous system, with symptoms of sleepiness, tremors and weakness in the legs, slurred speech, emotional disturbances, loss of balance, and in more advanced cases, an irreversible condition with symptoms similar to Parkinsons or Lou Gehrig's disease, including a mask-like facial expression, spastic gait, tremors, slurred speech, fatigue, anorexia, apathy, and inability to concentrate. The neurologic disorder that develops is known as "manganism". A syndrome may develop with symptoms of compulsive behavior, emotional volatility and hallucinations. High levels of manganese in the blood may increase anemia by interfering with iron absorption. Iron deficiency may increase an individual's susceptibility to manganese. Studies suggest that populations at risk of adverse effects due to manganese exposure are infants, and those with existing iron deficiency.

Potential chronic health effects

Not available.

General : May cause damage to organs through prolonged or repeated exposure.

Carcinogenicity : No known significant effects or critical hazards. : No known significant effects or critical hazards. Mutagenicity

Reproductive toxicity : May damage fertility or the unborn child.

Numerical measures of toxicity

Acute toxicity estimates

Date of issue/Date of revision Date of previous issue 8/13 : 4/13/2023 Version:1 : No previous validation

MICROBURST 2-0-0

Section 11. Toxicological information

Product/ingredient name	(3	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/ I)
MICROBURST 2-0-0 manganese sulfate urea zinc sulfate ferrous sulfate copper sulfate	4381.1 2150 8471 500 319 300	N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A N/A

Other information : Not available.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
manganese sulfate	Acute EC50 25700 μg/l Marine water	Algae - Phaeodactylum	96 hours
		tricornutum	
	Acute EC50 8.28 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 0.15 mg/l Fresh water	Crustaceans - Canthocamptus	48 hours
		sp Larvae	
	Acute LC50 3.32 mg/l Fresh water	Fish - Oncorhynchus mykiss -	96 hours
		Embryo	
	Chronic NOEC 1270 µg/l Fresh water	Fish - Pimephales promelas - Egg	28 days
urea	Acute EC50 6573.1 mg/l Fresh water	Crustaceans - Ceriodaphnia	48 hours
		dubia - Neonate	
	Acute EC50 3910000 µg/l Fresh water	Daphnia - Daphnia magna -	48 hours
	rease = 000 co rocco pg/r r recir mase.	Neonate	
	Acute LC50 22.5 ppt Fresh water	Fish - Oreochromis	96 hours
	riodio 2000 22.0 ppt i room water	mossambicus - Young	oo noaro
	Chronic NOEC 2 g/L Fresh water	Fish - Heteropneustes fossilis	30 days
zinc sulfate	Acute EC50 724.4 µg/l Fresh water	Algae - Stichococcus bacillaris	72 hours
Zino danate	Acute EC50 202 µg/l Marine water	Algae - Ulva fasciata - Zoea	96 hours
	Acute LC50 4 µg/l Fresh water	Crustaceans - Mesocyclops	48 hours
	Addic 2000 4 µg/11 resit water	hyalinus - Adult	40 Hours
	Acute LC50 21.8 µg/l Fresh water	Daphnia - Daphnia magna -	48 hours
	Addic 2000 21.0 pg/11 resit water	Neonate	40 Hours
	Acute LC50 2.36 μg/l Fresh water	Fish - Cirrhinus mrigala	96 hours
	Chronic NOEC 142.5 µg/l Marine water	Algae - Ulva fasciata - Zoea	96 hours
	Chronic NOEC 0.2 mg/l Marine water	Crustaceans - Litopenaeus	21 days
	Official NOLO 0.2 mg/r Marine water	vannamei - Post-larvae	Zidays
	Chronic NOEC 1.7 mg/l Fresh water	Daphnia - Daphnia magna -	21 days
	Chloric NOLC 1.7 hight resit water	Neonate	Ziuays
	Chronic NOEC 26 µg/l Fresh water	Fish - Jordanella floridae	100 days
ferrous sulfate	Acute EC50 143000 µg/l Fresh water	Crustaceans - Crangonyx	48 hours
ierrous sunate	Acute 2000 140000 µg/11 resit water	pseudogracilis - Adult	40 110013
	Acute EC50 7.2 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 1750 µg/l Fresh water	Fish - Salvelinus fontinalis	96 hours
copper sulfate	Acute EC50 0.4 µg/l Marine water	Algae - Isochrysis galbana	72 hours
copper sunate	Acute EC50 16.2 µg/l Fresh water	Aquatic plants - Lemna	96 hours
	Acute EC30 To.2 µg/I Fresh water	aequinoctialis	90 110015
	Acute EC50 1.4 μg/l Fresh water	Crustaceans - Bosmina	48 hours
	Acute EC50 1.4 µg/i Fresii water		46 110015
	Acute LC50 0.01 ng/ml Fresh water	longirostris - Neonate	10 hours
	Acute LOSO 0.01 fig/fill Fresh Water	Daphnia - Daphnia magna -	48 hours
	Aguto I CEO O 057 ug/l Eroob water	Neonate	06 hours
	Acute LC50 0.057 µg/l Fresh water	Fish - Cirrhinus mrigala	96 hours
	Chronic NOEC 0.0003 mg/l Marine water		72 hours
	Chronic NOTC 0 0040 // Freeh	Exponential growth phase	06 ba
	Chronic NOEC 0.0018 mg/l Fresh water	Aquatic plants - Lemna minor	96 hours

Date of issue/Date of revision: 4/13/2023Date of previous issue: No previous validationVersion: 1

Section 12. Ecological information

y	icai information		
	Chronic NOEC 5.06 μg/l Marine water	Crustaceans - Moina mongolica - Neonate	21 days
		Daphnia - Daphnia magna - Instar Fish - Acipenser transmontanus - Larvae	

Conclusion/Summary

: Toxic to aquatic life with long lasting effects. May be harmful to the environment if released in large quantities. Apply this product only as specified on the label.

Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
urea	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
urea	<-1.73	-	low
zinc sulfate	-0.07	60960	high
ferrous sulfate	-	20	low

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: Read label before use. Follow disposal instructions on label. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Triple rinse containers with water and add the rinse water to the spray tank. Do not reuse containers for any purpose. Disposal should be in accordance with applicable regional, national and local laws and regulations. Recycling decontaminated containers is the best option of container disposal. The Agricultural Container Recycling Council (ACRC) operates the national recycling program. To contact your state and local ACRC recycler visit the ACRC web page at http://www.acrecycle.org/. Do not contaminate water, food or feed by storage or disposal.

Section 14. Transport information

	DOT Classification	TDG Classification	IMDG	IATA
UN number	UN3082	UN3082	UN3082	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (copper sulfate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (zinc sulfate, copper sulfate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (zinc sulfate, copper sulfate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (zinc sulfate, copper sulfate)
Transport hazard class(es)	9	9	9	9
Packing group	III	III	III	III
Environmental hazards	Yes.	Yes.	Yes.	Yes.

Section 14. Transport information

Additional information

DOT Classification

: Non-bulk packages of this product are not regulated as hazardous materials unless transported by inland waterway. This product is not regulated as a hazardous material when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of §§ 173.24 and 173.24a.

TDG Classification

: Part 3 (Documentation) and Part 4 (Dangerous Goods Safety Marks) do not apply to substances that are classified as marine pollutants in accordance with section 2.43 of Part 2 (Classification) if they are in transport solely on land by road vehicle or railway vehicle.

Additional exceptions for shipment of less than a total of 450 kg or 450 L of this product by road vehicle or rail vehicle are provided under Special Provision 99 of the TDG

Regulations

IMDG
 This product is not regulated as a dangerous good when transported in sizes of ≤5 L or
 ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and

4.1.1.4 to 4.1.1.8.

in This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and

5.0.2.8.

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in the

event of an accident or spillage.

to IMO instruments

Transport in bulk according : Not available.

Section 15. Regulatory information

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Japan

Australia : Not determined.

Canada : All components are listed or exempted.

China : Not determined.

Eurasian Economic Union: Russian Federation inventory: All components are listed or exempted.

Japan inventory (CSCL): Not determined.
 Japan inventory (ISHL): Not determined.

New Zealand : All components are listed or exempted.

Philippines : Not determined.

Republic of Korea : Not determined.

Taiwan : All components are listed or exempted.

Thailand : Not determined.

Turkey : Not determined.

Date of issue/Date of revision : 4/13/2023 Date of previous issue : No previous validation Version : 1 11/13

Section 15. Regulatory information

United States

: All components are active or exempted.

Viet Nam

: All components are listed or exempted.

U.S. Federal regulations

: TSCA 4(a) final test rules: biuret; Urea, reaction products with formaldehyde

TSCA 8(a) PAIR: uronium hydrogen sulphate

TSCA 8(a) CDR Exempt/Partial exemption: Not determined Clean Water Act (CWA) 307: zinc sulfate; copper sulfate

Clean Water Act (CWA) 311: zinc sulfate; ferrous sulfate; copper sulfate

Clean Air Act Section 112

(b) Hazardous Air **Pollutants (HAPs)** : Listed

Clean Air Act Section 602

Class I Substances

: Not listed

Clean Air Act Section 602

Class II Substances

: Not listed

DEA List I Chemicals (Precursor Chemicals) : Not listed

DEA List II Chemicals (Essential Chemicals) : Not listed

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : SERIOUS EYE DAMAGE - Category 1

TOXIC TO REPRODUCTION - Category 1B

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	zinc sulfate	7785-87-7 7733-02-0 7758-98-7	5 - 10 1 - 5 1 - 5
Supplier notification	zinc sulfate	7785-87-7 7733-02-0 7758-98-7	5 - 10 1 - 5 1 - 5

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts : The following components are listed: zinc sulfate; ferrous sulfate; copper sulfate **New York** : The following components are listed: zinc sulfate; ferrous sulfate; copper sulfate **New Jersey** : The following components are listed: zinc sulfate; ferrous sulfate; copper sulfate

Pennsylvania : The following components are listed: manganese sulfate; zinc sulfate; ferrous sulfate;

copper sulfate

California Prop. 65

MARNING: This product can expose you to chemicals including Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Date of issue/Date of revision 12/13 : 4/13/2023 Date of previous issue Version: 1 : No previous validation

Section 16. Other information

History

Date of issue/Date of

revision

: 4/13/2023

Date of previous issue

: No previous validation

Version

: 1

Key to abbreviations

: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available SGG = Segregation Group UN = United Nations

Procedure used to derive the classification

Classification	Justification
TOXIC TO REPRODUCTION - Category 1B	Calculation method Calculation method Calculation method

Indicates information that has changed from previously issued version.

Notice to reader

Supply chain partners must ensure they pass this SDS, and all other relevant safety information to their customers.

DISCLAIMER AND LIMITATION OF LIABILITY

The information and recommendations contained in this Safety Data Sheet ("SDS") relate only to the specific material referred to herein (the "Material") and do not relate to the use of such Material in combination with any other material or process. The information and recommendations contained herein are believed to be current and correct as of the date of this SDS. HOWEVER, THE INFORMATION AND RECOMMENDATIONS ARE PRESENTED WITHOUT WARRANTY, REPRESENTATION OR LICENSE OF ANY KIND, EXPRESS OR IMPLIED, WITH RESPECT TO THEIR ACCURACY, CORRECTNESS OR COMPLETENESS, AND THE SELLER, SUPPLIER AND MANUFACTURER OF THE MATERIAL AND THEIR RESPECTIVE AFFILIATES (COLLECTIVELY, THE "SUPPLIER") DISCLAIM ALL LIABILITY FOR RELIANCE ON SUCH INFORMATION AND RECOMMENDATIONS. This SDS is not a guarantee of safety. A buyer or user of the Material (a "Recipient") is responsible for ensuring that it has all current information necessary to safely use the Material for its specific purpose.

FURTHERMORE, THE RECIPIENT ASSUMES ALL RISK IN CONNECTION WITH THE USE OF THE MATERIAL. THE RECIPIENT ASSUMES ALL RESPONSIBILITY FOR ENSURING THE MATERIAL IS USED IN A SAFE MANNER IN COMPLIANCE WITH APPLICABLE ENVIRONMENTAL, HEALTH, SAFETY AND SECURITY LAWS, POLICIES AND GUIDELINES. THE SUPPLIER DOES NOT WARRANT THE MERCHANTABILITY OF THE MATERIAL OR THE FITNESS OF THE MATERIAL FOR ANY PARTICULAR USE AND ASSUMES NO RESPONSIBILITY FOR INJURY OR DAMAGE CAUSED DIRECTLY OR INDIRECTLY BY OR RELATED TO THE USE OF THE MATERIAL.

Date of issue/Date of revision : 4/13/2023 Date of previous issue : No previous validation Version : 1 13/13