

PHT Latron B-1956

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : PHT Latron B-1956
Product code : M22901
Other means of identification : WA Reg. No. 7001-12001
CA Reg. No. 7001-50524

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

JR Simplot Company
P.O. Box 70013
Boise, ID 83707
T 1-208-336-2110

1.4. Emergency telephone number

Emergency number : CHEMTREC 1-800-424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Liq. 3 H226
Skin Irrit. 2 H315
Eye Irrit. 2B H320
STOT SE 3 H335
STOT SE 3 H336

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS02

GHS07

Signal word (GHS-US) : Warning

Hazard statements (GHS-US) : H226 - Flammable liquid and vapour
H315 - Causes skin irritation
H320 - Causes eye irritation
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness

Precautionary statements (GHS-US) : P210 - Keep away from heat/sparks/open flames/hot surfaces.
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical/ventilating/lighting/... equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray
P264 - Wash ... thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P302+P352 - If on skin: Wash with plenty of water/...
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P312 - Call a poison center/doctor/... if you feel unwell
P321 - Specific treatment (see ... on this label)

PHT Latron B-1956

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P332+P313 - If skin irritation occurs: Get medical attention
P337+P313 - If eye irritation persists: Get medical attention
P362 - Take off contaminated clothing and wash before reuse
P370+P378 - In case of fire: Use ... to extinguish
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/container to ... specify in accordance with local/regional/national regulations

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Modified phthalic glycerol alkyd resin	(CAS No) 67746-02-5		Not classified
1-butanol	(CAS No) 71-36-3		Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 STOT SE 3, H336

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : Allow victim to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.

First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Not expected to present a significant hazard under anticipated conditions of normal use.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

PHT Latron B-1956

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

PHT Latron B-1956		
ACGIH	Not applicable	
OSHA	Not applicable	
1-butanol (71-36-3)		
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	ACGIH STEL (ppm)	20 ppm
OSHA	Not applicable	
Modified phthalic glycerol alkyd resin (67746-02-5)		
ACGIH	Not applicable	
OSHA	Not applicable	

8.2. Exposure controls

Personal protective equipment : Avoid all unnecessary exposure.

Hand protection : Wear protective gloves.

Eye protection : Chemical goggles or safety glasses.

Respiratory protection : Wear appropriate mask.

Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

PHT Latron B-1956

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Appearance	: Brown liquid.
Colour	: brown
Odour	: Wine like
Odour threshold	: No data available
pH	: 7
Melting point	: \approx °C
Freezing point	: No data available
Boiling point	: 117 °C
Flash point	: 44 °C
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Vapour pressure	: No data available
Relative density	: No data available
Relative vapour density at 20 °C	: No data available
Solubility	: Water: Solubility in water of component(s) of the mixture : • 1-butanol: 8 g/100ml
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable. Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Extremely high temperatures. Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Oxidizing agent. Aluminum. Copper. Nickel. Magnesium. Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

1-butanol (71-36-3)	
LD50 oral rat	790 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Literature; 2293 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	3400 mg/kg (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity; 3430 mg/kg bodyweight; Rabbit)

PHT Latron B-1956

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1-butanol (71-36-3)	
LC50 inhalation rat (mg/l)	24 mg/l/4h (Rat)
LC50 inhalation rat (ppm)	8000 ppm/4h (Rat)
ATE US (oral)	790.000 mg/kg bodyweight
ATE US (dermal)	3400.000 mg/kg bodyweight
ATE US (gases)	8000.000 ppmv/4h
ATE US (vapours)	24.000 mg/l/4h
ATE US (dust,mist)	24.000 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation. pH: 7
Serious eye damage/irritation	: Causes eye irritation. pH: 7
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified Based on available data, the classification criteria are not met
Specific target organ toxicity (single exposure)	: May cause respiratory irritation. May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Potential adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

1-butanol (71-36-3)	
LC50 fish 1	1376 mg/l (96 h; Pimephales promelas; GLP)
LC50 other aquatic organisms 1	1200 mg/l (48 h; Xenopus laevis)
EC50 Daphnia 1	1328 mg/l (48 h; Daphnia magna; GLP)
LC50 fish 2	2300 mg/l (96 h; Alburnus alburnus)
EC50 Daphnia 2	1880 mg/l (24 h; Daphnia magna)
Threshold limit other aquatic organisms 1	1200 mg/l (48 h; Xenopus laevis; Toxicity test)
Threshold limit other aquatic organisms 2	280 mg/l (Pseudomonas putida)
Threshold limit algae 1	350 mg/l (Scenedesmus quadricauda; Toxicity test)
Threshold limit algae 2	100 mg/l (192 h; Microcystis aeruginosa)

12.2. Persistence and degradability

PHT Latron B-1956	
Persistence and degradability	Not established.
1-butanol (71-36-3)	
Persistence and degradability	Readily biodegradable in water. Low potential for adsorption in soil. Photolysis in the air. Not established.
Biochemical oxygen demand (BOD)	1.1 - 1.92 g O ₂ /g substance
Chemical oxygen demand (COD)	2.46 g O ₂ /g substance
ThOD	2.59 g O ₂ /g substance
BOD (% of ThOD)	0.33 - 0.79 % ThOD
Modified phthalic glycerol alkyd resin (67746-02-5)	
Persistence and degradability	Not established.

PHT Latron B-1956

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.3. Bioaccumulative potential

PHT Latron B-1956	
Bioaccumulative potential	Not established.
1-butanol (71-36-3)	
BCF other aquatic organisms 1	3.16
Log Pow	1 (Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method; 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4). Not established.
Modified phthalic glycerol alkyd resin (67746-02-5)	
Bioaccumulative potential	Not established.

12.4. Mobility in soil

1-butanol (71-36-3)	
Surface tension	0.025 N/m (20 °C)
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : NA1993 Combustible liquid, n.o.s., 3, III

UN-No.(DOT) : NA1993

Proper Shipping Name (DOT) : Combustible liquid, n.o.s.

Transport hazard class(es) (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Packing group (DOT) : III - Minor Danger

DOT Packaging Non Bulk (49 CFR 173.xxx) : 203

DOT Packaging Bulk (49 CFR 173.xxx) : 241

DOT Symbols : D - Proper shipping name for domestic use only, or to and from Canada,G - Identifies PSN requiring a technical name

DOT Special Provisions (49 CFR 172.102) : IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).
T1 - 1.5 178.274(d)(2) Normal..... 178.275(d)(2)
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / (1 + a (tr - tf))$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 60 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 220 L

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

PHT Latron B-1956

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Additional information

Other information : Non-Bulk Containers (<119 gallons): This product is not regulated by DOT
Bulk Containers (equal to or >119 gallons): NA1993, Combustible liquid, n.o.s. (Butyl Alcohol), 3, PG III
If transporting this material in bulk containers, greater than 2,500 gallon, please contact manufacturer for appropriate shipping information.

ADR

No additional information available

Transport by sea

UN-No. (IMDG) : 1993
Proper Shipping Name (IMDG) : FLAMMABLE LIQUID, N.O.S.
Class (IMDG) : 3 - Flammable liquids
Packing group (IMDG) : III - substances presenting low danger
Limited quantities (IMDG) : 5L

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

1-butanol	CAS No 71-36-3	
-----------	----------------	--

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

No additional information available

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

National regulations

No additional information available

15.3. US State regulations

No additional information available

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

PHT Latron B-1956

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2B	Serious eye damage/eye irritation, Category 2B
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H226	Flammable liquid and vapour
H302	Harmful if swallowed
H315	Causes skin irritation
H318	Causes serious eye damage
H320	Causes eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness

SDS US (GHS HazCom 2012)

Disclaimer: This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE CONCERNING THE INFORMATION HEREIN PROVIDED. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information nor do we offer warranty against patent infringement.