

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Substance
 Substance name : copper(II) sulfate, pentahydrate
 CAS No : 7758-99-8
 Formula : CuSO4.5H2O
 Synonyms : blue copper / blue copperras / blue stone / blue viking / blue vitriol / chalcantite / chalcantite, natural / copper sulfate, pentahydrate / copper sulphate, pentahydrate / copper vitriol / copper(2+) sulfate, pentahydrate / couperose bleue / CSP (=copper(II)sulfate, pentahydrate) / cupric sulfate, pentahydrate / Environmentally hazardous substance, solid, n.o.s. / phyto-bordeaux (=copper(II)sulfate, pentahydrate) / phyton-27 (=copper(II)sulfate, pentahydrate) / roman vitriol (=copper(II)sulfate, pentahydrate) / sulfacop / sulfuric acid, copper(2+) salt (1:1), pentahydrate / sulfuric acid, copper(II)salt, pentahydrate / triangle(=copper(II)sulfate, pentahydrate) / vencedor
 BIG no : 16466

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Algicide
 Fungicide
 Molluscicide
 Germicide
 Insecticide
 Food industry: additive
 industrial use: component
 Chemical raw material

1.3. Details of the supplier of the safety data sheet

Two Rivers Terminal
 3300 North Glade Road
 Pasco, Wa. 99302 - USA
 T 509-547-7776 - F 509-546-9508
www.tworiversterminal.com

1.4. Emergency telephone number

Emergency number : 24 Hour Emergency HAZMAT Response: (800) 229-5252; EPA National Response Center (800) 424-8802

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Acute Tox. 3 (Oral) H301
 Aquatic Acute 2 H401
 Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :  
 GHS06 GHS09

Signal word (GHS-US) : Danger
 Hazard statements (GHS-US) : H301 - Toxic if swallowed
 H401 - Toxic to aquatic life
 Precautionary statements (GHS-US) : P264 - Wash hands, forearms and face thoroughly after handling
 P270 - Do not eat, drink or smoke when using this product
 P273 - Avoid release to the environment
 P301+P310 - If swallowed: Immediately call a POISON CENTER, a doctor
 P321 - Specific treatment (see For further information see section 4 on this label)

copper(II) sulfate, pentahydrate

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P330 - Rinse mouth
P405 - Store locked up
P501 - Dispose of contents/container to an authorized waste collection point

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Name	Product identifier	%	Classification (GHS-US)
copper(II) sulfate, pentahydrate (Main constituent)	(CAS No) 7758-99-8	100	Acute Tox. 3 (Oral), H301 Aquatic Acute 2, H401

Full text of H-phrases: see section 16

3.2. Mixture

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with laboured breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital.
First-aid measures after inhalation	: Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.
First-aid measures after skin contact	: Wash immediately with lots of water. Do not apply (chemical) neutralizing agents. Take victim to a doctor if irritation persists.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Do not apply neutralizing agents. Take victim to an ophthalmologist if irritation persists.
First-aid measures after ingestion	: Rinse mouth with water. Immediately after ingestion: give lots of water to drink. Call Poison Information Centre (www.big.be/antigif.htm). Consult a doctor/medical service if you feel unwell. Ingestion of large quantities: immediately to hospital.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: AFTER INHALATION OF DUST: Dry/sore throat. Coughing. ON HEATING: Metal fume fever.
Symptoms/injuries after skin contact	: Tingling/irritation of the skin.
Symptoms/injuries after eye contact	: Irritation of the eye tissue.
Symptoms/injuries after ingestion	: Metal taste. Irritation of the oral mucous membranes. Nausea. Vomiting. Headache. Dizziness. Feeling of weakness. AFTER ABSORPTION OF HIGH QUANTITIES: Abdominal pain. Diarrhoea. Change in the haemogramme/blood composition. Change in urine composition. Disturbances of consciousness.
Chronic symptoms	: ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Red skin. Itching. Skin rash/inflammation. Feeling of weakness. Loss of weight. Coughing. Possible inflammation of the respiratory tract. Risk of pneumonia. Enlargement/affection of the liver.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: EXTINGUISHING MEDIA FOR SURROUNDING FIRES: Adapt extinguishing media to the environment.
Unsuitable extinguishing media	: No unsuitable extinguishing media known.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: DIRECT FIRE HAZARD. Non combustible. INDIRECT FIRE HAZARD. Reactions involving a fire hazard: see "Reactivity Hazard".
Explosion hazard	: DIRECT EXPLOSION HAZARD. No data available on direct explosion hazard. INDIRECT EXPLOSION HAZARD. No data available on indirect explosion hazard.

copper(II) sulfate, pentahydrate

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Reactivity : Reacts on exposure to water (moisture) with (some) metals. On burning: release of toxic and corrosive gases/vapours (sulphur oxides) and formation of metallic fumes. Reacts exothermically with (some) compounds: (increased) risk of fire. Reacts violently with (strong) reducers.

5.3. Advice for firefighters

Precautionary measures fire : Exposure to fire/heat: keep upwind. Exposure to fire/heat: consider evacuation. Exposure to fire/heat: have neighbourhood close doors and windows.

Firefighting instructions : Dilute toxic gases with water spray. Take account of environmentally hazardous firefighting water. Use water moderately and if possible collect or contain it.

Protection during firefighting : Heat/fire exposure: compressed air/oxygen apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Gloves. Face-shield. Protective clothing. Dust cloud production: compressed air/oxygen apparatus. Dust cloud production: dust-tight suit. See "Material-Handling" to select protective clothing.

Emergency procedures : Mark the danger area. Prevent dust cloud formation. No naked flames. Wash contaminated clothes. In case of reactivity hazard: consider evacuation.

Measures in case of dust release : In case of dust production: keep upwind. Dust production: have neighbourhood close doors and windows.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8 Exposure controls/personal protection".

6.2. Environmental precautions

Prevent soil and water pollution. Prevent spreading in sewers.

6.3. Methods and material for containment and cleaning up

For containment : Contain released substance, pump into suitable containers. Plug the leak, cut off the supply. Dam up the solid spill. Knock down/dilute dust cloud with water spray.

Methods for cleaning up : Prevent dispersion by covering with dry sand/earth. Scoop solid spill into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Wash clothing and equipment after handling.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8 : Exposure-controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Comply with the legal requirements. Remove contaminated clothing immediately. Clean contaminated clothing. Thoroughly clean/dry the installation before use. Do not discharge the waste into the drain. Avoid raising dust. Keep away from naked flames/heat. Observe strict hygiene. Keep container tightly closed. Measure the concentration in the air regularly. Carry operations in the open/under local exhaust/ventilation or with respiratory protection.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

Heat-ignition : KEEP SUBSTANCE AWAY FROM: heat sources.

Prohibitions on mixed storage : KEEP SUBSTANCE AWAY FROM: reducing agents. (strong) bases. water/moisture.

Storage area : Store in a dry area. Keep container in a well-ventilated place. Meet the legal requirements. Keep out of direct sunlight.

Special rules on packaging : SPECIAL REQUIREMENTS: hermetical. watertight. dry. clean. correctly labelled. meet the legal requirements. Secure fragile packagings in solid containers.

Packaging materials : SUITABLE MATERIAL: No data available. MATERIAL TO AVOID: No data available.

7.3. Specific end use(s)

No additional information available

copper(II) sulfate, pentahydrate

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

copper(II) sulfate, pentahydrate (7758-99-8)	
ACGIH	Not applicable
OSHA	Not applicable

8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Materials for protective clothing	: GIVE GOOD RESISTANCE: butyl rubber. PVC. viton.
Hand protection	: Gloves.
Eye protection	: Face shield. In case of dust production: protective goggles.
Skin and body protection	: Protective clothing. In case of dust production: head/neck protection. In case of dust production: dustproof clothing.
Respiratory protection	: Dust production: dust mask with filter type P2. Dust production: dust mask with filter type P3.
Environmental exposure controls	: Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Crystalline solid. Crystalline powder.
Color	: Blue
Odor	: Odourless
Odor threshold	: No data available
pH	: 4.0 (3.2 %)
pH solution	: 3.2 %
Melting point	: No data available
Freezing point	: Not applicable
Boiling point	: Not applicable
Flash point	: Not applicable
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: Not applicable
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: 2.3
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 2286 kg/m ³
Molecular mass	: 249.68 g/mol
Solubility	: Soluble in water. Soluble in methanol. Soluble in glycerol. Water: 23 g/100ml Ethanol: 16 g/100ml (18 °C)
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: Not applicable
Decomposition temperature	: > 110 °C
Viscosity	: No data available
Viscosity, kinematic	: Not applicable
Viscosity, dynamic	: No data available

9.2. Other information

VOC content	: Not applicable
Other properties	: Hygroscopic. Substance has acid reaction.

copper(II) sulfate, pentahydrate

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts on exposure to water (moisture) with (some) metals. On burning: release of toxic and corrosive gases/vapours (sulphur oxides) and formation of metallic fumes. Reacts exothermically with (some) compounds: (increased) risk of fire. Reacts violently with (strong) reducers.

10.2. Chemical stability

Hygroscopic.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Oral: Toxic if swallowed.

copper(II) sulfate, pentahydrate (7758-99-8)	
LD50 oral rat	300 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Experimental value; 482 mg/kg bodyweight; Rat)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit; Literature study; OECD 402: Acute Dermal Toxicity)
ATE US (oral)	300.000 mg/kg body weight

Skin corrosion/irritation	: Not classified pH: 4.0 (3.2 %)
Serious eye damage/irritation	: Not classified pH: 4.0 (3.2 %)
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: AFTER INHALATION OF DUST: Dry/sore throat. Coughing. ON HEATING: Metal fume fever.
Symptoms/injuries after skin contact	: Tingling/irritation of the skin.
Symptoms/injuries after eye contact	: Irritation of the eye tissue.
Symptoms/injuries after ingestion	: Metal taste. Irritation of the oral mucous membranes. Nausea. Vomiting. Headache. Dizziness. Feeling of weakness. AFTER ABSORPTION OF HIGH QUANTITIES: Abdominal pain. Diarrhoea. Change in the haemogramme/blood composition. Change in urine composition. Disturbances of consciousness.
Chronic symptoms	: ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Red skin. Itching. Skin rash/inflammation. Feeling of weakness. Loss of weight. Coughing. Possible inflammation of the respiratory tract. Risk of pneumonia. Enlargement/affection of the liver.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Dangerous for the environment.
Ecology - air	: Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009). Not included in the list of fluorinated greenhouse gases (Regulation (EC) No 842/2006). TA-Luft Klasse 5.2.1.

copper(II) sulfate, pentahydrate

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ecology - water : Ground water pollutant. Maximum concentration in drinking water: 2.0 mg/l (copper) (Directive 98/83/EC); 250 mg/l (sulfate) (Directive 98/83/EC). Highly toxic to fishes. Very toxic to invertebrates (Daphnia). Highly toxic to algae. pH shift.

copper(II) sulfate, pentahydrate (7758-99-8)	
LC50 fish 1	1.5 mg/l (24 h; Lepomis macrochirus; Toxicity test)
EC50 Daphnia 1	0.109 - 0.798 mg/l (48 h; Daphnia magna; Anhydrous form)
LC50 fish 2	0.17 mg/l (24 h; Salmo gairdneri (Oncorhynchus mykiss); Anhydrous form)
TLM fish 1	3.8 ppm 24 h; Salmo gairdneri (Oncorhynchus mykiss)
Threshold limit algae 1	0.01 - 0.28,72 h; Selenastrum capricornutum; Anhydrous form
Threshold limit algae 2	0.368 mg/l (72 h; Pseudokirchneriella subcapitata; Anhydrous form)

12.2. Persistence and degradability

copper(II) sulfate, pentahydrate (7758-99-8)	
Persistence and degradability	Biodegradability: not applicable. No (test)data on mobility of the substance available.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

12.3. Bioaccumulative potential

copper(II) sulfate, pentahydrate (7758-99-8)	
Bioaccumulative potential	Bioaccumable.

12.4. Mobility in soil

copper(II) sulfate, pentahydrate (7758-99-8)	
Ecology - soil	Toxic to flora.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Recycle/reuse. Precipitate/make insoluble. Remove to an authorized dump (Class I). Do not discharge into the sewer.

Additional information : LWCA (the Netherlands): KGA category 05. Hazardous waste according to Directive 2008/98/EC.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN3077 Environmentally hazardous substances, solid, n.o.s. (Copper Sulfate Pentahydrate), 9, III

UN-No.(DOT) : UN3077

Proper Shipping Name (DOT) : Environmentally hazardous substances, solid, n.o.s.
Copper Sulfate Pentahydrate

Hazard Classes (DOT) : 9 - Class 9 - Miscellaneous hazardous material 49 CFR 173.140

Hazard labels (DOT) : 9 - Class 9 (Miscellaneous dangerous materials)



copper(II) sulfate, pentahydrate

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Packing group (DOT)	: III - Minor Danger
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 213
DOT Packaging Bulk (49 CFR 173.xxx)	: 240
DOT Symbols	: G - Identifies PSN requiring a technical name
DOT Special Provisions (49 CFR 172.102)	: 8 - A hazardous substance that is not a hazardous waste may be shipped under the shipping description "Other regulated substances, liquid or solid, n.o.s.", as appropriate. In addition, for solid materials, special provision B54 applies. 146 - This description may be used for a material that poses a hazard to the environment but does not meet the definition for a hazardous waste or a hazardous substance, as defined in 171.8 of this subchapter, or any hazard class as defined in Part 173 of this subchapter, if it is designated as environmentally hazardous by the Competent Authority of the country of origin, transit or destination. 335 - Mixtures of solids that are not subject to this subchapter and environmentally hazardous liquids or solids may be classified as "Environmentally hazardous substances, solid, n.o.s," UN3077 and may be transported under this entry, provided there is no free liquid visible at the time the material is loaded or at the time the packaging or transport unit is closed. Each transport unit must be leak-proof when used as bulk packaging. A112 - Notwithstanding the quantity limits shown in Column (9A) and (9B) for this entry, the following IBCs are authorized for transportation aboard passenger and cargo-only aircraft. Each IBC may not exceed a maximum net quantity of 1,000 kg: a. Metal: 11A, 11B, 11N, 21A, 21B and 21N b. Rigid plastics: 11H1, 11H2, 21H1 and 21H2 c. Composite with plastic inner receptacle: 11HZ1, 11HZ2, 21HZ1 and 21HZ2 d. Fiberboard: 11G e. Wooden: 11C, 11D and 11F (with inner liners) f. Flexible: 13H2, 13H3, 13H4, 13H5, 13L2, 13L3, 13L4, 13M1 and 13M2 (flexible IBCs must be sift-proof and water resistant or must be fitted with a sift-proof and water resistant liner). B54 - Open-top, sift-proof rail cars are also authorized. IB8 - Authorized IBCs: Metal (11A, 11B, 11N, 21A, 21B, 21N, 31A, 31B and 31N); Rigid plastics (11H1, 11H2, 21H1, 21H2, 31H1 and 31H2); Composite (11HZ1, 11HZ2, 21HZ1, 21HZ2, 31HZ1 and 31HZ2); Fiberboard (11G); Wooden (11C, 11D and 11F); Flexible (13H1, 13H2, 13H3, 13H4, 13H5, 13L1, 13L2, 13L3, 13L4, 13M1 or 13M2). IP3 - Flexible IBCs must be sift-proof and water-resistant or must be fitted with a sift-proof and water-resistant liner. N20 - A 5M1 multi-wall paper bag is authorized if transported in a closed transport vehicle. T1 - 1.5 178.274(d)(2) Normal..... 178.275(d)(2) TP33 - The portable tank instruction assigned for this substance applies for granular and powdered solids and for solids which are filled and discharged at temperatures above their melting point which are cooled and transported as a solid mass. Solid substances transported or offered for transport above their melting point are authorized for transportation in portable tanks conforming to the provisions of portable tank instruction T4 for solid substances of packing group III or T7 for solid substances of packing group II, unless a tank with more stringent requirements for minimum shell thickness, maximum allowable working pressure, pressure-relief devices or bottom outlets are assigned in which case the more stringent tank instruction and special provisions shall apply. Filling limits must be in accordance with portable tank special provision TP3. Solids meeting the definition of an elevated temperature material must be transported in accordance with the applicable requirements of this subchapter.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 155
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: No limit
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: No limit
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

Additional information

Other information : No supplementary information available.

ADR

Transport document description	: UN 3077, 9, III, (E)
Packing group (ADR)	: III
Class (ADR)	: 9 - Miscellaneous dangerous substances and articles
Hazard identification number (Kemler No.)	: 90
Classification code (ADR)	: M7

copper(II) sulfate, pentahydrate

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (ADR) : 9 - Miscellaneous dangerous compounds



Orange plates



Tunnel restriction code (ADR) : E

Transport by sea

UN-No. (IMDG) : 3077
Proper Shipping Name (IMDG) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
Class (IMDG) : 9 - Miscellaneous dangerous compounds
Packing group (IMDG) : III - substances presenting low danger
EmS-No. (1) : F-A
EmS-No. (2) : S-F

Air transport

UN-No.(IATA) : 3077
Proper Shipping Name (IATA) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
Class (IATA) : 9 - Miscellaneous Dangerous Goods
Packing group (IATA) : III - Minor Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

copper(II) sulfate, pentahydrate (7758-99-8)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute Tox. 4 (Oral)	H302
Eye Irrit. 2	H319
Skin Irrit. 2	H315
Aquatic Acute 1	H400
Aquatic Chronic 1	H410

Full text of H-phrases: see section 16

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Xn; R22
Xi; R36/38
N; R50/53

Full text of R-phrases: see section 16

National regulations

No additional information available

15.3. US State regulations

SECTION 16: Other information

copper(II) sulfate, pentahydrate

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
H301	Toxic if swallowed
H401	Toxic to aquatic life

NFPA health hazard


: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard

: 0 - Materials that will not burn.

NFPA reactivity

: 2 - Normally unstable and readily undergo violent decomposition but do not detonate. Also: may react violently with water or may form potentially explosive mixtures with water.



SDS US (GHS HazCom 2012)

All information contained in this Safety Data Sheet is furnished free of charge and is intended for your evaluation. In our opinion the information is, as of the date of this Safety Data Sheet, reliable, however, it is your responsibility to determine the suitability of the information for your use. You are advised not to construe the information as absolutely complete since additional information may be necessary or desirable when particular, exceptional or variable conditions or circumstances exist or because of applicable laws or government regulations. Therefore, you should use this information only as a supplement to other information gathered by you, and you must make independent determinations of the suitability and completeness of the information from all sources to assure both proper use of the material described herein and the safety and health of employees. Accordingly, no guarantee is expressed or implied as to the results to be obtained based upon your use of the information.