



Material Safety Data Sheet

SECTAGON – K54

MSDS Number 2125 (Revised: (4/15/2013)

6 Pages

Section 1: CHEMICAL PRODUCT and COMPANY IDENTIFICATION

- 1.1 **Product Name** **SECTAGON-K54** **EPA REG # 61842-7**
 Chemical Family Dithiocarbamate salt solution
 Synonyms Potassium N-methyldithiocarbamate,
 N-Methyldithiocarbamic acid, potassium salt, Carbamic
 acid, N-methyldithio-,potassium salt,
 Formula C₂-H₄-N-S₂.K
- 1.2 **Manufacturer** Tessenderlo Kerley Inc.
 2255 N. 44th Street, Suite 300
 Phoenix, Arizona 85008-3279
 Information (602) 889-8300
- 1.3 **Emergency Contact** (866) 374-1975 (Tessenderlo Kerley)
(800) 424-9300 (CHEMTREC)

Section 2: COMPOSITION, INFORMATION ON INGREDIENTS

- 2.1 **Chemical Ingredients (% by wt.)**
 Potassium methylthiocarbamate CAS #:137-41-7 54%
 Inerts 46%

(See Section 8 for exposure guidelines)

Section 3: HAZARDS IDENTIFICATION

NFPA: Health - 2 Flammability - 0 Reactivity - 1

EMERGENCY OVERVIEW

Contact with skin or eyes may result in irritation.
 Repeated/prolonged skin contact may cause hypersensitivity type dermatitis.
 Inhalation may cause respiratory irritation.
 Prolonged exposure to air will result in gradual decomposition, to form methyl
 Isothiocyanate (MITC), which is poisonous.

Section 3: HAZARDS IDENTIFICATION Cont.**3.1 POTENTIAL HEALTH EFFECTS**

EYE: Contact with the eyes by may cause irritation or a burning sensation.

SKIN CONTACT: Contact with product may cause skin irritation. Repeated/prolonged skin contact may cause hypersensitivity type dermatitis.

SKIN ABSORPTION: Absorption is unlikely to occur.

INGESTION: Ingestion of product solution may cause irritation of the gastrointestinal tract to include nausea, vomiting and diarrhea. This product is classified as slightly toxic to humans.

INHALATION: Inhalation of product mist may cause irritation of the nose, throat and respiratory tract.

CHRONIC EFFECTS/CARCINOGENICITY: Not listed as a carcinogen by NTP, IARC or OSHA. See Section 11, Toxicological Information

Section 4: FIRST AID MEASURES

4.1 EYES: Immediately flush with large quantities of water for 15 minutes. Hold eyelids apart during irrigation to insure thorough flushing of the entire area of the eye and lids. Do not attempt to neutralize with chemical agents or use oils or ointments. Obtain immediate medical attention. Continue flushing if medical help not immediately available.

4.2 SKIN: Immediately flush with large quantities of water for 15 minutes. Remove contaminated clothing under a safety shower. Do not neutralize with chemical agents. Obtain medical attention if irritation occurs.

4.3 INGESTION: DO NOT INDUCE VOMITING. Give 1 or 2 glasses of water. If vomiting does occur, repeat fluid administration. If unconscious or convulsing, do not give fluids. Obtain immediate medical attention.

4.4 INHALATION: Remove victim from contaminated atmosphere. If breathing is labored, administer oxygen. If breathing has ceased, clear airway and start mouth to mouth resuscitation. If heart has stopped beating, external heart massage should be applied. Obtain immediate medical attention.

Section 5: FIRE FIGHTING MEASURES**5.1 FLAMMABLE PROPERTIES**

FLASH POINT: >200°F (93°C)

METHOD USED: Tag CC

5.2 FLAMMABLE LIMITS

Do data available. Not classified as a flammable/combustible.

5.3 EXTINGUISHING MEDIA: As appropriate for combustibles involved in fire.

5.4 FIRE & EXPLOSIVE HAZARDS: Heating will cause the release of MITC and hydrogen sulfide, both highly toxic and flammable gases. It is also conceivable that product breakdown from heating could release carbon disulfide and methylvamine, which are also toxic and flammable.

Section 5: FIRE FIGHTING MEASURES, Cont.

Keep containers/storage vessels in fire area cooled with water spray.

5.5 FIRE FIGHTING EQUIPMENT: Wear self-contained breathing apparatus, pressure demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1 Small releases: Confine and absorb small releases on sand, earth or other inert absorbent (clay, sawdust, straw, kitty litter, etc.). Sweep into open drums. Clean area with baking soda, soda ash (sodium carbonate) or common household detergent and a stiff brush and just enough water to make a slurry. Absorb and sweep into same open drum. Rinse area with water, absorb water and add to open drum. Close drum and dispose of material in accordance with federal and state governmental regulations.

6.2 Large releases: Confine area to qualified personnel. Shut off release if safe to do so. Dike spill area to prevent runoff into sewers, drains or surface waterways (potential toxicity). Recover as much of the solution as possible. Treat remaining material as a small release (above).

Section 7: HANDLING and STORAGE

7.1 Handling: Avoid contact with eyes. Use only in a well ventilated area. Wash thoroughly after handling. Avoid prolonged or repeated breathing of vapors. Avoid prolonged or repeated contact with the skin.

7.2 Storage: Store in cool, dry, well ventilated areas. Do not store combustibles in the area of storage vessels. Keep away from any sources of heat or flame. Store tote and smaller containers out of direct sunlight at moderate temperatures. Do not store at temperatures below 0°F (-18°C) as the product will crystallize at low temperatures. Warm or store at higher temperatures and mix to redissolve crystals before use. (See Section 10.4 for materials of construction)

Section 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

All personnel who handle this product in its end-use application should use this product only in accordance with its pesticide labeling and with the "Worker Protection Standard", 40 CFR 170.

8.1 RESPIRATORY PROTECTION: Personnel performing direct-contact activities must wear full face mask with SCBA or supplied air system or a cartridge respirator for organic vapors (with prefilter approved for pesticides – MSHA/NIOSH approved Number prefix TC-14G), or a NIOSH approved respirator with an organic vapor (OV) cartridge with any N, R, P or HE prefilter.

8.2 SKIN PROTECTION: Nitrile rubber gloves and apron should be worn to prevent contact with the liquid. Wash contaminated clothing prior to reuse. Under conditions where above normal levels of MITC may be encountered, protective clothing, gloves and boots should be polyethylene as MITC penetrates rubber.

8.3 EYE PROTECTION: Chemical goggles and a full face shield. DO NOT WEAR CONTACT LENSES.

Section	8:	EXPOSURE CONTROLS, PERSONAL PROTECTION, Cont.
----------------	-----------	--

8.4 EXPOSURE GUIDELINES:	OSHA		ACGIH	
	<u>TWA</u>	<u>STEL</u>	<u>TLV</u>	<u>STEL</u>
None	NA	NA	NA	NA

8.5 ENGINEERING CONTROLS: Use adequate exhaust ventilation to prevent inhalation of product vapors.

Section	9:	PHYSICAL and CHEMICAL PROPERTIES.
----------------	-----------	--

9.1 APPEARANCE:	Pale green through colorless to yellow/amber liquid.
9.2 ODOR:	Strong odor, sulfur and/or amine
9.3 BOILING POINT:	227 °F(108 °C)
9.4 VAPOR PRESSURE:	Not determined
9.5 VAPOR DENSITY:	Not determined
9.6 SOLUBILITY IN WATER:	Miscible with water (complete)
9.7 SPECIFIC GRAVITY:	1.273 (10.6 lbs/gal @25°C, typical))
9.8 FREEZING POINT:	Approx. 0 °F (-18 °C)
9.9 pH:	10.0 - 11.0
9.10 VOLATILE:	Not determined
9.11 Viscosity:	3.46 cp @ 20°C

Section	10:	STABILITY and REACTIVITY
----------------	------------	---------------------------------

10.1 STABILITY: This is a stable material

10.2 HAZARDOUS POLYMERIZATION: Will not occur

10.3 HAZARDOUS DECOMPOSITION PRODUCTS: Heating this product will evolve methyl isothiocyanate (MITC) and hydrogen sulfide (H₂S) and potentially carbon disulfide (CS₂) and methylamine (MMA). Heating to dryness will cause the production of oxides of nitrogen.

10.4 INCOMPATIBILITY: Prolonged exposure to air will result in decomposition to form methyl isothiocyanate (MITC) a very toxic and flammable material. Product solutions are corrosive to copper, zinc, or aluminum or any of their alloys such as brass, or galvanized materials. These materials of construction should not be used in handling systems or storage containers for this product. (SEE Section 7.2, Storage)

Section	11:	TOXICOLOGICAL INFORMATION
----------------	------------	----------------------------------

11.1 ORAL: Oral-Rat LD₅₀: 970 mg/Kg (male); 790 mg/Kg (female)

11.2 DERMAL: Dermal-rabbit LD₅₀ 1050 mg/Kg

11.3 INHALATION: Data not available

11.4 CHRONIC/CARCINOGENICITY: Laboratory studies have shown some developmental and carcinogenic effects in laboratory animals. Exposure monitoring studies conducted during agricultural applications of metam sodium have shown that human exposure is extremely low; therefore, any potential risk to humans from metam sodium is considered minimal.

Section	11:	TOXICOLOGICAL INFORMATION, Cont.
----------------	------------	---

11.5 TERATOLOGY: Data not available

11.6 REPRODUCTION: Data not available

11.7 MUTAGENICITY: Data not available

Section	12:	ECOLOGICAL INFORMATION
----------------	------------	-------------------------------

Data not available but is know to be toxic to fish.

Section	13:	DISPOSAL CONSIDERATIONS
----------------	------------	--------------------------------

Product by itself is not a listed waste but under spill or release conditions may exhibit characteristics of a hazardous waste in accordance with 40 CFR 261. Purification solids (as from filtering, evaporation, etc.) from the production of dithiocarbamate acid salts are a K161 listed hazardous waste. Dispose of released material in accordance with all federal, state or local regulations.

Section	14:	TRANSPORT INFORMATION
----------------	------------	------------------------------

14.1 DOT Shipping Name:	Corrosive liquid, basic, inorganic, n.o.s.	
14.2 DOT Hazard Class:	8	
14.3 UN/NA Number:	UN3266	
14.4 Packing Group:	II	
14.5 DOT Placard:	Corrosive	
14.6 DOT Label(s):	Corrosive	
14.7 IMO Shipping Name:	Corrosive liquid, basic, inorganic, n.o.s.	(UN3266)
14.8 RQ (Reportable Quantity):	NA	
14.9 RR STCC Number:	2879937/4934204	
14.10 DOT/IMO Mark	NA	

Section	15:	REGULATORY INFORMATION
----------------	------------	-------------------------------

15.1 OSHA: This product is listed as a hazardous material under criteria of the Federal OSHA Hazard Communication Standard, 29 CFR 1910.1200.

15.2 SARA TITLE III: a. **EHS** (Extremely Hazardous Substance) List: No

Section	15: REGULATORY INFORMATION, Cont.
----------------	--

b.	Section 311/312, (Tier I,II) Categories:	Immediate (acute)	Yes
		Fire	No
		Sudden release	No
		Reactivity	No
		Delayed (chronic)	No

c.	Section 313 (Toxic Release Reporting-Form R):	Yes
----	---	-----

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Concentration</u>
----------------------	-------------------	----------------------

Potassium N-methyldithiocarbamate	137-41-7	54%
-----------------------------------	----------	-----

d.	TPQ (Threshold Planning Quantity):	No
----	---	----

15.3 CERCLA/SUPERFUND:	RQ (Reportable Quantity)	No
-------------------------------	--------------------------	----

15.4 TSCA (Toxic Substance Control Act) Inventory List:	Yes
--	-----

15.5 RCRA (Resource Conservation and Recovery Act) Status:	NA, See Section 13
---	--------------------

15.6 WHMIS (Canada) Hazard Classification:	ND
---	----

15.7 DOT Hazardous Material: (See Section 14)	Yes
--	-----

15.8 CAA Hazardous Air Pollutant (HAP)	No
---	----

15.9 FIFRA Registered pesticide	Yes
	EPA REG # 61842-7 (RESTRICTED USE PESTICIDE)

15.10 Prop 65 (CA)	No
---------------------------	----

Section	16: OTHER INFORMATION
----------------	------------------------------

REVISIONS: The entire MSDS was reformatted to comply to ANSI Standard Z400.1-1993, by Technical Services-Tessengerlo Kerley, Inc.

Revised Product name & registration AND Section 8, 5/31/06

Revised Boiling Point, Section 9.3, 7/10/2006.

Revised MSDS Number and SG and pH in Section 9, 10/5/06

Revised Section 1.3, Emergency Contact, 7/14/09.

Revised Section 15.9, RUP. 4/15/2013

<p>THE INFORMATION PUBLISHED IN THIS MATERIAL SAFETY DATA SHEET HAS BEEN COMPILED FROM OUR EXPERIENCE AND OSHA, ANSI, NFPA, DOT, ERG, AND CHRIS. IT IS THE USER'S RESPONSIBILITY TO DETERMINE THE SUITABILITY OF THIS INFORMATION FOR THE ADOPTION OF NECESSARY SAFETY PRECAUTIONS. WE RESERVE THE RIGHT TO REVISE MATERIAL SAFETY DATA SHEETS PERIODICALLY AS NEW INFORMATION BECOMES AVAILABLE.</p>
