

Safety Data Sheet

ULTRA-PURE OIL

Revision date : 2016/11/28
Version: 3.0

Page: 1/12
(30473446/SDS_CPA_US/EN)

1. Identification

Product identifier used on the label

ULTRA-PURE OIL

Recommended use of the chemical and restriction on use

Recommended use*: insecticide

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Substance number: 417476
EPA Registration number: 69526-5-499
Synonyms: Petroleum oil mixture

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Asp. Tox. 1 Aspiration hazard

Label elements

Pictogram:

Safety Data Sheet

ULTRA-PURE OIL

Revision date : 2016/11/28
Version: 3.0

Page: 2/12
(30473446/SDS_CPA_US/EN)



Signal Word:
Danger

Hazard Statement:
H304 May be fatal if swallowed and enters airways.

Precautionary Statements (Response):
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P331 Do NOT induce vomiting.

Precautionary Statements (Storage):
P405 Store locked up.

Precautionary Statements (Disposal):
P501 Dispose of contents/container to hazardous or special waste collection point.

Hazards not otherwise classified

Labeling of special preparations (GHS):

The following percentage of the mixture consists of components(s) with unknown hazards regarding the acute toxicity: 2 % dermal

The following percentage of the mixture consists of components(s) with unknown hazards regarding the acute toxicity: 2 % oral

The following percentage of the mixture consists of components(s) with unknown hazards regarding the acute toxicity: 2 % Inhalation - vapour

The following percentage of the mixture consists of components(s) with unknown hazards regarding the acute toxicity: 2 % Inhalation - mist

According to Regulation 1994 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Emergency overview

CAUTION:
KEEP OUT OF REACH OF CHILDREN.
KEEP OUT OF REACH OF DOMESTIC ANIMALS.
HARMFUL IF SWALLOWED.
HARMFUL IF ABSORBED THROUGH SKIN.
Repeated or prolonged skin contact may cause allergic skin reactions in sensitive individuals.
Potential sensitizer.
Moderately irritating to the eyes.
Avoid contact with the skin, eyes and clothing.
Avoid inhalation of mists/vapours.
Wash thoroughly after handling.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Weight %</u>	<u>Chemical name</u>
8042-47-5	98.0 %	White mineral oil (petroleum)

Safety Data Sheet

ULTRA-PURE OIL

Revision date : 2016/11/28
Version: 3.0

Page: 3/12
(30473446/SDS_CPA_US/EN)

According to Regulation 1994 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Weight %</u>	<u>Chemical name</u>
8042-47-5	98.0 %	White mineral oil (petroleum)
	2.0 %	Proprietary ingredients

4. First-Aid Measures

Description of first aid measures

General advice:

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

If on skin:

Immediately wash thoroughly with soap and water, seek medical attention.

If in eyes:

Remove contact lenses, if present. Wash affected eyes for at least 15 minutes under running water with eyelids held open. Seek medical attention.

If swallowed:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Do not induce vomiting due to aspiration hazard.

Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11., Further important symptoms and effects are so far not known.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Additional information:

Use extinguishing measures to suit surroundings.

Special hazards arising from the substance or mixture

Hazards during fire-fighting:

carbon monoxide, carbon dioxide, fumes/smoke, unburned hydrocarbons, carbon oxides
The substances/groups of substances mentioned can be released in case of fire.

Safety Data Sheet

ULTRA-PURE OIL

Revision date : 2016/11/28
Version: 3.0

Page: 4/12
(30473446/SDS_CPA_US/EN)

Advice for fire-fighters

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Evacuate area of all unnecessary personnel. Contain contaminated water/firefighting water. Do not allow to enter drains or waterways.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Take appropriate protective measures. Clear area. Shut off source of leak only under safe conditions. Extinguish sources of ignition nearby and downwind. Ensure adequate ventilation. Wear suitable personal protective clothing and equipment.

Environmental precautions

Do not discharge into the subsoil/soil. Do not discharge into drains/surface waters/groundwater. Contain contaminated water/firefighting water. A spill of or in excess of the reportable quantity requires notification to state, local and national emergency authorities. This product is not regulated by CERCLA ('Superfund').

Methods and material for containment and cleaning up

Dike spillage. Pick up with suitable absorbent material. Spilled substance/product should be recovered and applied according to label rates whenever possible. If application of spilled substance/product is not possible, then spills should be contained, solidified, and placed in suitable containers for disposal. After decontamination, spill area can be washed with water. Collect wash water for approved disposal.

7. Handling and Storage

Precautions for safe handling

RECOMMENDATIONS ARE FOR MANUFACTURING, COMMERCIAL BLENDING, AND PACKAGING WORKERS. PESTICIDE APPLICATORS & WORKERS must refer to the Product Label and Directions for Use attached to the product. Provide good ventilation of working area (local exhaust ventilation if necessary). Keep away from sources of ignition - No smoking. Keep container tightly sealed. Protect against heat. Handle and open container with care. Do not open until ready to use. Once container is opened, content should be used as soon as possible. Provide means for controlling leaks and spills. Follow label warnings even after container is emptied. The substance/product may be handled only by appropriately trained personnel. Avoid all direct contact with the substance/product. Avoid contact with the skin, eyes and clothing. Avoid inhalation of dusts/mists/vapours. Wear suitable personal protective clothing and equipment.

Protection against fire and explosion:

The relevant fire protection measures should be noted. Fire extinguishers should be kept handy. Avoid all sources of ignition: heat, sparks, open flame. Avoid extreme heat. Ground all transfer equipment properly to prevent electrostatic discharge. Electrostatic discharge may cause ignition.

Conditions for safe storage, including any incompatibilities

Segregate from incompatible substances. Segregate from foods and animal feeds. Segregate from textiles and similar materials.

Further information on storage conditions: Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame. Protect containers from physical damage. Protect against contamination. The authority permits and storage regulations must be observed.

Safety Data Sheet

ULTRA-PURE OIL

Revision date : 2016/11/28
Version: 3.0

Page: 5/12
(30473446/SDS_CPA_US/EN)

Storage stability:

May be kept indefinitely if stored properly.

If an expiry date is mentioned on the packaging/label this takes priority over the statements on storage duration in this safety data sheet.

8. Exposure Controls/Personal Protection

Users of a pesticidal product should refer to the product label for personal protective equipment requirements.

Components with occupational exposure limits

White mineral oil (petroleum)	OSHA PEL	PEL 5 mg/m3 Mist ; TWA value 5 mg/m3 Mist ;
	ACGIH TLV	TWA value 5 mg/m3 Inhalable fraction ;

Advice on system design:

Whenever possible, engineering controls should be used to minimize the need for personal protective equipment.

Personal protective equipment

RECOMMENDATIONS FOR MANUFACTURING, COMMERCIAL BLENDING, AND PACKAGING WORKERS:

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator. For situations where the airborne concentrations may exceed the level for which an air purifying respirator is effective, or where the levels are unknown or Immediately Dangerous to Life or Health (IDLH), use NIOSH-certified full facepiece pressure demand self-contained breathing apparatus (SCBA) or a full facepiece pressure demand supplied-air respirator (SAR) with escape provisions.

Hand protection:

Chemical resistant protective gloves, Protective glove selection must be based on the user's assessment of the workplace hazards.

Eye protection:

Safety glasses with side-shields. Tightly fitting safety goggles (chemical goggles). Wear face shield if splashing hazard exists.

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. head protection, apron, protective boots, chemical-protection suit.

General safety and hygiene measures:

RECOMMENDATIONS FOR MANUFACTURING, COMMERCIAL BLENDING, AND PACKAGING WORKERS Wear long sleeved work shirt and long work pants in addition to other stated personal protective equipment. Work place should be equipped with a shower and an eye wash. Handle in accordance with good industrial hygiene and safety practice. Personal protective equipment should be decontaminated prior to reuse. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks). Take off immediately all contaminated clothing. Store work clothing separately. Hands and/or face should be washed before breaks and at the end of the shift. No eating, drinking, smoking or tobacco use at the place of work. Keep away from food, drink and animal feeding stuffs.

Safety Data Sheet

ULTRA-PURE OIL

Revision date : 2016/11/28
Version: 3.0

Page: 6/12
(30473446/SDS_CPA_US/EN)

9. Physical and Chemical Properties

Form:	liquid
Odour:	faint odour, of petroleum
Odour threshold:	Not determined due to potential health hazard by inhalation.
Colour:	colourless to slightly yellow
pH value:	not applicable
Melting point:	not determined
Boiling point:	The product has not been tested.
Flash point:	173 °C (Cleveland open cup) (other)
Flammability:	not readily ignited
Lower explosion limit:	As a result of our experience with this product and our knowledge of its composition we do not expect any hazard as long as the product is used appropriately and in accordance with the intended use.
Upper explosion limit:	As a result of our experience with this product and our knowledge of its composition we do not expect any hazard as long as the product is used appropriately and in accordance with the intended use.
Autoignition:	not determined
Vapour pressure:	negligible No data available.
Density:	approx. 0.85 g/cm ³ (15 °C)
Vapour density:	not applicable
Partitioning coefficient n-octanol/water (log Pow):	not applicable
Self-ignition temperature:	Based on its structural properties the product is not classified as self-igniting.
Thermal decomposition:	carbon monoxide, carbon dioxide, nitrogen dioxide, nitrogen oxide Stable at ambient temperature. If product is heated above decomposition temperature toxic vapours may be released. To avoid thermal decomposition, do not overheat. No decomposition if stored and handled as prescribed/indicated.
Viscosity, kinematic:	9.6 mm ² /s (40 °C)
Solubility in water:	insoluble
Evaporation rate:	not applicable
Other Information:	If necessary, information on other physical and chemical parameters is indicated in this section.

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:

Corrosive effects to metal are not anticipated.

Safety Data Sheet

ULTRA-PURE OIL

Revision date : 2016/11/28
Version: 3.0

Page: 7/12
(30473446/SDS_CPA_US/EN)

Oxidizing properties:

Based on its structural properties the product is not classified as oxidizing.

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

The product is chemically stable.

No hazardous reactions if stored and handled as prescribed/indicated.

Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame. Avoid prolonged storage. Avoid electro-static discharge. Avoid contamination. Avoid prolonged exposure to extreme heat. Avoid extreme temperatures.

Incompatible materials

strong acids, strong bases, strong oxidizing agents

Hazardous decomposition products

Decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated., Prolonged thermal loading can result in products of degradation being given off.

Hazardous decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated., Prolonged thermal loading can result in products of degradation being given off.

Thermal decomposition:

Possible thermal decomposition products:

carbon monoxide, carbon dioxide, nitrogen dioxide, nitrogen oxide

Stable at ambient temperature. If product is heated above decomposition temperature toxic vapours may be released. To avoid thermal decomposition, do not overheat.

No decomposition if stored and handled as prescribed/indicated.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Slightly toxic after single ingestion. Slightly toxic after short-term skin contact. Relatively nontoxic after short-term inhalation.

Oral

Information on: White mineral oil (petroleum)

Type of value: LD50

Species: rat

Value: > 5,000 mg/kg

Inhalation

Safety Data Sheet

ULTRA-PURE OIL

Revision date : 2016/11/28
Version: 3.0

Page: 8/12
(30473446/SDS_CPA_US/EN)

Information on: White mineral oil (petroleum)

Type of value: LC50

Species: rat

Value: > 5.2 mg/l

Exposure time: 4 h

An aerosol was tested.

Dermal

Information on: White mineral oil (petroleum)

Type of value: LD50

Species: rabbit

Value: > 2,000 mg/kg

Irritation / corrosion

Assessment of irritating effects: May cause slight but temporary irritation to the eyes. May cause slight irritation to the skin.

Skin

Species: rabbit

Result: non-irritant

Eye

Species: rabbit

Result: non-irritant

Sensitization

Assessment of sensitization: The product has not been tested. The statement has been derived from the properties of the individual components.

Information on: White mineral oil (petroleum)

Assessment of sensitization:

There is no evidence of a skin-sensitizing potential.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: The product has not been tested. The statement has been derived from the properties of the individual components. No substance-specific organotoxicity was observed after repeated administration to animals.

Genetic toxicity

Assessment of mutagenicity: The product has not been tested. The statement has been derived from the properties of the individual components. Mutagenicity tests revealed no genotoxic potential.

Carcinogenicity

Assessment of carcinogenicity: The product has not been tested. The statement has been derived from the properties of the individual components. The results of various animal studies gave no indication of a carcinogenic effect.

Reproductive toxicity

Assessment of reproduction toxicity: The product has not been tested. The statement has been derived from the properties of the individual components. The results of animal studies gave no indication of a fertility impairing effect.

Safety Data Sheet

ULTRA-PURE OIL

Revision date : 2016/11/28
Version: 3.0

Page: 9/12
(30473446/SDS_CPA_US/EN)

Teratogenicity

Assessment of teratogenicity: The product has not been tested. The statement has been derived from the properties of the individual components. Animal studies gave no indication of a developmental toxic effect at doses that were not toxic to the parental animals.

Other Information

Misuse can be harmful to health.

Symptoms of Exposure

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11., Further important symptoms and effects are so far not known.

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

The product has not been tested. The statement has been derived from the properties of the individual components.

Aquatic toxicity

Information on: White mineral oil (petroleum)

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms.

Toxicity to fish

Information on: White mineral oil (petroleum)

LL50 (96 h) > 10,000 mg/l, Leuciscus idus (OECD Guideline 203, static)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. Limit concentration test only (LIMIT test).

Analogous: Assessment derived from products with similar chemical character.

Aquatic invertebrates

Information on: White mineral oil (petroleum)

LL50 (48 h) > 100 mg/l, Daphnia magna (OECD Guideline 202, part 1, static)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. Nominal concentration.

Analogous: Assessment derived from products with similar chemical character.

Aquatic plants

Information on: White mineral oil (petroleum)

Lowest observed effect concentration (72 h) < 100 mg/l (growth rate), Pseudokirchneriella subcapitata (OECD Guideline 201, static)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. Nominal concentration. Limit concentration test only (LIMIT test).

Analogous: Assessment derived from products with similar chemical character.

Safety Data Sheet

ULTRA-PURE OIL

Revision date : 2016/11/28
Version: 3.0

Page: 10/12
(30473446/SDS_CPA_US/EN)

Chronic toxicity to fish

Information on: White mineral oil (petroleum)
Study scientifically not justified.

Chronic toxicity to aquatic invertebrates

Information on: White mineral oil (petroleum)
(21 d) 10 mg/l, Daphnia magna (OECD Guideline 211, semistatic)
The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. Nominal concentration.

Persistence and degradability

Assessment biodegradation and elimination (H2O)

The product has not been tested. The statement has been derived from the properties of the individual components.

Elimination information

Inherently biodegradable.

Assessment biodegradation and elimination (H2O)

Information on: White mineral oil (petroleum)

Not readily biodegradable (by OECD criteria). Moderately/partially biodegradable.

Mobility in soil

Assessment transport between environmental compartments

The product has not been tested. The statement has been derived from the properties of the individual components.

Information on: White mineral oil (petroleum)

Study does not need to be conducted.

Additional information

Other ecotoxicological advice:
The product has not been tested.

Do not discharge product into the environment without control.

13. Disposal considerations

Waste disposal of substance:

Pesticide wastes are regulated. If pesticide wastes cannot be disposed of according to label instructions, contact the State Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

Safety Data Sheet

ULTRA-PURE OIL

Revision date : 2016/11/28
Version: 3.0

Page: 11/12
(30473446/SDS_CPA_US/EN)

Must be sent to a suitable incineration plant, observing local regulations.

Container disposal:

Rinse thoroughly at least three times (triple rinse) in accordance with EPA recommendations. Consult state or local disposal authorities for approved alternative procedures such as container recycling. Recommend crushing, puncturing or other means to prevent unauthorized use of used containers.

14. Transport Information

Land transport

USDOT

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US blocked / not listed

Crop Protection TSCA, US released / exempt

EPCRA 311/312 (Hazard categories): Acute; Fire

State regulations

State RTK

PA

MA

NJ

CAS Number

8042-47-5

8042-47-5

8042-47-5

Chemical name

White mineral oil (petroleum)

White mineral oil (petroleum)

White mineral oil (petroleum)

16. Other Information

SDS Prepared by:

BASF NA Product Regulations

SDS Prepared on: 2016/11/28

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in

Safety Data Sheet

ULTRA-PURE OIL

Revision date : 2016/11/28
Version: 3.0

Page: 12/12
(30473446/SDS_CPA_US/EN)

a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.
END OF DATA SHEET