

# Water Guard WG 4500

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 11/13/2019

Revision date: 05/11/2023

Version: 1.2

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Product name : Water Guard WG 4500  
Product code : M80031

#### 1.2. Recommended use and restrictions on use

#### 1.3. Supplier

Simplot AB Retail, Inc.  
P.O. Box 9296  
Boise, ID 83707

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC 1-800-424-9300

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

Oxidizing liquids Category 1	H271 May cause fire or explosion; strong oxidizer
Corrosive to metals Category 1	H290 May be corrosive to metals
Acute toxicity (oral) Category 4	H302 Harmful if swallowed
Skin corrosion/irritation Category 1	H314 Causes severe skin burns and eye damage
Serious eye damage/eye irritation Category 1	H318 Causes serious eye damage

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

##### GHS US labeling

Hazard pictograms (GHS US)



Signal word (GHS US)

: Danger

Hazard statements (GHS US)

: H227 - Combustible liquid  
H271 - May cause fire or explosion; strong oxidizer  
H290 - May be corrosive to metals  
H302 - Harmful if swallowed  
H314 - Causes severe skin burns and eye damage  
H318 - Causes serious eye damage

Precautionary statements (GHS US)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P220 - Keep/Store away from clothing and other combustible materials  
P221 - Take any precaution to avoid mixing with combustibles  
P234 - Keep only in original container.  
P260 - Do not breathe dust/fume/gas/mist/vapors/spray.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P270 - Do not eat, drink or smoke when using this product.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
P283 - Wear fire/flammable resistant/retardant clothing.  
P301+P312 - If swallowed: Call a doctor if you feel unwell  
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

# Water Guard WG 4500

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P306+P360 - If on clothing: Rinse immediately contaminated clothing and skin with plenty of water before removing clothes  
P310 - Immediately call a poison center or doctor  
P321 - Specific treatment (see supplemental first aid instruction on this label)  
P330 - Rinse mouth.  
P363 - Wash contaminated clothing before reuse.  
P370+P378 - In case of fire: Use media other than water to extinguish.  
P371+P380+P375 - In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.  
P390 - Absorb spillage to prevent material-damage.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P405 - Store locked up.  
P406 - Store in corrosive resistant container with a resistant inner liner.  
P501 - Dispose of contents/container to ...in accordance with local/regional/national regulations

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
hydrogen peroxide	(CAS-No.) 7722-84-1	26.5-27.3	Ox. Liq. 1, H271 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1A, H314
acetic acid	(CAS-No.) 64-19-7	3-8	Flam. Liq. 3, H226 Skin Corr. 1A, H314
peracetic acid	(CAS-No.) 79-21-0	5.5-5.9	Acute Tox. 4 (Oral), H302

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician.
First-aid measures after skin contact	: IF ON CLOTHING: Rinse immediately contaminated clothing and skin with plenty of water before removing clothes. Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a poison center or doctor/physician. Call a physician immediately.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or doctor/physician if you feel unwell. Immediately call a poison center or doctor/physician. Do not induce vomiting. Call a physician immediately.

### 4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met. Harmful if swallowed.
Symptoms/effects	: Causes severe skin burns and eye damage.
Symptoms/effects after skin contact	: Burns.
Symptoms/effects after eye contact	: Causes serious eye damage. Serious damage to eyes.
Symptoms/effects after ingestion	: Swallowing a small quantity of this material will result in serious health hazard. Burns.

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

# Water Guard WG 4500

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Specific hazards arising from the chemical

- Fire hazard : Combustible liquid. May cause fire or explosion; strong oxidizer.
- Explosion hazard : May form flammable/explosive vapor-air mixture. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
- Hazardous decomposition products in case of fire : Toxic fumes may be released.

#### 5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.

##### 6.1.1. For non-emergency personnel

- Emergency procedures : Ventilate spillage area. Evacuate unnecessary personnel. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray.

##### 6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".
- Emergency procedures : Ventilate area.

#### 6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. Absorb spillage to prevent material-damage. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapors are flammable. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Hazardous waste due to potential risk of explosion. May be corrosive to metals.
- Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Take any precaution to avoid mixing with combustibles. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact during pregnancy/while nursing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid contact with skin and eyes.
- Hygiene measures : Do not eat, drink or smoke when using this product. Wash hands, forearms and face thoroughly after handling. Always wash hands after handling the product. Wash contaminated clothing before reuse.

# Water Guard WG 4500

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Proper grounding procedures to avoid static electricity should be followed. Comply with applicable regulations.
Storage conditions	: Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use. Keep in fireproof place. Store in a well-ventilated place. Keep cool. Store in corrosive resistant container with a resistant inner liner. Keep only in original container. Store locked up.
Incompatible products	: Strong bases. Strong acids.
Incompatible materials	: Sources of ignition. Direct sunlight. Heat sources. Combustible materials. Metals.
Packaging materials	: Store in corrosive resistant container with a resistant inner liner.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Water Guard WG 4500	
No additional information available	
hydrogen peroxide (7722-84-1)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH TWA (ppm)	1 ppm
ACGIH STEL (ppm)	1 ppm
acetic acid (64-19-7)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH TWA (ppm)	10 ppm
ACGIH STEL (ppm)	10 ppm
peracetic acid (79-21-0)	
No additional information available	

### 8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Avoid all unnecessary exposure.

#### Hand protection:

Wear protective gloves.

#### Eye protection:

Chemical goggles or face shield. Safety glasses

#### Skin and body protection:

Wear suitable protective clothing.

#### Respiratory protection:

Wear appropriate mask

#### Personal protective equipment symbol(s):



#### Other information:

Do not eat, drink or smoke during use.

# Water Guard WG 4500

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Colourless
Odor	: Vinegar odour
Odor threshold	: No data available
pH	: < 1
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 200°F (93.3 °C)
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Combustible liquid.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: 1.12 g/ml
Solubility	: Complete.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: 270 °C
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: May cause fire or explosion; strong oxidizer.

#### 9.2. Other information

No additional information available

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Thermal decomposition generates : Corrosive vapors. May cause fire or explosion; strong oxidizer.

#### 10.2. Chemical stability

Combustible liquid. May form flammable/explosive vapor-air mixture. May cause fire or explosion; strong oxidizer.

#### 10.3. Possibility of hazardous reactions

May react with incompatible materials.

#### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks. Avoid contact with hot surfaces. No flames, no sparks. Eliminate all sources of ignition.

#### 10.5. Incompatible materials

bases. Combustible materials. metals. reducing agents.

#### 10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases. Thermal decomposition generates : Corrosive vapors.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Harmful if swallowed.
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

ATE US (oral)	500 mg/kg body weight
---------------	-----------------------

# Water Guard WG 4500

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

hydrogen peroxide (7722-84-1)	
LD50 oral rat	1518 mg/kg (Rat)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit)

peracetic acid (79-21-0)	
LD50 oral rat	1540 mg/kg (Rat)

Skin corrosion/irritation	: Causes severe skin burns. pH: < 1
Serious eye damage/irritation	: Causes serious eye damage. pH: < 1
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

hydrogen peroxide (7722-84-1)	
IARC group	3 - Not classifiable

Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Not classified
Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met. Harmful if swallowed.
Symptoms/effects	: Causes severe skin burns and eye damage.
Symptoms/effects after skin contact	: Burns.
Symptoms/effects after eye contact	: Causes serious eye damage. Serious damage to eyes.
Symptoms/effects after ingestion	: Swallowing a small quantity of this material will result in serious health hazard. Burns.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment. Before neutralisation, the product may represent a danger to aquatic organisms.
-------------------	--

acetic acid (64-19-7)	
LC50 fish 1	88 mg/l (96 h; Pimephales promelas; Pure substance)
EC50 Daphnia 1	6000 mg/l (24 h; Daphnia magna; Pure substance)
EC50 other aquatic organisms 1	> 5000 mg/l (5 h; Activated sludge; Pure substance)
LC50 fish 2	75 mg/l (96 h; Lepomis macrochirus; Pure substance)
EC50 Daphnia 2	32 mg/l (48 h; Artemia salina; Pure substance)
TLM fish 1	47 mg/l (96 h; Lepomis macrochirus; Pure substance)
TLM fish 2	100 ppm (96 h; Carassius auratus; Pure substance)
Threshold limit other aquatic organisms 1	12 - 1350, Protozoa; Pure substance
Threshold limit algae 1	4000 mg/l (Scenedesmus quadricauda; Pure substance)
Threshold limit algae 2	90 mg/l (Microcystis aeruginosa; Pure substance)

### 12.2. Persistence and degradability

Water Guard WG 4500	
Persistence and degradability	Not established.
hydrogen peroxide (7722-84-1)	
Persistence and degradability	Biodegradability: not applicable. No (test) data on mobility of the components available. Photolysis in the air.

# Water Guard WG 4500

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### hydrogen peroxide (7722-84-1)

Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

### acetic acid (64-19-7)

Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. No (test) data on mobility of the components available. Not established.
Biochemical oxygen demand (BOD)	0.6 – 0.74 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.03 g O <sub>2</sub> /g substance
ThOD	1.07 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.56 – 0.69 % ThOD

## 12.3. Bioaccumulative potential

### Water Guard WG 4500

Bioaccumulative potential	Not established.
---------------------------	------------------

### hydrogen peroxide (7722-84-1)

Partition coefficient n-octanol/water (Log Pow)	-1.36
Bioaccumulative potential	Bioaccumulation: not applicable.

### acetic acid (64-19-7)

Partition coefficient n-octanol/water (Log Pow)	-0.31 – -0.17
Bioaccumulative potential	Bioaccumulation: not applicable. Not established.

## 12.4. Mobility in soil

### acetic acid (64-19-7)

Ecology - soil	May be harmful to plant growth, blooming and fruit formation.
----------------	---

## 12.5. Other adverse effects

Other information : Avoid unintentional release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
Additional information	: Handle empty containers with care because residual vapors are flammable. Hazardous waste due to potential risk of explosion.
Ecology - waste materials	: Avoid unintentional release to the environment.

## SECTION 14: Transport information

### Department of Transportation (DOT)

In accordance with DOT

Transport document description	: UN3098 Oxidizing Liquid, corrosive, n.o.s. (contains hydrogen peroxide and peroxyacetic acid mixture, stabilized), 5.1(8), II
UN-No.(DOT)	: UN3098
Proper Shipping Name (DOT)	: <b>Oxidizing liquid, corrosive, n.o.s.</b>
Class (DOT)	: 5.1 - Class 5.1 - Oxidizer 49 CFR 173.128
Packing group (DOT)	: II - Medium Danger

# Water Guard WG 4500

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Hazard labels (DOT)

: 5.1 - Oxidizer  
8 - Corrosive



DOT Packaging Non Bulk (49 CFR 173.xxx)

: 202

DOT Packaging Bulk (49 CFR 173.xxx)

: 243

DOT Special Provisions (49 CFR 172.102)

: 145 - This entry applies to formulations that neither detonate in the cavitated state nor deflagrate in laboratory testing, show no effect when heated under confinement, exhibit no explosive power, and are thermally stable (self-accelerating decomposition temperature (SADT) at 60 C (140 F) or higher for a 50 kg (110.2 lbs.) package). Formulations not meeting these criteria must be transported under the provisions applicable to the appropriate entry in the Organic Peroxide Table in 173.225 of this subchapter.  
A2 - Single packaging are not permitted on aircraft.  
A3 - For combination packaging, if glass inner packaging (including ampoules) are used, they must be packed with absorbent material in tightly closed metal receptacles before packing in outer packaging.  
A6 - For combination packaging, if plastic inner packaging are used, they must be packed in tightly closed metal receptacles before packing in outer packaging.  
B53 - Packaging must be made of either aluminum or steel.  
IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.  
T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)  
TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.  
TP6 - The tank must be equipped with a pressure release device which prevent a tank from bursting under fire engulfment conditions (the conditions prescribed in CGA pamphlet S1.2 (see 171.7 of this subchapter) or alternative conditions approved by the Associate Administrator may be used to consider the fire engulfment condition), taking into account the properties of the hazardous material to be transported.  
TP24 - The portable tank may be fitted with a device to prevent the build up of excess pressure due to the slow decomposition of the hazardous material being transported. The device must be in the vapor space when the tank is filled under maximum filling conditions. This device must also prevent an unacceptable amount of leakage of liquid in the case of overturning.

DOT Packaging Exceptions (49 CFR 173.xxx)

: None

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)

: 1 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)

: 5 L

DOT Vessel Stowage Location

: D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger vessels in which the limiting number of passengers is exceeded.

Transport/Additional information

: 25 - Protected from sources of heat, 66 - Stow "separated from" flammable solids, 75 - Stow "separated from" permanganates

Other information

: No supplementary information available.

### Transportation of Dangerous Goods

#### Transport by sea

Transport document description (IMDG)

: UN3098 Oxidizing Liquid, corrosive, n.o.s. (contains hydrogen peroxide and peroxyacetic acid mixture, stabilized), 5.1(8), II

UN-No. (IMDG)

: 3098

Proper Shipping Name (IMDG)

: **Oxidizing liquid, corrosive, n.o.s.**

Class (IMDG)

: 5.1 - Oxidizing substances

# Water Guard WG 4500

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Packing group (IMDG)	: II - substances presenting medium danger
Subsidiary risks (IMDG)	: 8 - Corrosive substances
Limited quantities (IMDG)	: 1 L

**Air transport**

Transport document description (IATA)	: UN3098 Oxidizing Liquid, corrosive, n.o.s. (contains hydrogen peroxide and peroxyacetic acid mixture, stabilized), 5.1(8), II
UN-No. (IATA)	: 3098
Proper Shipping Name (IATA)	: <b>Oxidizing liquid, corrosive, n.o.s.</b>
Class (IATA)	: 5.1 - Oxidizing Substances
Packing group (IATA)	: II - Medium Danger
Subsidiary hazards (IATA)	: 8 - Corrosive substances

# Water Guard WG 4500

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

# Water Guard WG 4500

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Water G
---------

# Water Guard WG 4500

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

EPA Labeling Requirements	<p>This chemical is a pesticide product registered by the United States Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS), and for workplace labels of non-pesticide chemicals. The hazard information required on the pesticide label is reproduced below. The pesticide label also includes other important information, including directions for use.</p> <p><b>KEEP OUT OF REACH OF CHILDREN</b></p> <p><b>DANGER</b></p> <p><b>DANGER CORROSIVE:</b> Do not enter an enclosed area without proper respiratory protection. Causes irreversible eye damage and skin burns. May be fatal if inhaled or absorbed through skin. Harmful if swallowed. Do not breathe vapors or spray mist. Do not get in eyes, on skin, or on clothing. Wear goggles and face shield and rubber gloves when handling. Wash thoroughly with soap and water after handling and before eating, drinking or using tobacco. Remove contaminated clothing and wash before reuse.</p> <p><b>PHYSICAL OR CHEMICAL HAZARDS</b></p> <p><b>STRONG OXIDIZING AGENT. CORROSIVE.</b> Mix only with potable water below 140°F. Product must be diluted in accordance with label directions prior to use. Water Guard WG 4500 is not combustible; however, at temperatures exceeding 156°F, decomposition occurs releasing oxygen. The oxygen released could initiate combustion.</p> <p><b>ENVIRONMENTAL HAZARDS</b></p> <p>This pesticide is toxic to birds, fish and aquatic invertebrates. Caution should be used when applying indoors because pets may be at risk. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of the National Pollution Discharge System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product into sewer systems without previously notifying the local sewage plant authority</p> <p><b>STORAGE AND DISPOSAL</b></p> <p><b>Storage:</b> Never return Water Guard WG 4500 to the original container after it has been removed. Avoid all contaminants, especially dirt, caustic, reducing agents, and metals. Contamination and impurities will reduce shelf life and can induce decomposition. In case of a decomposition, isolate container, douse container with cool water and dilute Water Guard WG 4500 with large volumes of water. Avoid damage to containers. Keep container closed at all times when not in use. Keep container out of direct sunlight. To maintain product quality, store at temperatures below 86°F.</p> <p><b>Procedure for Leak or Spill:</b> Stop leak if this can be done without risk. Shut off ignition sources: no flames, smoking, flares, or spark producing tools. Keep combustible and organic materials away. Flush spilled material with large quantities of water. Undiluted material should not enter confined spaces.</p> <p><b>Pesticide Disposal:</b> Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or Hazardous Waste representative at the nearest EPA Regional Office for guidance. If material has been spilled, an acceptable method of disposal is to dilute with at least 20 volumes of water followed by discharge into suitable treatment system in accordance with all local, state and Federal environmental laws, rules, regulations, standards, and other requirements. Because acceptable methods of disposal may vary by location, regulatory agencies should be contacted prior to disposal. Water Guard WG 4500, which is to be discarded, should be disposed of as hazardous waste after contacting the appropriate local, state or Federal agency to determine proper procedures.</p> <p><b>Container Disposal:</b> Nonrefillable container. Do not reuse or refill this container. Clean container promptly after emptying. Offer for recycling if available. Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank. Fill the container 1/4 full with water. Replace and tighten closures. Tip container on its side and roll it back and forth, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip it back and forth several times. Empty the rinsate into application equipment or a mix tank or</p>
---------------------------	---

# Water Guard WG 4500

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Water G	
	store rinsate for later use or disposal. Repeat this procedure two more times.

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

peracetic acid	CAS-No. 79-21-0	5.5-5.9%
----------------	-----------------	----------

acetic acid (64-19-7)	
CERCLA RQ	5000 lb

peracetic acid (79-21-0)	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	500 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	500 lb

### 15.2. International regulations

#### CANADA

hydrogen peroxide (7722-84-1)	
Listed on the Canadian DSL (Domestic Substances List)	
acetic acid (64-19-7)	
Listed on the Canadian DSL (Domestic Substances List)	
peracetic acid (79-21-0)	
Listed on the Canadian DSL (Domestic Substances List)	

#### EU-Regulations

No additional information available

#### National regulations

No additional information available

### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Component	State or local regulations
hydrogen peroxide(7722-84-1)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
acetic acid(64-19-7)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
peracetic acid (79-21-0)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

## SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 05/11/2023  
Other information : None.

# Water Guard WG 4500

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

H226	Flammable liquid and vapour
H227	Combustible liquid
H271	May cause fire or explosion; strong oxidizer
H290	May be corrosive to metals
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H332	Harmful if inhaled

SDS US (GHS HazCom 2012)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*