

66" x 42" Heated BubbleMassage™ air bath with Bask™ K-1170-GHW

Features

- 122 airjets release thousands of heated bubbles that surround, support, and massage the body.
- Variable-speed blower lets you adjust massage intensity to 18 levels.
- Bask[®] heated surface creates spa-like relaxation with soothing warmth on your back, shoulders, and neck.
- Built-in heater.
- Automatic and manual purge cycles remove residual water from air channels after use.
- 60-minute automatic shutoff timer.
- Generous 66" length provides spacious bathing for up to two people.
- Integral lumbar support.
- Keypad control.
- Textured bottom surface.
- Coordinates with other products in the Memoirs collection.
- Bask[®] heated surface creates spa-like relaxation with soothing warmth on your back, shoulders, and neck.

Material

Acrylic.

Technology

 Heated BubbleMassage[™] technology warms and humidifies air before it enters the bath.

Installation

- Drop-in.
- Center rear drain.

Required Products/Accessories

K-11677 Bath Drain

Recommended Products/Accessories

K-1446 Remote Installation Kit K-7161-AF 1-1/2" adjustable pop-up drain above- or through-floor K-24916 Wireless Music Kit K-37380 30" Rough-in Cable Bath Drain K-37383 Rough-in cable bath drain, PVC, 30" cable with tubing K-1491 Bath/Whirlpool Pillow K-1601 Bath/Whirlpool Footstop K-7213 27" Cable Bath Drain K-7214 27" Cable Bath Drain K-7259 Brass toe tap bath drain K-9497 2-1/2" Keypad Trim K-1177 Vinyl Tiling-in Bead

Included Components

Additional Components: 40" (1016 mm) cable



Memoirs[®]

Codes/Standards

ASME A112.19.7/CSA B45.10 CSA B45.5/IAPMO Z124 ASTM E162 ASTM E662 UL 1795 CSA C22.2 No. 218.2

KOHLER® Hydrotherapy Components Five-Year Limited Warranty KOHLER® Plastic Baths and Receptors Lifetime Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color Code Description

0	White
96	Biscuit
NY	Dune





Memoirs®

66" x 42" Heated BubbleMassage[™] air bath with Bask[™] K-1170-GHW



Required Electrical Service

Two dedicated circuits required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI). Outside North America, this device may be known as a Residual Current Device (RCD).

Blower, Heated	120 V, 15 A, 60 Hz
Surface:	
Air bath:	120 V, 15 A, 60 Hz

Technical Information

All product dimensions are nominal.

Installation:	Drop-in
Basin area, bottom:	42" x 27" (1067 mm x 686 mm)
Basin area, top:	54" x 30" (1372 mm x 762 mm)
Weight:	156 lbs (70.8 kg)
Minimum floor load:	44 lbs/ft² (214.8 kg/m²)
Water depth:	16" (406 mm)
Water capacity:	81 gal (306.6 L)
Electrical component	Blower: 120 V, 10 A, 60 Hz
rating:	Heated Surface: 120 V, 0.5 A, 60 Hz
	Air bath: 120 V, 5 A, 60 Hz

Notes

Measure your actual product for rough-in details. Install this product according to the installation instructions.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

