



NOTES:

THIS UNIT IS IAPMO LISTED

FEATURES:

- NON-SKID TEXTURED BOTTOM SURFACE.
- INTEGRAL HYDROBERM FEATURE FORMS AN EFFECTIVE SPLASH GUARD ALONG THE TOP EDGE OF THE TUB/SHOWER ENCLOSURE.
- GREEN FRIENDLY TUBS AND SHOWERS: UTILIZING ADVANCED CHEMISTRY THAT YIELDS, HIGHER QUALITY, GREATER STRENGTH AND LOWER EMISSIONS.

TECHNICAL SPECS:

- GEL COAT THICKNESS .020" ± .005"
- 1ST LAMINATE .125" NOMINAL THICKNESS
- BOTTOM OF UNIT IS REINFORCED WITH WOOD TO MEET 300# LOAD TEST.
- 2ND LAMINATE COMPLETELY COVERS ALL AREAS.
- SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.



UNIT PART NUMBERS		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE AS FOLLOWS				Fiber Care Baths, Inc.			9832 Yucca Rd. Adelanto, CA 92301 Phone: 760-246-0019 Fax: 760-246-5189								
RIGHT HAND UNIT	AT60-30WS-15 R	DECIMAL: .XX =+.010 .XXX =+.005	FRACTIONAL: ±1/4"		ANGULAR: ±1/2°	TITLE: ACRYLIC TUB, WITH SKIRT											
LEFT HAND UNIT			AT60-30WS-15 L														
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF FIBER CARE BATHS, INC. ANY REPRODUCTION OR UNAUTHORIZED USE IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF FIBER CARE BATHS, INC. IS STRICTLY PROHIBITED. PRODUCT CONFIGURATION, DIMENSIONS, STANDARD ACCESSORIES, MATERIALS COMPOSITION AND CONSTRUCTION ARE SUBJECT TO CHANGE WITHOUT NOTICE.		CAPACITY / OPERATING LEVEL:			GAL	DRAWN: ANDREW						SIZE: A		MODEL #: AT60-30WS-15		REV A	
		CAPACITY / OVERFLOW LEVEL:			GAL												
		APPROX. UNIT WEIGHT:		LBS													
		APPROX. SHIPPING WEIGHT:		LBS								DATE: 3/30/2015		SCALE: NTS		STATUS: IAPMO LISTED	