


# Fig. 29 TOLCO double offset hanger & restrainer for CPVC plastic pipe

**Function:** Intended to perform as a hanger and restrainer for CPVC plastic fire sprinkler pipe. Provides double offset 1½" (38.1mm) x 1½" (38.1mm) from mounting surface. This design will ease installation by eliminating the need for wood block extension and allow retrofit attachment of hanger to sprinkler pipe.

**To install:** Install using a rechargeable electric drill fitted with a 5/16" (8mm) socket attachment with the special #10 x 1" hex head self-threading screws provided. Install screws until they bottom out. Pipe can be "snapped" into hanger before or after installation of the screws to the mounting surface. Can be used as a single offset hanger by aligning "dimples" with top of mounting surface and utilizing two fasteners in any two of the three holes provided.

**Note:** "Thumb tab" may be bent up to provide additional protection to the pipe but is not required for performance of the hanger / restrainer function.



Meets and exceeds requirements of NFPA 13, 13R and 13D.

US Patent No. 9,726,304  
Can. Pat. No. 2618941



## Maximum hanger spacing required per NFPA 13 for CPVC plastic pipe

Pipe size	Hanger spacing
¾"	5' 6"
1"	6' 0"
1¼"	6' 6"
1½"	7' 0"
2"	8' 0"

**EATON**  
Powering Business Worldwide

**Eaton**  
1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
Eaton.com

13201 Dahlia Street, Suite 200  
Fontana, CA 92337  
United States  
Phone: 800-851-7415

© 2021 Eaton  
All Rights Reserved  
Printed in USA  
Publication No. IL309021EN SEIS-3  
March 2021 B-Line Division

Eaton.com/tolco  
Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

