

L25 - 4 Hole Gusset Corner Angle

Available Finishes / Materials:

EG -- Electro-galvanized


HD -- Hot dipped galvanized

S4 -- 304 stainless steel

S6 -- 316 stainless steel

YC -- Yellow chromate

Standard Finish: EG



Catalog Number: L25 0000EG Weight: 0.75 Lbs.

Material is 15/8" [41.3] wide x 1/4" [6.3] thick unless specified. Holes are 3/4" (14.3) diameter, 13/4" [20.6] center to edge on 17/4" [47.6] centers unless specified.

Material Specifications and Finishes

Carbon Steel - ASTM A1011-00 SS GR 33 or ASTM A1011-00CS Type B

- EG Electro-Galvanized. Electroplating deposits zinc on the surface of the steel by electrolysis from a bath of zinc salts. Recommended for relatively dry indoor use. This is the standard coating for most Jet Stream products. Thickness of applied zinc is between 0.2 mils to 0.5 mils [5.1 μm to 12.7 μm]. Coatings on Jet Stream EG products meet ASTM B633 SC1 Type III.
- HD Hot Dip Galvanized After Fabrication. Fabricated product is dipped in molten zinc and is completely covered on all surfaces. Recommended for outdoor use. Coatings on Jet Stream HD products meet ASTM A123/153. The zinc coating is typically 2.6 mils [66.0 μm] or 1.5 oz. per square foot [0.46 kg per square meter] per side.
- S4 304 Stainless Steel ASTM A240 (Type 304)
- S6 316 Stainless Steel ASTM A240 (Type 316), 316 Stainless Steel Nuts – ASTM A276-03
- YC Yellow Zinc Dichromate. A 0.5 mil [12.7 μm] electro-galvanized zinc plating meeting ASTM B633 SC1 Type III is applied to the surface of the metal. Yellow Dichromate is applied over the zinc. This results in a yellowish gold appearance and acts as a nonporous barrier sealant that is corrosion resistant and can be painted.

Note: Specifications subject to change without notice.

Project:	Date:	Phone:
Submited By:	Address:	
Comment		