
Bronze Ball Valve For Potable Water Two Piece Full Port 200 psig @ 250°F† Press x Press Ends Blow-Out Proof Stem

**Dimensions and Workmanship Conform to MSS SP-110** 

## MATERIAL LIST

IVIA	MATERIAL LIST									
ITEM	PART	MATERIAL	ASTM SPEC							
1	Body	Cast Bronze	B584							
			C89833							
2	Tailpiece	Cast Bronze	B584							
			C89833							
3	Ball	Brass w/Hard Chrome	B283							
		Plating	C27450							
		316 Stainless Steel (1)	A276							
			S31600							
4	Seat	RPTFE, 15% Glass Filled	Commercial							
5	Stem	Brass	B21							
			C46400							
		316 Stainless Steel (1)	A276							
			S31600							
6	Thrust Washer	RPTFE, 25% Glass Filled	Commercial							
7	Packing	PTFE	Commercial							
8	Packing Nut	Brass	B16							
			C36000							
9	Handle	Steel w/Zinc Plating	Commercial							
10	Handle Grip	Vinyl	Commercial							
11	Handle Nut	Steel w/Zinc Plating	Commercial							
12	Press Adapters	Brass Fitting w/EPDM	B283							
		O-Ring	C27450							

<sup>(1)</sup> Ball and stem are stainless for UPBA400S



## **DIMENSIONS**

	UNITS	1/2" DN15	3/4" DN20	1" DN25	1-1/4" DN32	1-1/2" DN40	2" DN50
A (DIA)	INCHES	0.50	0.76	1.06	1.31	1.56	2.00
A (DIA)	mm	13	19	27	33	40	51
STD INSERTION	INCHES	0.87	0.98	0.98	1.02	1.42	1.58
DEPTH	mm	22	25	25	26	36	40
В	INCHES	2.19	2.59	3.32	3.77	4.28	5.10
	mm	54	66	84	96	109	130
B <sup>1</sup>	INCHES	5.19	6.17	7.32	7.84	8.76	11.10
В.	mm	132	157	186	199	228	282
С	INCHES	1.10	1.30	1.59	1.81	2.06	2.37
	mm	27	33	40	46	52	60
D	INCHES	1.91	2.32	2.68	2.82	3.00	3.36
	mm	47	59	68	72	76	85
Е	INCHES	3.82	4.55	6.33	6.33	6.33	7.19
	mm	94	116	161	161	161	183
F	THREAD SIZE	1/2" NPT	3/4" NPT	1"NPT	1-1/4" NPT	1-1/2" NPT	2" NPT
Cv		13	30	61	110	185	360


Note: DN (Diameter Nominal) = Metric equivalent size.

†Non-Shock



**Note:** Lead free refers to the wetted surface of the pipe, fittings and fixtures in potable water systems that have a weighted average lead content ≤0.25%. Source: California Health and Safety Code (116875).

The information presented on this sheet is correct at the time of publication. Milwaukee Valve reserves the right to change design, and/or material specifications without notice. For the Installation, Operation and Maintenance Manual (IOM) see the Technical/Service Information section on our website. For the most current information access www.milwaukeevalve.com



Press End Adapter.

Available with Press x Threaded Ends (Order UPBA400P1/ UPBA400SP1)