



## MULTI ATTACHMENT, 13/16" HOLE 1, 9/16" HOLE 2

### **CATALOG NUMBER**

**CSBMA050075EG**



### **CERTIFICATIONS**



### **FEATURES**

Disperses load over two anchors

Minimizes the number of installed braces needed for concrete and wood structures

Ideal for deck installations

Use for both lateral and longitudinal sway brace applications

Meets NFPA®-13 requirements for seismic sway bracing

Meets CEN/TS 17551:2021 requirements for Seismic Sway Bracing

### **PRODUCT ATTRIBUTES**

Material: Steel

Finish: Electrogalvanized

Hole Size 1: 13/16"

Hole Size 2: 9/16"

A: 12"

B: 2 1/2"

C: 2 1/2"

D: 9"

UL Listed Load: 3,740 lb

## ADDITIONAL PRODUCT DETAILS



Mount to structure using holes indicated in HS1.

Structure Attachment and Brace Member are not included.

<b>FM Loads</b>				
<b>Part Number</b>	<b>Horizontal Capacity per Installation Angle from Vertical</b>			
	<b>30° - 44°</b>	<b>45° - 59°</b>	<b>60° - 74°</b>	<b>75° - 90°</b>
CSBMA050050EG	3,290 lb	4,520 lb	5,540 lb	6,200 lb
CSBMA050075EG	3,290 lb	4,520 lb	5,540 lb	6,200 lb

<b>UL Loads</b>				
<b>Part Number</b>	<b>Structure Attachment Fitting</b>	<b>Brace Member</b>	<b>Load Rating</b>	
CSBMA050050	CSBU1	1" - 2" Sch. 40 NPS	680 lb	
	CSBUNIV050	1" - 2" Sch. 40 NPS	680 lb	
	CSBURC12	CSB12CBL	418 lb	
		CSB18CBL	772 lb	
		CSB36CBL	1100 lb	
	CSBURC12	CSB12CBL	418 lb	
		CSB18CBL	772 lb	
		CSB36CBL	1300 lb	
	CSBMA050075	CSBU1	680 lb	
		1" - 2" Sch. 40 NPS	680 lb	
		CSB12CBL	418 lb	
		CSB18CBL	772 lb	
		CSB36CBL	1100 lb	
		CSB12CBL	418 lb	
		CSB18CBL	772 lb	
		CSB36CBL	1300 lb	

## DIAGRAMS



## **WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

### **North America**

+1.800.753.9221  
Option 1 – Customer Care  
Option 2 – Technical Support

### **Europe**

Netherlands: +31 800-0200135  
France: +33 800 901 793

### **Europe**

Germany: 800 1890272  
Other Countries: +31 13 5835404

### **APAC**

Shanghai: + 86 21 2412 1618/19  
Sydney: +61 2 9751 8500



Our powerful portfolio of brands:  
**nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF**  
**TRACER**