

6.34



PIPE PLUGS AND BUSHING

Rev. 8-13 Shaded area indicates changes



Brass plug - Machine inserted*
AWWA taper
(MUELLER "CC") thread

H-10034N

1/2"‡	5/8"	3/4"	1"	1-1/4"‡	1-1/2"	2"
-------	------	------	----	---------	--------	----



Brass plug** - Square head with
AWWA taper
(MUELLER "CC") thread

H-10033N

1/2"	5/8"	3/4"	1"	1-1/4"	1-1/2"	2"
------	------	------	----	--------	--------	----



Brass plug - Machine inserted*
I.P. thread

H-10037N

3/4"‡	1"‡	1-1/4"‡	1-1/2"‡	2"‡	2-1/2"‡
-------	-----	---------	---------	-----	---------



Brass plug- Square head with
I.P. thread

H-10035N

1/2"‡	3/4"	1"	1-1/4"‡	1-1/2"‡	2"‡
-------	------	----	---------	---------	-----



Brass bushing
Male AWWA taper
(MUELLER "CC") thread x
female AWWA taper
(MUELLER "CC") thread

H-10036N

1"x3/4"	1-1/2"x1"	2"x3/4"	2"x1"	2"x1-1/2"
---------	-----------	---------	-------	-----------



Brass Bushings

- 47162** 1-1/4" MIP x 1" FIP
- 47163** 2" MIP x 3/4" FIP
- 47164** 2" MIP x 1" FIP
- 47165** 1" MIP x 3/4" FIP
- 47168** 1-1/2" MIP x 3/4" FIP
- 47169** 1-1/2" MIP x 1" FIP
- 47172** 2" MIP x 1-1/2" FIP

*Nominal size.

‡Requires minimum ordering quantity. Contact MUELLER Customer Service Center for minimum ordering requirements and availability.

MUELLER Pipe Plugs and Bushings are manufactured and tested in accordance with ANSI/AWWA C800. Components in contact with potable water will also comply with latest requirements of the Federal Safe Drinking Water Act.