

Location: \_\_\_\_\_



**FS1730-FL**

**12" X 12" X 8" FLOOR AREA & INDIRECT  
SANITARY WASTE DRAIN WITH FLANGE**

**Specification:** MIFAB Series FS1730-FL, 12" x 12" x 8" deep cast iron floor area and indirect sanitary waste drain complete with white acid resistant porcelain enamel coated interior, light duty loose set grate and anchor flange with weepholes. Anti-splash aluminum dome strainer included.

**Function:** Used in kitchens, restaurants, grocery stores, hospitals, schools, and other areas that require a large volume sanitary drain. Also suitable for indirect waste applications. The anchor flange is engineered to receive water proofing membrane. Membrane clamps are recommended for use with the anchor flange (Suffix -C).

**A.R.E. LOOSE SET GRATE**

**MEMBRANE CLAMPS (4)**  
2 x (FS1700-PCS)  
2 x (FS1700-PCL)

**9.31"**

**12"**

**ANCHOR FLANGE**  
(14 1/2" x 14 1/2")

**WEEP HOLE**

**HARDWARE**  
(8) x (H-10)

**2"**

**8"**

**2", 3", 4"  
OUTLET**

**BODY HEIGHT**  
SEE BODY HEIGHT  
CHART 1

**POLY  
DOME STRAINER**  
(FS1500-PD)  
(INCLUDED)

**WHITE ACID RESISTANT  
PORCELAIN ENAMEL (A.R.E.) COATING  
ON INSIDE OF CAST IRON BODY**

**\*ADD 3/4" TO DIMENSION AND 1/2" TO HEIGHT FOR NB, SS FRAME & GRATE**

**FS1730-FL PARTS**

**Note:** Specify outlet size and connection type.  
Dome strainer included with body.

(\*) Specify 150 for 1/2 grate, 175 for 3/4 grate or nothing for full grate  
**Note:** For Nickel Bronze or Stainless Steel grate and frame, specify -TA instead of -PG and specify -1 for Nickel Bronze and -3 for Stainless Steel

**FS1730T-FL (Transition Body) PARTS**

**Note:** Specify outlet size and connection type.  
Dome strainer included with body.

**FS1730-FL-PB** **FS1700-PG-(\*)** **A3-PG** **A1-11 Body**

**IAPMO** **SP** **ASME**

**B79.7-22** **A112.6.7-22**

PIPE SIZE	BODY HEIGHT				
	NO HUB (STANDARD)	PUSH ON (P)	INSIDE CAULK (X)	THREADED (T)	PVC (-30) / ABS (-31)
2" (51)	9 3/4" (248)	9 3/4" (248)	*12" (305)	*10 1/2" (267)	*11 1/4" (286)
3" (76)	9 3/4" (248)	9 3/4" (248)	10 5/8" (270)	*10 7/8" (276)	*11 1/4" (286)
4" (102)	9 3/4" (248)	9 3/4" (248)	10 5/8" (270)	*10 7/8" (276)	*11 1/4" (286)

\*Indicates outlet size and connection available with transition outlet body only. Outlet sizes indicated by the \* are available with the transition outlet body only

Suffix	Description	-150	Half grate
-1	Nickel bronze strainer	-175	3/4 grate
-3	Stainless steel strainer	-C	Membrane clamp (add to FS1730-FL only)
-5	Sediment bucket (FS1700-PB)	-P	Push on outlet
-6	Security screws (H-1039A, 4 pcs) (-1, -3 only)	-T	Threaded outlet
-7	Trap seal primer connection	X	Inside caulk outlet
-8	Backwater Valve (BV1250 Series) (2", 3", 4")		
-9	Hinged grate (-3 only)		
-21	Secondary flat strainer (FD-9600 Series)		
-22	Less Enamel Cast Iron grate (deduct)		
-22	Less Nickel Bronze grate (deduct)		
-22	Less Stainless Steel grate (deduct)		
-30	PVC socket connection W/A.R.E. Body (2", 3", 4")		
-31	ABS socket connection W/A.R.E. body (2", 3", 4")		
-32	Deep seal trap (2", 3", 4" no hub) (MI-950 Series)		
-51	2 1/2" round center grate opening (-1, -3 only)		
-69	Stainless Steel Sediment bucket (FS1700-PB-3)-3)		
-83	Stainless steel mesh screen over sediment bucket		

CALIFORNIA PROPOSITION 65 WARNING. This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Job Name: \_\_\_\_\_  
Section No: \_\_\_\_\_  
Schedule No: \_\_\_\_\_

Page No: \_\_\_\_\_  
Contractor: \_\_\_\_\_  
Purchase Order No: \_\_\_\_\_