

Inverter Driven Heat Pump

9,000 BTU Single Zone High SEER Wall Mounted System

Job Name _____
 Location _____
 Engineer _____
 Submitted To _____
 Submitted By _____
 Reference _____

Date _____
 Approval _____
 Construction _____
 Unit No _____
 Drawing No _____

PRODUCT FEATURES

Auto Changeover
 Weekly & 24 hr. Timer
 Auto Louver: 4 way
 Minimum Heat Mode
 Auto Restart
 Economy Mode
 Energy Saving Program (ESP)
 Wireless Remote control
 Outdoor Unit Low Noise Schedule



Heating down to -15°F outdoor temperatures



MODEL NUMBERS

Indoor Unit	ASUG09LZBS
Outdoor Unit	AOUG09LZAH1
System	09LZBH1

EFFICIENCIES

SEER	33.1
EER	18
HSPF	14
COP	5.33
	18.20

OUTDOOR TEMPERATURE OPERATION RANGE

Cooling	°F(°C)	14 to 115 (-10 to 46)
Heating		-15 to 75 (-26 to 24)

CAPACITIES

Cooling	Rated	9,000
	Min.-Max.	3,100-12,000
Heating	Rated	12,000
	Min.-Max.	3,100-22,000

LINESET REQUIREMENTS

Connection Method		Flare
Liquid	in (mm)	Ø1/4 (Ø6.35)
Gas		Ø3/8 (Ø9.52)
Pre-Charge Length	ft (m)	49 (15)
Minimum Length		16 (5)
Maximum Length		66 (20)
Max. Height Diff.		49 (15)

INDOOR DIMENSIONS & WEIGHT

Net (H x W x D)	in	11 x 38-9/16 x 9-7/16
	mm	280 x 980 x 240
Gross (H x W x D)	in	12- 11/16 x 42- 7/16 x 13- 10/16
	mm	322 x 1078 x 346
Net Weight	lb (kg)	29 (13)
Gross Weight		37 (17)

OUTDOOR DIMENSIONS & WEIGHT

Net (H x W x D)	in	24-7/8 x 31-7/16 x 11-7/16
	mm	632 x 799 x 290
Gross (H x W x D)	in	27- 4/16 x 37 x 14- 12/16
	mm	692 x 940 x 375
Net Weight	lb (kg)	86 (39)
Gross Weight		95 (43)



Indoor Unit ETL#: 91987
 Outdoor Unit ETL#: 91987

Effective Date: 7/13/2021

Fujitsu General America, Inc. • 340 Changebrige Rd, Pine Brookfield, NJ 07058 • Toll Free: (888) 888-3424 • www.fujitsugeneral.com

Warranty Information



7 Year Compressor, 5 Year Parts out-of-the-box Warranty



10 Year Compressor, 10 Year Parts Warranty when registered within 60 days of installation in a residence



12 Year Compressor, 12 Year Parts Warranty when registered within 60 days of installation in a residence, and installed by a Fujitsu Elite contractor

ACCESSORIES

UTY-TTRX	3rd Party Thermostat Converter
UTY-TWRXZ2	Interface Kit
UTY-RNRUZ5	Wired Remote Controller (Touch Panel)
UTY-RSRY	Simple Remote Control
UTY-RHRY	Simple Remote Control (Hospitality)
UTY-TFSXF1	WiFi Interface Module



This system combination is Energy Star qualified



+App available in Apple® App Store and Google® Play Store.

Due to continuous product improvements, specifications are subject to change without notice. Please log in to the Fujitsu Portal for the most up-to-date documentation <https://portal.fujitsugeneral.com>

Inverter Driven Heat Pump

9,000 BTU Single Zone High SEER Wall Mounted System

FAN DATA

Indoor Unit Airflow Rate	Cooling	High	CFM (m3/h)	542 (920)
		Medium		406 (690)
		Low		312 (530)
		Quiet		206 (350)
	Heating	High		542 (920)
		Medium		406 (690)
		Low		312 (530)
		Quiet		206 (350)
Outdoor Unit Airflow Rate	Cooling			1089 (1,850)
	Heating			1089 (1,850)

SOUND PRESSURE

Indoor Unit	Cooling	High	dB (A)	43
		Medium		37
		Low		31
		Quiet		23
	Heating	High		43
		Medium		36
		Low		31
		Quiet		23
Outdoor Unit	Cooling			46
	Heating			47

REFRIGERANT

Type			R410A
Charge	lb oz	2lb 14oz	
	kg	1	
Oil Type			POE (RB68)

ELECTRICAL SPECIFICATIONS


Voltage/Frequency/Phase				208/230 V / 1Ø / 60Hz
Voltage Range				187-253V~60HZ
Current	Cooling	Rated	A	2.5
	Heating	Rated		3.3
Maximum Operating Current		Cooling		9.4
		Heating		11.9
Starting Current				3.3
MCA				14.4
Maximum Circuit Breaker				15
Input Power	Cooling	Rated	kW	0.5
		Min.–Max.		0.11–0.85
	Heating	Rated		0.66
		Min.–Max.		0.17–1.93
Power Factor	Cooling		%	87
	Heating			87

OTHER

Moisture Removal		pints/h (L/h)		2.5 (1.2)
Energy Star				Yes
Drain hose	Material			PP+LLDPE
Size	in (mm)	Ø 17/32 (Ø 13.8) (I.D.) Ø 5/8 to Ø 21/32 (Ø 15.8 to Ø 16.7) (O.D.)		
Operation Range	Cooling	°F (°C)	64 to 90 (18 to 32)	
		%RH	80 or less	
	Heating	°F (°C)	60 to 86 (16 to 30)	

Wall Bracket Data:

Units: In. (mm)



The Fujitsu logo is a worldwide trademark of Fujitsu General Limited. The Halcyon logo and name is a worldwide trademark of Fujitsu General Limited and is a registered trademark in Japan, the USA and other countries or areas. Copyright 2018 Fujitsu General America, Inc. Fujitsu's products are subject to continuous improvements. Fujitsu reserves the right to modify product design, specifications and information in this brochure without notice and without incurring any obligations.


Note: Specifications are based on the following conditions:
Cooling: Indoor temperature of 80°F (26.7°C) DB/67°F (19.4°C) WB, and outdoor temperature of 95°F (35°C) DB/75°F (23.9°C) WB. Heating: Indoor temperature of 70°F (21.1°C) DB/60°F (15.6°C) WB, and outdoor temperature of 47°F (8.3°C) DB/43°F (6.1°C) WB. Pipe length: 25ft. (7.5m), Height difference: 0ft. (0m) (Outdoor unit – indoor unit).

Inverter Driven Heat Pump

9,000 BTU Single Zone High SEER Wall Mounted System

DIMENSIONS

Units: In. (mm)



The Fujitsu logo is a worldwide trademark of Fujitsu General Limited. The Halcyon logo and name is a worldwide trademark of Fujitsu General Limited and is a registered trademark in Japan, the USA and other countries or areas. Copyright 2018 Fujitsu General America, Inc. Fujitsu's products are subject to continuous improvements. Fujitsu reserves the right to modify product design, specifications and information in this brochure without notice and without incurring any obligations.

Note: Specifications are based on the following conditions:
Cooling: Indoor temperature of 80°F (26.7°C) DB/67°F (19.4°C) WB, and outdoor temperature of 95°F (35°C) DB/75°F (23.9°C) WB. Heating: Indoor temperature of 70°F (21.1°C) DB/60°F (15.6°C) WB, and outdoor temperature of 47°F (8.3°C) DB/43°F (6.1°C) WB. Pipe length: 25ft. (7.5m), Height difference: 0ft. (0m) (Outdoor unit – indoor unit).