

Inverter Driven Heat Pump

9,000 BTU Slim Duct Type

Job Name _____
Location _____
Engineer _____
Submitted To _____
Submitted By _____
Reference _____

Date _____
Approval _____
Construction _____
Unit No _____
Drawing No _____

PRODUCT FEATURES

Automatic Changeover
Auto/Cool/Dry/Fan/Heat Modes
24 Hr./Weekly timer
Built in Condensate Pump
Auxiliary Heat Control Logic
Auto Restart
Economy Mode



MODEL NUMBERS				
Indoor Unit			ADUH09LUAS1	
Nominal Capacity			9,000	
LINESET REQUIREMENTS				
Connection Method			Flare	
Liquid	in (mm)		Ø 1/4 (Ø 6.35)	
Gas			Ø 3/8 (Ø 9.52)	
Drain hose	Material	HARD PVC		
	in (mm)	Ø1 (Ø25) (I.D.), Ø1-1/4 (Ø32) (O.D.)		
INDOOR DIMENSIONS & WEIGHT				
Net (H × W × D)	in (mm)	7-13/16 × 27-9/16 × 24-7/16 (192 × 700 × 620)		
Gross (H × W × D)		10-13/16 × 37-3/16 × 30-3/8 (274 × 945 × 772)		
Net Weight	lb (kg)	37 (17)		
Gross Weight		49 (22)		
ELECTRICAL SPECIFICATIONS				
Voltage/Frequency/Phase			208/230 V ~ 60 Hz	
Available Voltage Range			187–253 V	
Running Current		A	0.3	
Input Power		W	49	
SOUND PRESSURE				
Indoor Unit	Cooling	HIGH	dB (A)	28
		MED		27
		LOW		26
		QUIET		25
	Heating	HIGH		28
		MED		26
		LOW		25
		QUIET		24
FAN DATA				
Indoor Unit Airflow rate	Cooling	HIGH	CFM (m3/h)	353 (600)
		MED		324 (550)
		LOW		294 (500)
		QUIET		265 (450)
	Heating	HIGH		353 (600)
		MED		324 (550)
		LOW		294 (500)
		QUIET		265 (450)

Warranty Information



7 Year Compressor, 5 Year Parts out-of-the-box Warranty



10 Year Compressor, 10 Year Parts Warranty when registered within 60 days of installation in a residence



12 Year Compressor, 12 Year Parts Warranty when registered within 60 days of installation in a residence, and installed by a Fujitsu Elite contractor

ACCESSORIES

UTY-RNRUZ-Series	Wired Remote Controller
UTY-RSRY	Simple Remote Controller
UTY-RHRY	Simple Remote Controller
UTY-LBTUM	IR Kit (Remote & IR Receiver Unit)
UTY-TFSXZ2	WLAN Adapter
UTY-VMSX	Modbus Converter
UTD-GXTA-W	Auto Louver Grille Kit
UTY-TTRXZ1	Thermostat Converter
UTY-XWZXZG	External Connect Kit

Due to continuous product improvements, specifications are subject to change without notice. Please log in to the Fujitsu Portal for the most up-to-date documentation
<https://connect.fujitsugeneral.com>


Effective Date: 1/12/2023

Fujitsu General America, Inc. • 340 Changebridge Rd, Pine Brook, NJ 07058 • Toll Free: (888) 888-3424 • www.fujitsugeneral.com

DIMENSIONS:

Indoor Unit:

Units: In. (mm)



The Fujitsu logo is a worldwide trademark of Fujitsu General Limited. The Airstage logo and name is a worldwide trademark of Fujitsu General Limited and is a registered trademark in Japan, the USA and other countries or areas. Copyright 2022 Fujitsu General America, Inc. Fujitsu's products are subject to continuous improvements. Fujitsu reserves the right to modify product design, specifications and information in this brochure without notice and without incurring any obligations.

Note: Specifications are based on the following conditions:
Cooling: Indoor temperature of 80°F (26.7°C) DB/67°F (19.4°C) WB, and outdoor temperature of 95°F (35°C) DB/75°F (23.9°C) WB. Heating: Indoor temperature of 70°F (21.1°C) DB/60°F (15.6°C) WB, and outdoor temperature of 47°F (8.3°C) DB/43°F (6.1°C) WB. Pipe length: 25ft. (7.5m), Height difference: 0ft. (0m) (Outdoor unit - indoor unit).