

Mariposa® 66" x 36" alcove heated whirlpool, left drain K-1224-LH

Features

- Single-speed whirlpool offers performance and value, with 5 fully adjustable jets
- Hydromassage flow and direction can be controlled at each jet
- Hourglass shape adds style and elegance to your bathroom
- Built-in heater
- Integral flange helps prevent water from seeping behind wall and simplifies alcove installation
- Textured bottom surface

Material

Acrylic

Hydrotherapy

• Whirlpool

Installation

- Left drain
- Alcove

Required Products/Accessories

K-37383 Rough-in cable bath drain, PVC, 30" cable with tubing K-37385 rough-in cable drain, PVC, 45" cable K-78438 30" cable bath drain K-78439 45" cable bath drain K-T37391 Rotary-turn bath drain trim K-T37392 Rotary-turn bath drain trim

Recommended Products/Accessories

K-1601 Bath/whirlpool footstop, removable K-7213 27" Cable Bath Drain K-7214 27" Cable Bath Drain K-23726 Drain treatment K-23732 Tub & shower cleaner K-31796 Above-the-floor bath drain kit K-31798 Bath drain kit



Codes/Standards

ASME A112.19.7/CSA B45.10 CSA B45.5/IAPMO Z124 ASTM E162 ASTM E662 UL 1795 IAPMO Certification UL Listed

KOHLER® Plastic Baths and Shower Bases Lifetime Limited WarrantyKOHLER® Hydrotherapy Components Five-Year Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color Code Description

0 White





Mariposa® 66" x 36" alcove heated whirlpool, left drain K-1224-LH



Required Electrical Service

Two dedicated circuits required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI). Outside North America, this device may be known as a Residual Current Device (RCD).

Pump:	120 V, 15 A, 60 Hz
Heater [.]	120 V 15 A 60 Hz

Technical Information

All product dimensions are nominal.

Left
48" x 24" (1219 mm x 610 mm)
59" x 30" (1499 mm x 762 mm)
115 lbs (52.2 kg)
43 lbs/ft² (209.9 kg/m²)
14" (356 mm)
67 gal (253.6 L)
Pump: 120 V, 7.5 A, 60 Hz
Heater: 120 V, 12.5 A, 60 Hz, 1500 W
Single
1-15/16" (49 mm)

Notes

Measure your actual product for rough-in details.

Install this product according to the installation instructions.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

If installing a rim-mount faucet, make sure there is no interference above or below the deck before drilling any holes.

1-800-4KOHLER (1-800-456-4537)

Kohler Co. reserves the right to make revisions without notice to product specifications. For the most current Specification Sheet, go to <u>www.kohler.com</u> USA or <u>www.kohler.ca</u> Canada 8-26-2024 22:15 - US/CA

