



**Rêve®**  
67" x 31-1/2" drop-in/undermount bath  
**K-817**

### Features

- Comfort Depth® design offers a convenient and low step-over height while retaining the depth of a standard 21" bath
- Integral lumbar support on both ends
- Safeguard® slip-resistant surface provides excellent traction underfoot
- Slotted overflow allows for deep soaking
- Coordinates with other products in the Rêve collection

### Material

- KOHLER® enameled cast iron
- Painted exterior surface smoothness can vary from product to product

### Installation

- Center drain
- Drop-in or undermount

### Required Products/Accessories

K-7271 Brass Slotted Overflow Bath Drain  
or  
K-7272 PVC Slotted Overflow Bath Drain

### Recommended Products/Accessories

K-136 Bath/BubbleMassage™ Under-mount Kit  
K-1179 Vinyl Tiling-in Bead  
K-23726 Drain treatment  
K-23725 Cast iron cleaner



### Codes/Standards

ASME A112.19.1/CSA B45.2  
ASTM F462


### KOHLER® Enameled Cast Iron Bath and Shower Base Lifetime Limited Warranty


See website for detailed warranty information.

### Available Colors/Finishes

*Color tiles intended for reference only.*

Color	Code	Description
-------	------	-------------

	0	White
---	---	-------



### Technical Information

All product dimensions are nominal.

Drain location:	Center
Basin area, bottom:	49" x 22" (1245 mm x 559 mm)
Basin area, top:	62-1/2" x 24-3/4" (1588 mm x 629 mm)
Weight:	365 lbs (165.6 kg)
Minimum floor load:	78 lbs/ft² (380.8 kg/m²)
Water depth:	15-1/4" (387 mm)
Water capacity:	75 gal (283.9 L)
Cutout:	Drop-in, 65-1/2" x 30" (1664 mm x 762 mm)
Minimum flat for door:	1" (25 mm)

### Notes

Measure your actual product for rough-in details.

Install this product according to the installation instructions.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

Kit is required for undermount installations (sold separately).

To clear the overflow side bath rim, a minimum 7" (178 mm) bath spout is recommended.

To clear the end wall bath rim, a minimum 10" (254 mm) bath spout is recommended.