



SL-94-3.2MM-AL  
Aluminum Hourglass Sleeve

AG-24-44-xxx  
3/32" 7x7 Galv. Cable

ZF-25X2-HG

Cable Length (ft)	Griplock P/n
5	GH-AG24-44-X2-60
10	GH-AG24-44-X2-120
15	GH-AG24-44-X2-180
20	GH-AG24-44-X2-240

**Working Load: 160lbs**

Unless otherwise specified  
 1. Dimensions are in inches  
 2. Tolerances are:  
 .XX ±.01 .XXX ±.005 Angles 1°  
 3. Break all edges .005 min  
 4. Finish 63 micro inches  
 5. Dimensions apply after finish  
 6. Concentricity = .025 TIR

DRAWN BY: NRB  
 REV: INT  
 CHECKED BY:

**PROPRIETARY AND CONFIDENTIAL**

This drawing and these specifications are the exclusive property of GRIPLOCK SYSTEMS LLC and shall not be divulged, reproduced, copied, or used as the basis for the manufacture or sale of apparatus without the express written authorization of GRIPLOCK SYSTEMS LLC.

REF: DATE: 2/14/2023  
 MATERIAL: VARIOUS  
 SCALE: 1:1.25 FILE: GH-AG24-44-X2-xxx



**GRIPLOCK SYSTEMS**

793 Duncan Reidville Rd., Duncan, SC 29334  
 Phone (805) 566-0064

GRIPLOCK P/N: GH-AG24-44-X2-xxx

DESCRIPTION:  
 3/32" Looping Grip kit w/ Cable Loop End