

**Features**

- Handshower features contemporary design
- Three spray functions and ADA-compliant nonpositive shutoff
- Thumb tab allows for a smooth transition between sprays
- Sidebar features adjustable mounting brackets for installation flexibility
- Includes 60" (1524 mm) smooth hose
- This product can help a building earn Water Efficiency points in LEED® Green Building Rating System

**Optional Products/Accessories**

K-98350 wall-mount supply elbow

K-98351 wall-mount supply elbow with check valve

**ADA****Codes/Standards**

ASME A112.18.1/CSA B125.1

DOE - Energy Policy Act 1992

EPA WaterSense®

California Energy Commission (CEC)

ADA

ICC/ANSI A117.1

NOM Standards


NOM 008-CONAGUA

**KOHLER® Faucet Lifetime Limited Warranty**

See website for detailed warranty information.

**Available Colors/Finishes***Color tiles intended for reference only.***Color   Code   Description**

	CP	Polished Chrome
	BN	Vibrant® Brushed Nickel
	BL	Matte Black
	2MB	Vibrant® Brushed Moderne Brass



### Technical Information

All product dimensions are nominal.

#### Spout:

Handshower rated max flow: 1.75 gal/min (6.6 l/min)

#### Notes

Install this product according to the installation instructions.

Plumbing codes require approved backflow prevention devices to be installed in-line to handshowers. Please consult with local plumbing officials.

Mount the slidebar to stud framing or install backing support. For tile or other solid finish surfaces: Predrill mounting holes through surface material only; do not drill into the stud. For drywall surface: No predrill is required.

ADA compliant when installed to the specific requirements of these regulations.