



PIPE TOOLS & VISES
SINCE 1896

LIGHTEN UP!

FEED TAP™ DRILLING MACHINE

**COMPACT & LIGHTWEIGHT WITH
INDEPENDENT FEED CONTROL**

- Drills through 3/4" - 2" pressurized ductile iron, cast iron, PVC or PE
- Kits available for AWWA, NPT, and 110 Compression
- Powered by either drill or manually (manual is recommended for PVC)



- ✓ Independent, controlled feed.
The preferred tool for PVC taps.
- ✓ Manual power recommended for taps on PVC.
- ✓ Bleed-off valve flushes chips out of the line.



**VIDEO
TRAINING**





PIPE TOOLS & VISES
SINCE 1896



www.reedmfgco.com
reedsales@reedmfgco.com

FEED TAP™ KITS

Catalog No.	Item Code	Description
FTB	09160	Feed Tap Base Machine
FT2000CCI10	09161	AWWA/110 Compression Feed Tap Kit 3/4" - 2"
FT2000	09162	AWWA Feed Tap Kit 3/4" - 2"
FT2000UNIV	09165	Complete Feed Tap Kit 3/4" - 2"
FT2000CCNPT	09166	AWWA/110 Comp 3/4" - 1" and 1 1/2" - 2" NPT Feed Tap Kit
FT1000CCI10	09167	AWWA/110 Comp Feed Tap Kit 3/4" - 1"
FTP2000UNIV	09168	Feed Tap Kit 3/4" - 2" for Plastic Pipe Only
FTBB	09169	Feed Tap Main Unit, CRPD25 and TMTC6 – no case

CORPORATION ADAPTERS

Catalog No.	Item Code	Description	Weight	
			lbs	kg
FT75CCI10	09170	3/4" AWWA and 110 Comp	0.60	0.27
FT100CCI10	09171	1" AWWA and 110 Comp	0.55	0.25
FT150	09172	1 1/2" AWWA	1.20	0.55
FT150I10	09173	1 1/2" 110 Comp	1.35	0.61
FT200	09174	2" AWWA	1.40	0.64
FT200I10	09175	2" 110 Comp	1.40	0.64
FT150NPT	99109	1 1/2" NPT	0.80	0.36
FT200NPT	99112	2" NPT	0.80	0.36
FT75NPT	99117	3/4" NPT	0.45	0.20
FT100NPT	99118	1" NPT	0.45	0.20

HEAVY-DUTY SHELL CUTTERS FOR CAST/DUCTILE IRON

Catalog No.	Item Code	Shell Size	Corp. Stop Size	Cutting Depth	Weight	
					lbs	kg
Δ FTSC688	99132	1 1/16"	3/4"	1.875"	0.09	0.04
Δ FTSC875	99134	7/8"	1"	1.875"	0.15	0.07
Δ FTSCI438	99137	1 7/16"	1 1/2"	2"	0.41	0.19
Δ FTSCI750	99138	1 3/4"	2"	2"	0.57	0.26

PVC/PE SHELL CUTTERS, PL SERIES

Catalog No.	Item Code	Shell Size	Corp. Stop Size	Cut Max. Wall Thickness	Weight	
					lbs	kg
PL688	04385	1 1/16"	3/4" NPT & AWWA	1 1/8"	0.2	0.1
PL875	04386	7/8"	1" NPT & AWWA	1 1/8"	0.2	0.1
PL1438	04387	1 7/16"	1 1/2" NPT & AWWA	1 1/8"	0.5	0.2
PL1750	04392	1 3/4"	2" NPT & AWWA	1 1/8"	0.7	0.3

ACCESSORIES

Catalog No.	Item Code	Description
FTPLAA	04423	Arbor Assembly (adapter) used with 1 1/2" & 2" PVC/PE Shell Cutters, PL1438 & PL1750
FTPLSAA	94198	Coupling Nut (adapter) used with 3/4" and 1" PVC/PE Shell Cutters
CRPD25	99129	1/4" diameter Carbide Tipped Coupon Retaining Drill Bit

TAPPING COMPOUND

Catalog No.	Item Code	Description
TMTC	98425	16 oz. (.45 kg) resealable can
TMTC6	99140	6 oz. (170 g) squeezable bottle



FIELD OPERATORS SAY



"Lightweight and fast!"

"It's easy to feel when the shell cutter cuts into and through the pipe wall."

"The coupon is retained and can be inspected."



1

Assemble the unit.



2

Open corp stop valve.



3

Turn independent feed until the pilot drill touches the pipe.



4

Attach drill.



5

Make the tap, then reverse the process.



6

Inspect the coupon.

FT2000UNIV

