

▲ Designate finish suffix

# BRIZO

## **ON-WALL HAND SHOWER**

- Odin<sup>®</sup> Bath Collection
- Single-function Hand Shower

#### **FEATURES:**

• H<sub>2</sub>Okinetic<sup>®</sup> Technology

#### **STANDARD SPECIFICATIONS:**

- Max flow rate 1.75 gpm @ 80 psi, 6.6 L/min @ 550 kPa
- · Wall mount elbow included
- Integrated elbow has standard 1/2"-14 NPT supply
- · Certified dual check valves for backflow prevention
- 60-82" (1524 mm-2083 mm) stretchable finished metal
- ullet Single Spray Setting:  $H_2$ Okinetic $^{\hbox{\scriptsize $\mathbb R$}}$  Spray


#### **WARRANTY**

- Parts and Finish Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date the product is received by the original purchaser or their authorize representative (installation contractor, etc.).
- Please go to www.brizo.com for the complete details of our limited warranty.



### **COMPLIES WITH:**

- ASME A112.18.1 / CSA B125.1
  EPA WaterSense<sup>®</sup>



◆ Your Brizo hand shower incorporates a backflow protection system that has been tested to be in compliance with ASME A112.18.3 and ASME A112.18.1/CSA B125.1. It incorporates two certified check valves in series, which operate independently and are integral, non-serviceable parts of the wand assembly.