

Floor (4000 BTU) Indoor Unit
For Heat-recovery/Heat-pump Airstage VRF System

| | |
|--------------|--|
| Job Name | |
| Location | |
| Engineer | |
| Submitted To | |
| Submitted By | |
| Reference | |

| | |
|--------------|--|
| Date | |
| Approval | |
| Construction | |
| Unit No | |
| Drawing No | |

FEATURES

- Floor mount models can fit easily under most windows and replace a radiator twice its size
- Quiet and powerful airflow
- Louver auto-swing in two directions
- Auto-closing louvers
- Very low power usage
- Compatible with 2-wire remotes only
- 10 year Extended Warranty on parts and compressor. See Warranty Statement.



| PIPING ACCESSORIES | |
|--------------------|--|
| UTP-AX090A | Separation Tube - 2-Pipe - 90 MBH or Less |
| UTP-AX180A | Separation Tube - 2-Pipe - 91 to 180 MBH |
| UTP-AX567A | Separation Tube - 2-Pipe - 180 MBH or More |

| CONTROLLER | |
|------------|---|
| UTY-RNKU | Wired Remote Control |
| UTY-LNHU | Wireless Remote Controller (requires IR Receiver) |
| UTY-DCGY | Central Remote Controller (100 units) |
| UTY-DTGYZ1 | Touch Panel Controller with Internet (400 units) |

| ACCESSORIES | |
|-------------|--------------------------------|
| #N/A | #N/A |
| UTY-XSZX | Remote Sensor for ducted units |

| WEIGHT AND DIMENSIONS | |
|--|--|
| Enclosure - Net Weight - lbs [kg] | 32[14.5] |
| Enclosure - Gross Weight - lbs [kg] | 40 [18] |
| Dimensions - Net (H x W x D) - in [mm] | 23-5/8×29-1/8×7-7/8 600×740×200 |
| Dimensions - Gross (H x W x D) - in [mm] | 27-9/16×32-5/16×12-3/16 700×820×310 |

| CAPACITY | |
|---------------------------------|-------------|
| Capacity - Cooling - Btu/h [kW] | 4,000 [1.2] |
| Capacity - Heating - Btu/h [kW] | 4,400 [1.3] |

| ELECTRICAL | |
|------------------------------------|---------------------------|
| Power Source | 208 / 230V, 1-Phase, 60Hz |
| Available Voltage Range - VAC | 187 to 253 |
| Input Power - W | 0.014 |
| Full Load Amps - FLA - A | 0.17 |
| Max Circuit Breaker - A | 15 |
| Minimum Circuit Ampacity - MCA - A | 0.22 |

| FAN | |
|------------------------------------|----------------|
| Fan Type | Cross flow × 2 |
| Airflow Rate - High - CFM [m³/h] | 253 [430] |
| Airflow Rate - Medium - CFM [m³/h] | 188 [320] |
| Airflow Rate - Low - CFM [m³/h] | 165 [280] |

| SOUND PRESSURE | |
|------------------------------|----------|
| Sound Pressure Level - dB(A) | 28/31/36 |

| WIRING | |
|---------------------|--|
| Communication Cable | LonWorks (Fujitsu Pink Cable. See AE Bulletin 009) |

| PIPING | |
|---|---------------|
| Connection Pipe Diameter - Liquid (Flare) - in [mm] | ø 1/4 [6.35] |
| Connection Pipe Diameter - Gas (Flare) - in [mm] | ø 3/8 [12.70] |
| Connection Pipe Diameter - Drain (ID; OD) - in [mm] | ø9/16 (13.8) |
| Drain-Pump | Optional |

| ETL | |
|--------|-------|
| E.T.L. | 91987 |

| TEMPERATURE SETTINGS | |
|--|---------------------|
| Operating Temp. Cooling (DB) - °F [°C] | 64 to 90 [18 to 32] |
| Operating Temp. Heating (DB) - °F [°C] | 50 to 86 [10 to 30] |

Note: Specifications are based on the following conditions:
Cooling: Indoor temperature of 80°F (26.7°C) DB/67°F (19.4°C) WB, and outdoor temperature of 95°F (35°C) DB/75°F (23.9°C) WB. Heating: Indoor temperature of 70°F (21.1°C) DB/60°F (15.6°C) WB, and outdoor temperature of 47°F (8.3°C) DB/43°F (6.1°C) WB. Pipe length: 25ft. (7.5m), Height difference: 0ft. (0m) (Outdoor unit – indoor unit).



Fujitsu General America, Inc.
353 Route 46 West
Fairfield, NJ 07004
Toll Free: (888) 888-3424
Fax: (973) 836-0453
www.airstagevrf.com




Floor (4000 BTU) Indoor Unit
For Heat-recovery/Heat-pump Airstage VRF System

DIMENSIONS

Unit: In. (mm)

Front view

Bottom view



Fujitsu General America, Inc.
353 Route 46 West
Fairfield, NJ 07004
Toll Free: (888) 888-3424
Fax: (973) 836-0453
www.airstagevrf.com