



Veil® | K-18647

In-wall tank and carrier for K-76395 Veil® wall-hung smart toilet

Features

- Robust steel frame
- Insulated tank to prevent sweating
- Large flush actuator plate opening can be removed for easy access to inner tank
- Adjustable height allows bowl to be set anywhere from 15" to 23" (381 to 584 mm) from floor
- Dual-flush actuator offers a choice of 0.8 or 1.6 gpf (3.0 or 6.0 lpf)
- Requires K-76395 Veil smart wall-hung toilet (sold separately)
- Dual-flush technology allows you to choose between a full or partial flush
- Eligible for consumer rebates in some municipalities



Sustainability



Available Colors/Finishes

Color tiles intended for reference only.

NA NA Not Applicable



1-800-4KOHLER (1-800-456-4537)
Kohler Co. reserves the right to make revisions without notice to product specifications.
For the most current specification sheet, go to www.kohler.com USA or www.kohler.ca Canada.
7-03-2026 06:34 - US-CA

THE BOLD LOOK
OF **KOHLER**

Codes/Standards

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.

ADA CSA B651 OBC

ASME A112.6.2
ASME A112.19.14
ADA
ICC/ANSI A117.1
CSA B651
OBC

Technical Information

Installation Type: Wall-hung
Flush Type: Power
Flush Rate: 0.8 or 1.6 gpf (3 or 6 lpf)

Required Products/Accessories

- K-76395 Wall-hung compact elongated smart toilet bowl, dual-flush

Warranty

See website for detailed warranty information.

KOHLER® Intelligent Toilet and C3® Cleansing Seat Three-Year Limited Warranty



No image available.

This product is a component and not intended to be a standalone installation.

Installation

- Durable steel frame carrier is installed on 2" x 6" (51 x 152 mm) studs behind the wall. See installation guide and installation video for more detailed information
- When installed per Kohler installation instructions, the KOHLER in-wall tank and carrier system can support up to 500 lb (226.8 kg) without damage
- Supply line sold separately

Installation Notes

Install this product according to the installation instructions.

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.

Plumbing codes may require elongated toilets and elongated, open-front seats in public bathrooms.

Accessibility standards may require controls to be located on the open side of the toilet.

