

ICE MAKER OUTLET BOX

» 696 SERIES

OxBox™

SPECIFICATION

Sioux Chief 696 series supply OxBox™ shall be used where necessary in residential or commercial plumbing supply systems. Access box can be secured directly to vertical stud or between studs using galvanized bracket. Supply line can be installed from above or below. Arrester variations can be installed with arrester at any angle. Unit shall be available with 1/4-turn valves. Metal support bracket shall install into top/bottom tracks of box. Outlet connection shall be generally 1/4". Outlet connections should generally be provided with a test/tamper-resistant cap. Every unit shall include a debris cover for protection during rough-in. Valves will be plated.

MATERIALS

Valve body: no-lead brass¹

Valve shank: no-lead brass¹/copper/PPSU/CPVC, 304SS grip ring

Outlet box/frame: ABS

Arrester body: stainless steel, C69300 NL brass¹

Arrester piston: GFPP with EPDM o-rings

Bracket: galvanized steel

CERTIFICATIONS/APPROVALS

NSF-372 compliant, IAPMO listed box and valve, ASSE 1010 arrester*

Valve meets ASME A112.18.1

VALVE/ARRESTER WORKING LIMITS

Max working temperature: 200°F

Max air/water testing & working pressure: 150 PSIG

DIMENSIONS

A: Frame width	5 3/4"
B: Frame height	7 1/4"
C: Frame opening width	3 3/8"
D: Frame opening height	5 1/8"
E: Rough-in box inner width	4"
F: Rough-in box overall depth	3 1/2"
G: Rough-in box inner height	5 1/2"
H: Supply connection	1/2" nominal
I: Outlet connection	1/4" compression
J: Bracket length	18"


ITEM # SUBMITTED	_____
JOB NAME	_____
LOCATION	_____
ENGINEER	_____
CONTRACTOR	_____
PO#	_____ TAG _____



696-G1010XF



696-G1000WR



Create Item Number

696-G10A0B C

e.g. **696-G1010MF:** Ice maker supply box with no lead FSWT valve with arrester and frame

ARRESTER A

- 0 = No arrester
- 1 = With arrester*

SUPPLY CONNECTION B

- C = 1/2" Male CPVC
- M = 1/2" MIP/FSWT
- P = 1/2" Male sweat/press/push
- V = 1/2" Viega® PureFlow® PEX
- W = 1/2" PEX F1960 Grip™
- X = 1/2" PEX F1807/F2159 Crimp™

FRAME PACKAGING C

- F = Standard pack (supply box, frame, bracket, debris cover)
- FPK4 = Display box (supply box, frame, bracket, debris cover)
- FS = Standard pack w/6-ft. braided supply line
- R = Rough-in pack (supply box, bracket, debris cover)

Available Separately:
 696-1F: frame only
 696-SC1: frame insert w/ hose knockout
 696-EX: frame extension