



# Kingston™ | K-25100-RA

Toilet tank, 1.28 gpf

## Features

- Ideal for commercial installations
- 1.28 gpf (4.8 lpf)
- Durable metal right-hand Polished Chrome trip lever
- Combines with a K-25076 or K-25076-SS bowl to create a complete K-25077-RA or K-25077-SSRA Kingston two-piece toilet
- Class Five® canister optimizes the flow out of the tank, harnessing gravity and the natural, powerful reducing cascade of water to increase the power and effectiveness of the flush



## Sustainability



## Available Colors/Finishes

*Color tiles intended for reference only.*

0 White



1-800-4KOHLER (1-800-456-4537)  
Kohler Co. reserves the right to make revisions without notice to product specifications.  
For the most current specification sheet, go to [www.kohler.com](http://www.kohler.com) USA or [www.kohler.ca](http://www.kohler.ca) Canada.  
7-06-2026 22:07 - US-CA

THE BOLD LOOK  
OF **KOHLER**

## Codes/Standards

*Plumbing codes may require elongated toilets and elongated, open-front seats in public bathrooms.*



ASME A112.19.2/CSA B45.1

EPA WaterSense®

---

## Technical Information

Flush Type: Class Five

Flush Rate: 1.28 gpf (4.8 lpf)

---

## Recommended Products/Accessories

K-23726 Drain treatment

---

## Warranty

*See website for detailed warranty information.*

KOHLER® Toilets and Seats Limited Warranty



1-800-4KOHLER (1-800-456-4537)

Kohler Co. reserves the right to make revisions without notice to product specifications.

For the most current specification sheet, go to [www.kohler.com](http://www.kohler.com) USA or [www.kohler.ca](http://www.kohler.ca) Canada.

7-06-2026 22:07 - US-CA

No image available.

This product is a component and not intended to be a standalone installation.

## Installation

- Three-bolt quick-connect installation
  - Supply line sold separately
- 

## Installation Notes

*Install this product according to the installation instructions.*

Product dimensions are nominal and may vary per ASME A112.19.2 tolerances.

