



# PureWash® E750 | K-4108

Elongated bidet toilet seat with remote control

## Features

- In-line heater provides continuously heated water for consistent comfort
- Front and rear wash modes provide warm water for cleansing
- Adjustable water temperature and water pressure
- Choose oscillating or pulsating spray
- Touch-screen remote control with two programmable user presets
- Self-cleaning function uses UV light to automatically clean the wand surfaces
- Heated seat with adjustable temperature settings
- LED lighting illuminates the bowl to serve as a nightlight
- Warm-air drying system with adjustable temperature settings
- Carbon filter for odor control
- Quiet-Close™ elongated lid and seat prevents slamming
- Grip-Tight bumpers hold seat firmly in place
- Quick-Release™ functionality allows seat to be removed easily from toilet for convenient cleaning
- Ergonomically designed for comfortable seating
- Fits most elongated toilets
- Continuously heated water for consistent comfort
- Automatic deodorization system for odor control
- Energy-save function
- Single stainless steel wand with adjustable water pressure, temperature, and pulsate settings



## Available Colors/Finishes

*Color tiles intended for reference only.*

0 White



1-800-4KOHLER (1-800-456-4537)

Kohler Co. reserves the right to make revisions without notice to product specifications.

For the most current specification sheet, go to [www.kohler.com](http://www.kohler.com) USA or [www.kohler.ca](http://www.kohler.ca) Canada.

7-03-2026 00:00 - US-CA

THE BOLD LOOK  
OF **KOHLER**

## Codes/Standards

ASME A112.4.2/CSA B45.16  
UL 1431  
CSA C22.2 No. 64  
CSA C22.2 No. 68  
cUL Listed  
UL Listed

## Technical Information

*All product dimensions are nominal.*

|                      |                 |
|----------------------|-----------------|
| Lighting Included:   | Yes             |
| Seat Shape Type:     | Elongated       |
| Seat Front Type:     | Closed-front    |
| Seat-Mounting Holes: | 5-1/2" (139 mm) |

## Material

- Plastic construction

## Required Electrical Service

One dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI). Outside North America, this device may be known as a Residual Current Device (RCD).

|                    |                    |
|--------------------|--------------------|
| Bidet toilet seat: | 120 V, 15 A, 60 Hz |
|--------------------|--------------------|

## Electrical Component Ratings

|                    |                    |
|--------------------|--------------------|
| Bidet toilet seat: | 120 V, 15 A, 60 Hz |
| Power Cord Length: | 46" (1168 mm)      |


## Warranty

*See website for detailed warranty information.*

KOHLER® Intelligent Toilet and C3® Cleansing Seat Three-Year Limited Warranty



1-800-4KOHLER (1-800-456-4537)  
Kohler Co. reserves the right to make revisions without notice to product specifications.  
For the most current specification sheet, go to [www.kohler.com](http://www.kohler.com) USA or [www.kohler.ca](http://www.kohler.ca) Canada.  
7-03-2026 00:00 - US-CA



## Installation

- Requires dedicated electrical GFCI circuit (120 V, 15 A, 60 Hz)

## Installation Notes

*Install this product according to the installation instructions.*

Connect the seat to a cold water supply of drinking quality water at a pressure of 20 psi - 80 psi (139 kPa - 551 kPa). Do not install this seat in a location where: (1) water might be splashed on the product or (2) excessive moisture, high humidity levels, or condensation is present. This will avoid damage to the electronic components.

**CAUTION:** Risk of property damage. A single extension cord may be used provided the cord "Type" begins with "SJ", 12 gauge, grounded (12/3), no longer than 25 feet, and plugged into a GFCI outlet. Promptly replace any extension cord that exhibits any sign of damage.

To avoid possible product malfunction, do not plug in the seat until instructed to do so.

Locate the receptacle at least 6" (152 mm) above the floor, and within a 32" (813 mm) radius measured 2" (51 mm) from the bowl ledge.



1-800-4KOHLER (1-800-456-4537)

Kohler Co. reserves the right to make revisions without notice to product specifications.

For the most current specification sheet, go to [www.kohler.com](http://www.kohler.com) USA or [www.kohler.ca](http://www.kohler.ca) Canada.

7-03-2026 00:00 - US-CA