



Product Data

N-Flex R8

Corporate Office
265 Radio Road
Corona, CA 92879
Phone: 951-493-0082
Fax: 951-808-9076

N-Flex RV-8

- A Class '1' Air Duct
- Underwriters Laboratories Approval # MH16545

Performance Data

- Max Velocity: 5000 FPM
- Max Positive Pressure: 8" W.G.
- Max Negative Pressure: 2" W.G.
- 'R' Value: 8 @ 75° F.

Material Data

Aluminum:

- 3003 Alloy
 - "O" Temper
- Aluminum Coil Dry .005" x 3.75" 3003-0
Aluminum Coil Dry .0065" x 3.750" 3003-0

Insulation:

- 3" Thick Blanket of Fiberglass Insulation, Factory Installed.

Vapor Barrier:

- Metalized Jacket Lay Flat.
- Flame Spread 25 or Less.
- Smoke Developed 50 Or Less.

Collars:

- Collars Both Ends, Male & Female, with Mechanical Locks
- 30 Gauge Galvanized Prime G-60 Material
- Collars attached with Galvanized Staples



Standard Features:

- Fabricated From Prime Aluminum Alloy
- 6ft Standard Length With Male & Female Collars (5064)
- 7.5ft Standard Length With Male & Female Collars (5069)
- Sealed Male & Female Locking Collars
- Sizes 04" to 20" UL Approved

☐ **Approved As Is**

Customer Signature: _____

☐ **Approved As Corrected**

Customer Signature: _____

*****Production cannot begin until an approved drawing is received by ADP from customer*****