


POLYKEN® 558CA

Premium UL 181B-FX Listed Duct Tape - CEC Approved



Backing: Printed Polyethylene Coated Cloth

Adhesive: Specially-Formulated Rubber

Liner: N/A

Colors: Metallic (Printed)

Specifications: UL 181B-FX Listed
CEC Approved

Standard Sizes: 48mm x 55M, 72mm x 55M

Applications

- A superior closure system for use on UL Listed flexible, non-metallic air duct
- Challenging bonding, protecting, bundling, and repair applications

Features & Benefits

- High strength PE Coated Cloth Backing
- Aggressive Natural Rubber Adhesive
- UL 181B-FX Listed
- Low VOC Content
- Tough and durable
- Conformable to wrap ducts for an effective seal
- 30 Year performance life
- Excellent bond to sheet metal and other surfaces
- High strength for long-term air tight seals
- Resistant to moisture and mold growth
- Meets code requirements and can contribute toward requirements for EA Credit 1 (Optimize Energy Performance) under LEED®
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	14.0 mils	0.356 mm	ASTM D-1000
Adhesion to Steel	40 oz/in	4.38 N/cm	PSTC-101
Adhesion to Backing	25 oz/in	2.74 N/cm	PSTC-101
Tensile Strength	50 lb/in	87.56 N/cm	ASTM D-1000
Operating Temperature	40 to 200 °F	4 to 93 °C	
VOC Content	<1 g/L		

Recommended Storage Conditions: 60-80 °F at 40-60% RH

Standard Shelf Life (at 25 °C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.