

C	SMITH® JAY R. SMITH MFG. CO.® DIVISION OF SMITH INDUSTRIES, INC. POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 334-272-7396 www.jrsmith.com MEMBER OF: MEMBER OF: MEMBER OF:					LOCATION	
	SOLIDS INTERCEPTORS						
	SUSPENDED TYPE						
	FUNCTION: Compact design makes this unit particularly adaptable for use directly under the fixture in place of the regular "P" trap. Unit will intercept all types of solids and precious metals. Interceptor is cleaned and inspected by removing bottom sediment strainer plate and dropping entire assembly. Fig. 8730T A (Pipe Size) = 0150 (40) or 02 (50) NOTE: Allow 8 1/2" (215) below interceptor for removal of strainer. NOTE: It is the responsibility of the installer to check all parts (internal and external) to verify they are in their proper operating order and location. REGULARLY FURNISHED: White Duco Coated Cast Iron Body and Aluminum Strainer with Removable Stainless Steel Screens. OPTIONAL MATERIALS: Acid Resistant Coating Inside - ARI Acid Resistant Coating Outside - ARO Acid Resistant Coating Inside and Outside - ARI0 Aluminum Body -AA All ABS (Specify Fig. 8730-ABS)						
TYPICAL INSTALLATION							
SUSPENDED TYPE INSTALLATION							
NOTE: Dimensions shown in parentheses are in millimeters.							

8730	FIGURE NUMBER	C B A	7-11-03 3-14-96 9-14-94	Revised Optional Materials Added Millimeters Submittal Update	RN EMB CMB	CL BS BS	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER 8730
	REV.	DATE	DESCRIPTION			BY	CKD. BY		