



1/2 in. SWIVEL-LOK® Series, Type B Liquidtight Multi-Position Connector

By RACO
Catalog # 4732

1/2 in. SWIVEL-LOK®, Type B Liquidtight Multi-Position
Connector

Features

- All gray nonmetallic construction provides superior corrosion resistance
- Each connector is supplied with a Neoprene O-ring and nylon gasket
- SWIVEL-LOK, multi-position connector (trade sizes 3/8 in. to 1 in.) twists from 0° to 90°, easing installation in difficult locations and eliminating need to stock other angle connectors
- UPC bar coded fittings are individually polybagged with a preprinted UPC-A bar code and packaged in pre-scored tear top cartons for an attractive presentation
- Additional sizes available

Application

For use in dry or wet locations when the conduit and fittings are not subject to physical damage;Use Type B conduit and fittings whenever flexibility is required for installation, operation, or maintenance

Specifications

Certified Listed	• UL Listed • CSA Certified
Environmental Conditions	Wet Location
Industry Standard(s)	UL 514B
Nema Rating	NEMA 4X, 12 and 13
Buy America(n) Qualified	Contact Manufacturer



Configuration

Connector Type	SWIVEL-LOK
----------------	------------

Dimensions

Trade Size	1/2 in
Length	3.27 in
Width	1.3 in
Weight	0.1 lb.
Height	1.3 in
Dimensions	3.27 in x 1.3 in x 1.3 in

General

Fitting Type	Connectors
Series	SWIVEL-LOK® Series
Conduit Type	Liquidtight
Material	Nylon
UPC	050169947326

Logistics

Minimum Pack Quantity	25
Carton Quantity	25
Pallet Quantity	7200

Product Assets

- [Catalog \[English\]](#)
[Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Catalog Page \[English\]](#)