INSTALLATION

Tools:


Adjustable Wrench


Plumbers Putty


Sealant Tape


Rags

OLYMPIA FAUCETS, INC.
Interchange City Distribution Center #20
1277 Heil Quaker Boulevard
La Vergne, TN 37086
(888) 772-7701
www.olympiafaucets.com


Model Number: L-7570, L-7572




Warnings and Notes:
Check with local plumbing code requirements before installation.
This product should be installed by a local listed plumber.
Do not use plumbers putty on threads.

Installation Steps:


Two Handle Lavatory Faucet




(1) Shut off water supplies. Remove old faucet. Clean mounting surface in preparation for new faucet.



(2) Place the faucet in position on the sink. Apply plumbers putty under the base gasket. Install washer on shanks and tighten with locknut from under the sink




(3) When using stainless steel braided faucet supply hose, this faucet requires one end of the supply hose to have a 1/2" female IPS connection. The other end of this supply hose must match the thread on the water supply valve under your sink. Once you've identified the required size, carefully follow the manufacturer's installation instructions for each hose.




(4) Turn on water supplies. Check for any minor joint leaks. Remove aerator from spout by turning counterclockwise. Turn on both side handles. Flush and allow water to run at full flow at least one minute. Turn off both side handles. Replace aerator.


Pop-up Drain Installation:




(1) Remove pop-up flange from body




(2) Place a ring of putty on the bottom of flange.




(3) Insert pop-up flange through drain hole and attach flange to body. Ensure the pop-up outlet faces towards the sink. Do not overtighten.




(4) Remove the excess putty. Connect the trap (check manufacturer's instructions for installation).



(5) Remove pivot rod nut from pop-up body, ensure the washers is in place, insert pivot rod, tighten pivot rod nut back to pop-up body.



(6) Push pivot rod down, insert drain plug carefully. Test to ensure drain plug works properly.




(7) Connect lift rod strap to pivot rod by using clip. Tighten the thumbscrew to connect lift rod strap to pop-up lift rod.

Exploded Drawing:

* Note: Please specify finish/color when ordering.

	ITEM #	DESCRIPTION
A	OP-190015C,H*	Lever Handle-Cold, Hot
B	OP-450002	Bonnet Nut
C	OP-430029	Gasket
D	OP-330002C,H	Ceramic Disc Cartridge-Cold,Hot
E	OP-490065*	1.2 GPM Aerator
F	OP-450005	Base Gasket
G	OP-590003	Mounting Kit
H	OP-590001	Supply Nut
I	OP-630004*	50/50 Pop-Up Drain Assembly (For L-7570)
J	OP-630002*	Brass Pop-Up Drain Assembly (For L-7572)
1	OP-490029	3/32” Allen Screw



OLYMPIA

For more care information or trouble shooting inquiries about your Olympia product, Please call:
OLYMPIA FAUCETS, INC. (888) 772-7701
Monday-Friday 8AM to 8PM EST (5AM to 5PM PST)
www.olympiafaucets.com