



OLYMPIA FAUCETS, INC.

Interchange City Distribution Center #20
1277 Heil Quaker Boulevard
La Vergne, TN 37086
(888) 772-7701
www.olympiafaucets.com

Model Number: L-6160, L-6161, L-6161G, L-6162,
L-6164, L-6170, L-6172, L-6174

Warnings and Notes:

Check with local plumbing code requirements before installation.
This product should be installed by a local listed plumber.
Do not use plumbers putty on threads.

INSTALLATION

Tools:



Adjustable Wrench



Plumbers Putty



Teflon Tape




Rags




Installation Steps:


Single Handle Lavatory Faucet



(1) Shut off water supplies. Remove old faucet. Clean mounting surface in preparation for new faucet.



(2) Place the faucet in position on the sink. Place washer and tighten with locknut.




(3) When using stainless steel braided faucet supply hose, this faucet requires one end of the supply hose to have a 1/2" female IPS connection. The other end of this supply hose must match the thread on the water supply valve under your sink. Once you've identified the required size, carefully follow the manufacturer's installation instructions for each hose.




(4) Important: After installation is complete, remove aerator. Turn water supply on and allow both hot and cold water to run at least one minute each. While water is running, check for leaks. Turn off water and replace aerator.


Pop-up Drain Installation:




(1) Remove pop-up flange from body




(2) Place a ring of putty on the bottom of flange.




(3) Insert pop-up flange through drain hole and attach flange to body. Ensure the pop-up outlet faces towards the back of the sink. Tighten the locknut securely with a wrench. Do not overtighten.




(4) Remove the excess putty. Connect the trap (check manufacturer's instructions for installation).



(5) Remove pivot rod nut from pop-up body, ensure the washers are in place, insert pivot rod, tighten pivot rod nut back to pop-up body.



(6) Push pivot rod down, insert drain plug carefully. Test to ensure drain plug works properly.




(7) Connect lift rod strap to pivot rod by using clip. Tighten the thumbscrew to connect lift rod strap to pop-up lift rod.

Exploded Drawing:

* Note: Please specify finish/color when ordering.

	ITEM #	DESCRIPTION
A1	OP-190001*	Metal Lever Handle (For L-616X)
A2	OP-190002*	Metal Loop Handle (For L-617X)
B	OP-490003*	Cap & Adjusting Ring
C	OP-490004	Cam & Washer
D	OP-390001	Stainless Steel Ball
E	OP-490041	Springs & Seats
F	OP-490064*	1.2 GPM Aerator
G	OP-430010	Hole Cover (For L-61X4)
H	OP-530001	Mounting Kit
I	OP-590001	Supply Nut
J	OP-630004*	50/50 Pop-Up Drain Assembly (For L-61X0)
K	OP-630002*	Brass Pop-Up Drain Assembly (For L-61X2)
L	OP-630001	Brass Grid Strainer Drain Assembly (For L-6161G)
1	OP-490002	Hot & Cold Indicator
2	OP-490043	Allen Screw



OLYMPIA

For more care information or trouble shooting inquiries
about your Olympia product, Please call:
OLYMPIA FAUCETS, INC. (888) 772-7701
Monday-Friday 8AM to 8PM EST (5AM to 5PM PST)
www.olympiafaucets.com

NS006