ProPEX® Stop Valve


Submittal Information
Revision A: April 21, 2008

Project Information


Job Name:	
Location:	Part No. Ordered:
Engineer:	Date Submitted:
Contractor:	Submitted By:
Manufacturer's Representative:	Approved By:

Technical Data

Material:	CA 360 Brass
Maximum Temperature (no pressure):	250°F (121°C)
Maximum Working Pressure:	250 psi



Q4885038



Q4895038

Product Information and Application Use

The chrome-plated ProPEX® Stop Valve is available in either angle- or straight-stop configurations.[1] These stop valves are used for point-of-use shut-off at the fixture. Both valves connect ½" Wirsbo AQUAPEX® tubing to ⅜" o.d. risers. The valves are full-port and feature a quarter-turn shut-off. Compression inserts and rings for the ⅜" riser connections are included with the valves.

✓	Description	Part Number	A	B	C	Weight
☐	ProPEX Straight Stop Valve for ½" PEX	Q4885038	2.47"	1.63"	$^{9}/_{16}$-24 UNEF-2A Thread	0.30 lbs.
☐	ProPEX Angle Stop Valve for ½" PEX	Q4895038	2.75"	1.49"	$^{9}/_{16}$-24 UNEF-2A Thread	0.30 lbs.

Installation

Install valve according to local building code. Do not dismantle. Refer to the AQUAPEX Professional Plumbing Installation Handbook.

Standards

CSA B137.5 and B125; ASTM F877; ASTM F1960; ASME A112.18.1

Codes

IPC; UPC; NSPC; NPC of Canada

Listings

IAPMO 3960; NSF 61- and 9-certified

Related Applications

PEX-a Plumbing Systems

Contact Information

Uponor, Inc.
5925 148th Street West
Apple Valley, MN 55124 USA
Phone: (800) 321-4739
Fax: (952) 891-2008
www.uponor-usa.com

Uponor Ltd.
655 Park Street
Regina, SK S4N 5N1 CANADA
Phone: (888) 994-7726
Fax: (800) 638-9517
www.uponor.ca

[1]ProPEX® is a registered trademark of Uponor, Inc. ProPEX™ is a trademark of Uponor Ltd.