
Product Specifications

1/4'' Flip Toggle Anchor Kit w/ Pan Head Combo Drive Screws

Part Number FTG14
Category Number 4740
UPC 781002854517

The Flip Toggle Anchor is a single piece, nylon body anchor with a metal tilting head ideal for use in drywall, plaster and hollow wall concrete blocks. It's unique tilting mechanism ensures a trouble-free installation that yields twice the strength of a regular toggle bolt of the same bolt diameter.



Physical Characteristics

Anchor Type	Flip Toggle
Drive Type	Phillips/Slotted
Head Type	Pan
Screw Size	1/4"-20 x 2-1/2"
Anchor Diameter	1/4"
Thread Per Inch	20

Packaging Details

Number of Pieces	10
Kit Contains	(10) Flip Toggle Anchors, (10) 1/4"-20 x 2-1/2" Pan Phillips/Slotted Machine Screw
Standard Qty	1
Master Qty	10
Price Per	1
Package Length	9.60
Package Width	3.50
Package Height	1.50
Net Weight	0.68
Package Weight	.68

Performance Data

Tension Strength	1/2" Drywall: 148 lb, 5/8" Drywall: 240 lb, Hollow Concrete Block: 1070 lb
Safe Tension Load	1/2" Drywall: 74 lb, 5/8" Drywall: 120 lb, Hollow Concrete Block: 535 lb
Shear Strength	1/2" Drywall: 274 lb, 5/8" Drywall: 418 lb, Hollow Concrete Block: 870 lb
Grip Range	1/2" to 2-1/8"
Pre-Drill Size	1/2"
Applications	Drywall, Hollow Block, Walls, and Ceilings
Special Features	Twice as Strong as Toggle Bolt, Fast and Easy Installation, Suitable for Overhead Applications, One Strap Design, Only Requires 1/2" Hole, Used with Any Bolt Length up to 3-3/4"

Certifications

UNSPSC	31162814
RoHS Compliant	Yes