

TRUELINE™

HVAC & WATER HEATER PARTS AND ACCESSORIES

85-B32

SPRAY TYPE **LEAK REACTANT** BLUE LEAK DETECTOR


- Clings to vertical surfaces
- Maximum bubble action & longevity

CAUTION: KEEP OUT OF REACH OF CHILDREN. SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY AND FIRST AID STATEMENTS

NET CONTENTS 32 FL. OZ. (946 mL)



85-B32



6 62766 121506 9

- Spray-Type

- Clings to Vertical Surfaces
- Maximum Bubble Action & Longevity

Use to pinpoint both tiny, slow leaks and larger, fast leaks from pressurized air gas systems. Tiny leaks result in large bubbles or cocoons of foam. Larger leaks are indicated by a stream of bubbles. Excellent cohesion—clings to vertical surfaces and the underside of pipes for fast, accurate detection of even the smallest leak.

DIRECTIONS FOR USE: Adjust spray nozzle to desired spray pattern. Spray and coat all surfaces suspect of leakage. Within seconds, bubbles or foam will pinpoint any leakage. Respray as necessary.

85-B32

WARNING: Causes mild skin irritation. Causes serious eye irritation. KEEP OUT OF REACH OF CHILDREN.



PRECAUTIONS: Wash face, hands, and any exposed skin thoroughly after handling. Wear eye and face protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If skin irritation occurs: Get medical advice/attention.

Dispose of contents and container in accordance with all local, regional, and national regulations.

Contains [CAS]: Propylene glycol [57-55-6], ammonium laureth sulfate [67762-19-0].

Distributed by: Rheem Parts Division, Randleman, NC

Made in U.S.A.
North American Research Corp.,
PO Box 1318, Lewisville, TX 75067
800-527-7520 • 972-492-1800