



# RS Retrofit Retainer Strap – RS06



- Ideal for both new and existing applications
- Can be installed without disassembly of the hanging system and/or removing the clamp
- Compatible with all standard nVent CADDY beam clamps and can be secured to either the set screw or threaded rod
- Large teardrop-shaped opening is compatible with multiple threaded rod diameters, reducing inventory by 50%
- Coined edge on teardrop-shaped opening locks into rod, eliminating shifting during install
- Provides a secure attachment in seismic zones and complies with NFPA® requirements
- Meets the UL® load test for retainer straps (3/8" and 1/2" rod sizes)



|                             |                              |
|-----------------------------|------------------------------|
| Part Number                 | RS06                         |
| Material                    | Steel                        |
| Finish                      | Pregalvanized                |
| Length (L)                  | 6 1/2"                       |
| Width (W)                   | 1 3/4"                       |
| Thickness (T)               | 16 GA                        |
| Rod Size (RS)               | 3/8"<br>1/2"<br>5/8"<br>3/4" |
| Hole Size (HS)              | 1 1/8"                       |
| A                           | 3 1/4"                       |
| Certifications              | cULus                        |
| Standard Packaging Quantity | 100 pc                       |
| UPC                         | 78285695511                  |

Add 2" to width of flange to determine minimum length strap required.

NFPA is a registered trademark of National Fire Protection Association, Inc. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

**WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.erico.com](http://www.erico.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent 's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2020 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.

