

- Heavy-gauge galvanized steel cabinet to resist weather and impact
- One-piece bottom pan for leak-proof operation and low maintenance
- Unique bolted construction for easy interior access
- Includes 1-year limited warranty on parts
- Bottom pan includes 12-year limited warranty against leakage due to rust-through
- Built in the USA from domestic and imported components

WINDOW UNITS

- UL Listed
- Fully assembled with motor mounted and tested before shipment
- Convertible grille kits available, designed to fit a variety of window shapes (not available on WCM28)
- Leveling legs included for added support and easy installation

DUCTED UNITS

- UL Classified
- Side and down discharge unit options
- Convenient junction box for easy motor and pump connection
- Motor sold separately

¡HOLA! ¿Buscas especificaciones en Español?



ESCANEE ESTE



COOLING EFFICIENCY BY ZONE



- ZONE 1**
VERY HIGH EFFICIENCY
- ZONE 2**
HIGH EFFICIENCY
- ZONE 3**
MODERATE EFFICIENCY

WINDOW UNITS

	WCM28	RWC35*	RWC44*	RWC46*	RWC50*
CABINET DIMENSIONS					
HEIGHT	27"	30 1/2"	34 1/2"	34 1/2"	34 1/2"
WIDTH	24"	31 1/2"	34 1/8"	34 1/8"	34 1/8"
DEPTH	17"	21"	28 1/2"	34 1/8"	34 1/8"
TUNNEL DIMENSIONS					
HEIGHT	11 29/32"	14 7/8"	14 7/8"	14 7/8"	14 7/8"
WIDTH	22 1/8"	21 3/4"	21 3/4"	21 3/4"	21 3/4"
DEPTH	13 5/16"	12 11/16"	12 11/16"	12 11/16"	12 11/16"
COOLS UP TO (SQ. FT.) ¹					
ZONE 1	600	900	1100	1400	1600
ZONE 2	500	700	900	1100	1200
ZONE 3	400	500	600	700	800

*UNIT WITH REMOTE CONTROL

DUCTED UNITS

	3000 DD/SD	4001 DD/SD	5000 DD	5000SD
CABINET DIMENSIONS				
HEIGHT	33 7/16"	34 1/2"	42 7/16"	42 7/16"
WIDTH	28 1/8"	34 1/8"	39"	39"
DEPTH	28 1/8"	34 1/8"	39"	39"
DUCT OPENING DIMENSIONS				
HEIGHT	13 5/8"	17 3/4"	19 3/4"	20 1/16" 19 3/4" w/adapter ²
WIDTH	13 5/8"	17 3/4"	19 3/4"	19 3/4"
DEPTH	-	-	-	-
COOLS UP TO (SQ. FT.) ¹				
ZONE 1	1100	1800	2400	2300
ZONE 2	800	1400	1800	1800
ZONE 3	600	900	1200	1200

1. COOLING ESTIMATES BASED ON LARGER MOTORS. 2. ADAPTER AVAILABLE UPON REQUEST.

CUBIC FEET PER MINUTE

SIDE DISCHARGE	INCHES STATIC PRESSURE							DOWN DISCHARGE	INCHES STATIC PRESSURE						
	0	0.1	0.2	0.3	0.4	0.5	0		0.1	0.2	0.3	0.4	0.5		
3000 SD	13 HP	2077	1950	1760	1700	1550	NR	3000 DD	13 HP	2175	2060	1970	1810	1650	1520
4001 SD	13 HP	2973	2726	2550	2230	NR	NR	4001 DD	1/3 HP	3077	2880	2565	2240	NR	NR
4001 SD	12 HP	3432	3230	3000	2775	2140	1475	4001 DD	12 HP	3654	3430	3230	3064	2498	2010
5000 SD	12 HP	4190	3910	3650	3330	2900	NR	5000 DD	12 HP	4334	4000	3620	3300	2610	2170
5000 SD	34 HP	4734	4600	4320	4060	3810	3630	5000 DD	34 HP	4983	4780	4530	4280	4020	3780