Square two-function handshower, 1.75 gpm **K-21336-G**



Features

- Multifunction handshower offers full coverage and targeted massage spray settings
- Ergonomic design is comfortable and easy to grip
- MasterClean[™] sprayface features an easy-to-clean surface that withstands mineral buildup and maximizes spray performance
- 1.75 gpm (6.6 lpm) flow rate.
- Contains flow-regulating check valve for backflow prevention
- This product can help a building earn Water Efficiency points in LEED® Green Building Rating System



K-8593 72" Shower Hose K-9069 25" slidebar

or

K-9069 25" slidebar K-9514 60" Shower Hose

or

K-14791 wall-mount handshower holder with supply elbow K-8593 72" Shower Hose

OI

K-14791 wall-mount handshower holder with supply elbow K-9514 60" Shower Hose

Optional Products/Accessories

K-9660 Vacuum Breaker





Codes/Standards

ASME A112.18.1/CSA B125.1 DOE - Energy Policy Act 1992 EPA WaterSense® California Energy Commission (CEC) OBC NOM Standards NOM 008-CONAGUA

KOHLER® Faucet Lifetime Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.


Color	Code	Description
	CP	Polished Chrome
	SN	Vibrant® Polished Nickel
	AF	Vibrant® French Gold
	BN	Vibrant® Brushed Nickel
	BV	Vibrant® Brushed Bronze
	BL	Matte Black
	2MB	Vibrant® Brushed Moderne Brass
	TT	Vibrant Titanium
	BGP	Vibrant Brushed Graphite
	D.D.	D D





Square two-function handshower, 1.75 gpm

K-21336-G



Technical Information

All product dimensions are nominal.

Spout:

Handshower rated max flow: 1

KOHLER, Faucets

1.75 gal/min (6.6 l/min)

Notes

For use with automatic compensating valves rated at 1.5 gal/min (5.7 l/min) or less.

Install this product according to the installation instructions.

Plumbing codes may require that a vacuum breaker be installed in-line to handshowers. Please consult local plumbing codes.

OBC compliant when installed to the specific requirements of these regulations.

